

MCX A17 Essential MCU Arm® Cortex® M33 with 180 MHz and Rich Serial Peripherals

MCX-A17

NEW

Preproduction

本页介绍的产品处于样品阶段。此处的产品技术规格和信息如有变更，恕不另行通知。如需了解更多信息和样品供货情况，请联系恩智浦 支持服务或恩智浦当地销售人员。

Last Updated: Jan 7, 2026


The MCX A17 family is optimized for motor control applications, delivering high performance and advanced integration. These devices operate at up to 180#MHz and feature two FlexPWM modules with four submodules each, enhanced by AOI logic for sophisticated motor control. They also include up to two ADCs, SmartDMA for efficient data handling, and a rich set of serial interfaces such as I3C, CAN FD, USB, and FlexIO.

The MCX A175 and A176 provide up to 1#MB of Flash and 256#KB of RAM, while the MCX A173 and A174 offer up to 256#KB of Flash and 64#KB of RAM, giving developers flexibility to match application needs. All MCX A17 devices are supported by the MCUXpresso Developer Experience, which provides a comprehensive suite of tools and resources to simplify development and accelerate time-to-market.

MCX A173 and A174 Block Diagram



MCX A175 and A176 Block Diagram



View additional information for [MCX A17 Essential MCU Arm® Cortex® M33 with 180 MHz and Rich Serial Peripherals](#).

Note: The information on this document is subject to change without notice.

www.nxp.com

NXP and the NXP logo are trademarks of NXP B.V. All other product or service names are the property of their respective owners. The related technology may be protected by any or all of patents, copyrights, designs and trade secrets. All rights reserved. © 2026 NXP B.V.