

AN11115

USB Audio and USB CDC with FFT for LPC11U14

Rev. 1 — 1 October 2011

Application note

Document information

Info	Content
Keywords	LPC11U14, LPC11U1X, LPCXpresso, ARM Cortex-M0, USB Audio, USB CDC, FFT, AN11115
Abstract	This document describes a sample project created to demonstrate the LPC11U14F for LPCXpresso. This project demonstrates USB audio and USB CDC with FFT capabilities on NXP ARM Cortex-M0 LPC11U family devices. The development platform used was LPCXpresso.



Revision history

Rev	Date	Description
1	20111001	Initial version.

Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

1. Introduction

The LPC11U14 is an ARM Cortex-M0 based, low-cost 32-bit MCU, designed for 8/16-bit microcontroller applications, offering performance, low power, simple instruction set and memory addressing together with reduced code size compared to existing 8/16-bit architectures.

The peripheral complement of the LPC11U14 includes 32 kB of flash memory, 6 kB of SRAM data memory, one Fast-mode Plus I²C-bus interface, one RS-485/EIA-485 USART with support for synchronous mode and smart card interface, two SSP interfaces, four general purpose counter/timers, a 10-bit ADC, and up to 40 general purpose I/O pins.

This application note describes demonstration software that uses the hardware resources on the MCU such as the ARM core, IRQ handler, USB illustrating how it can handle complex processing like Fast Fourier Transforms (FFT) and events like Timer IRQ, and USB traffic, very efficiently.

This application note describes the following:

- System setup required to demonstrate the software
- Block diagram/overview of the setup
- Functional description of the system
- FFT algorithm
- System performance
- Applications
- A guide to setup the demonstration
- Conclusion

2. System setup

This demonstration requires an LPC11U14 LPCXpresso board. [Fig 1](#) shows the system setup. Note that LPC11U14 Keil and IAR boards will also support the application.




Fig 1. System setup

3. Block diagram




Fig 2. Block diagram

3.1 Functional description

- The target board receives 16-bit audio data from PC through USB Audio Class
- Performs Fast Cosine Transform (FCT) a derivative of Fast Fourier Transform (FFT) that transforms the audio data to its respective frequency components
- Sends the result to PC via USB CDC (VCOM)


3.2 Technical specification

- Audio : 16-bit 32 samples/s
- FFT Algorithm : 16-bit Fast Cosine Transform 64 points
- VCOM: 115.2 kbps

4. Functional description

4.1 Data flow

[Fig 3](#) shows the data flow of the system back to the PC.



The various steps involved in this process are:


- 16-bit Pulse Code Modulated (PCM) audio data is sent via USB Audio Class @32 samples/s
- FFT operation of 64 samples of audio data available in the buffer is performed every 64 ms

4.1.1 The 64 points FFT result (8-bit data) is sent via USB CDC (Bulk)

[Fig 4](#) depicts the time frame in which the LPC1114 performs FFT on the audio samples from the buffer and the resulting FFT data is sent back to the PC using Bulk data transfer mode.

The USB IRQ handler receives 32 samples of audio data every millisecond from the PC and interrupts each time. FFT is performed on the received audio data after 64ms or 64th USB IRQ (1st, 64th, 128th and so on).

Later, the 8-bit FFT data is sent back to the PC over USB CDC.



Processing time and workload:

- **FFT calculation:** The LPC1114 MCU requires 700 μ s to compute the FFT of the data from the buffer. Since the FFT is performed on the audio data every 64 ms, the load on the processor is $700 \mu\text{s}/64 \text{ ms} = 1.09 \%$
- **USB data transfer:** The USB receives audio data from PC @ 32 samples/s. It receives 32 samples every millisecond and requires 10 μ s to handle the samples and generate a USB IRQ. Thus the USB Data transfer workload on the processor is $10 \text{ ms/s} = 1.00 \%$

[Table 1](#) depicts that the processing time results in a very small CPU workload. This implies more complex applications are easily viable on the MCU.

Table 1. Processing time and workload

Function	Amount (times)	Processing time (us)	Total time (us)	Load
USB data transfer	64	10	640	1.00 %
FFT	1	700	700	1.09 %

[Table 2](#) depicts the Code Size and memory requirements of the program when compiled without optimization.

Table 2. Code size

Category	Size (bytes)
Code	16,296
Data	532
Workspace	2,064
Total code	18,892

5. Fast Fourier Transform (FFT) algorithm

The LPC11U14 implements a 64 point Fast Cosine Transform (derivation of DCT) to perform the FFT. Fig 5 shows the FFT algorithm and Fig 6 depicts procedure of the algorithm used.

A more detailed explanation of the algorithm can be found in wikipedia: (http://en.wikipedia.org/wiki/Discrete_cosine_transform).




Fig 5. FFT algorithm




Fig 6. Procedure of the FFT algorithm

6. Applications

The strong computing capability of the LPC11U14 MCU provides the user with wide application choices. This demo software utilizes a few of such applications.

The possible applications of this demo software could be:

- Spectrum analyzer
- Frequency based audio data compression
- High frequency component detection

The LPC11U14 MCU as a USB Audio class and USB CDC could be used for similar applications as mentioned above, such as utilizing the USB CDC as a speaker.

7. Application demonstration

7.1 Requirements

7.1.1 Hardware

LPCXpresso LPC11U14

7.1.2 Software

LPCXpresso IDE Version 4.0 or later.


The download link for the software can be found at:

<http://lpcxpresso.code-red-tech.com/LPCXpresso/> (registration is required for download).

A detailed description on how to get started, importing, and compiling projects in the LPCXpresso IDE can be found at:

<http://ics.nxp.com/support/documents/microcontrollers/pdf/lpcxpresso.getting.started.pdf>

7.2 Compile and flashing

1. Copy project files LPCXpresso11U14F_usbaudiowithFFT_usbdc and CMSISv2p00_LPC11xx to your workspace directory.
(CD://USB Audio FFT/LPC11DemoSoftware-LPCXpresso/)
2. Import the project file using LPCXpresso (as shown in [Fig 7](#))
3. Connect LPCXpresso LPC11U14 Target board J3 and J8 to PC's USB port using two separate USB cables
4. Compile and flash to board
 - a. Select the project LPCXpresso11U14_usbaudiowithFFT_usbdc at the Project Explorer Panel
 - b. Compile :Project → Build Project
 - c. Program flash: Click 
 - d. Select file: LPCXpresso1114_usbaudiowithFFT_usbdc\Debug\LPCXpresso1114_usbaudiowithFFT_usbdc.axf (as shown in [Fig 8](#))
 - e. Click OK
 - f. Recycle power to J3 (LPC-Link)




Fig 7. Importing project




Fig 8. Program flash

7.3 Install USB drivers

1. Make sure the USB cable between PC and LPC11U14F Target Board J8 is connected

Note: Jumpers SJ1 & J7 must be closed for the Target Board to be powered by USB connector J8 alone (as shown in [Fig 9](#)). Otherwise, the target must be powered by connecting J3 to the PC.




Fig 9. SJ1 Jumper settings

2. A pop-up notifies that two USB devices were recognized:

- a. NXP LPC VCOM device
 - Select Install from a list or specific location (Advanced)
 - Browse to directory which contains file LPC11xx_vcom.win32

(CD://USB Audio FFT/LPC11DemoSoftware-LPCXpresso/WinXP_Win7-32bit_usb_driver)

- Click Next
 - b. NXP Speaker will be automatically detected as USB audio class
3. Check the VCOM number
- a. Open Control Panel → System → Hardware → Device Manager
 - b. Check Port: e.g., NXP LPC Vcom Device (COM3) → COM3 (as shown in [Fig 10](#)).




Fig 10. Selecting COM port

7.4 FFT Demo

Run the USB Audio FFT Demo.

1. Open the FFTDemo.exe by clicking on the FFTDemo icon (The GUI program has been included in the Application Note zip file)
2. Run the demo by setting the COM # of VCOM and click Start to open the serial communication

Note:

1. Click Stop to stop the communication
2. Click Exit to exit the FFT demo

[Fig 11](#) shows the FFTDemo.exe screenshot





Fig 11. FFTDemo.exe

7.5 Play audio on a player

1. Run the audio player and play some music or a sound file
2. Observe the spectrum shown in the FFT Demo's display when the audio is played on the music player, as shown in [Fig 12](#).
3. Example of sound (dir: DemoSound/)
 - sweeplin.wav: run the sound from low to high frequency
 - sin500.wav: run sine wave 500 Hz
 - sin300_2000.wav: run sine wave 300&2000 Hz and observe the frequency spectrum on the GUI.
4. Audacity (<http://audacity.sourceforge.net/>) also lets the user generate various types of tones. This video <http://youtu.be/8GgGyOqgbyE> shows how to generate various audio tones using Audacity.



8. Conclusion

This application note described demonstration software that was developed to highlight the capabilities of the NXP LPC11U14 MCU. The USB audio and USB CDC sample software with FFT demonstrates the processing capability of the ARM Cortex-M0 powered NXP LPC11U14 MCU.

The successful demonstration of the sample software shows that the LPC11U14 MCU can handle quite complex processing like FFT requiring very little memory with only a very small burden on the CPU.

9. Legal information

9.1 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

9.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned

application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Evaluation products — This product is provided on an "as is" and "with all faults" basis for evaluation purposes only. NXP Semiconductors, its affiliates and their suppliers expressly disclaim all warranties, whether express, implied or statutory, including but not limited to the implied warranties of non-infringement, merchantability and fitness for a particular purpose. The entire risk as to the quality, or arising out of the use or performance, of this product remains with customer.

In no event shall NXP Semiconductors, its affiliates or their suppliers be liable to customer for any special, indirect, consequential, punitive or incidental damages (including without limitation damages for loss of business, business interruption, loss of use, loss of data or information, and the like) arising out of the use of or inability to use the product, whether or not based on tort (including negligence), strict liability, breach of contract, breach of warranty or any other theory, even if advised of the possibility of such damages.

Notwithstanding any damages that customer might incur for any reason whatsoever (including without limitation, all damages referenced above and all direct or general damages), the entire liability of NXP Semiconductors, its affiliates and their suppliers and customer's exclusive remedy for all of the foregoing shall be limited to actual damages incurred by customer based on reasonable reliance up to the greater of the amount actually paid by customer for the product or five dollars (US\$5.00). The foregoing limitations, exclusions and disclaimers shall apply to the maximum extent permitted by applicable law, even if any remedy fails of its essential purpose.

9.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are property of their respective owners.

10. Contents

1.	Introduction	3
2.	System setup	3
3.	Block diagram.....	4
3.1	Functional description	4
3.2	Technical specification	4
4.	Functional description	5
4.1	Data flow	5
4.1.1	The 64 points FFT result (8-bit data) is sent via USB CDC (Bulk).....	5
5.	Fast Fourier Transform (FFT) algorithm.....	7
6.	Applications.....	7
7.	Application demonstration	8
7.1	Requirements.....	8
7.1.1	Hardware.....	8
7.1.2	Software.....	8
7.2	Compile and flashing.....	8
7.3	Install USB drivers.....	10
7.4	FFT Demo	12
7.5	Play audio on a player.....	12
8.	Conclusion.....	13
9.	Legal information	14
9.1	Definitions	14
9.2	Disclaimers.....	14
9.3	Trademarks.....	14
10.	Contents.....	15

Please be aware that important notices concerning this document and the product(s) described herein, have been included in the section 'Legal information'.
