



# INDEX

## —A—

- ADDR D-23
  - bus signals 5-29
  - definition 2-4
  - signal 5-33
  - starting address D-18
- Address
  - bus (ADDR) 5-29
  - map 3-14
  - mark wakeup 6-33
  - space
    - encoding 5-31
    - maps 3-14—3-18
  - strobe ( $\overline{AS}$ ) 5-29
- Arbitration 6-3
- $\overline{AS}$  5-29, 5-35, 5-38, 5-45
- Asserted (definition) 2-4
- ATEMP 4-21
- AVEC 5-22, 5-32, 5-61, 5-66
  - enable bit 5-68, D-21

## —B—

- Background
  - debug mode 4-19, 5-39
    - commands 4-22
    - connector pinout 4-26
    - enabling 4-20
    - entering 4-21
    - registers
      - fault address register (FAR) 4-23
      - instruction program counter (PCC) 4-23
      - return program counter (RPC) 4-23
    - returning from 4-24
  - serial
    - data word 4-26
    - I/O block diagram 4-25
    - interface 4-24
    - peripheral interface protocol (SPI) 4-25
  - sources 4-20
- Basic operand size 5-33
- Baud
  - clock 6-28
  - rate generator 6-2
- BC D-42
- BCD 4-4
- Berg connector (male) 4-26
- $\overline{BERR}$  5-35, 5-39, 5-44, 5-45, 5-61
  - assertion results 5-43
- $\overline{BG}$  5-46, 5-66
- BGACK 5-46, 5-66

- BGND instruction 4-21
- BH D-42
- Binary
  - coded decimal (BCD) 4-4
- BITS D-33
  - encoding field 6-20
- Bits per transfer
  - enable (BITSE) D-38
  - field (BITS) D-33
- BITSE 6-22, D-38
- Bit-time 6-27
- BKPT 4-20, 5-39, 5-49, 5-58
  - external signal 4-21
- BKPT (TPU asserted) D-42
- BL D-42
- BLC D-41
- Block size (BLKSZ) 5-66, D-18
  - encoding 5-67, D-18
- BM D-42
- BME 5-23, D-13
- BMT 5-22, D-13
- BP D-42
- $\overline{BR}$  5-45, 5-46, 5-66
- Branch latch control (BLC) D-41
- Break frame 6-28
- Breakpoint
  - acknowledge cycle 5-39
  - asserted flag (BKPT) D-42
  - enable bits D-42
  - flag (PCBK) D-43
  - hardware breakpoints 5-39
  - instruction 4-19
  - mode selection 5-53
  - operation 5-41
  - software breakpoints 5-39
- Brushless motor commutation (COMM) 7-12
- BSA 4-20
- BT D-42
- Built-in emulation memory C-1
- Bus
  - arbitration
    - single device 5-47
  - cycle
    - regular 5-35
    - termination sequences 5-42
  - error
    - exception processing 5-44
    - signal ( $\overline{BERR}$ ) 5-22, 5-31, 5-44
    - timing of 5-44
  - grant ( $\overline{BG}$ ) 5-46
  - grant acknowledge ( $\overline{BGACK}$ ) 5-46



- monitor 5-22
  - external enable (BME) D-13
  - timeout period 5-23
  - timing (BMT) 5-22, D-13
- request (BR) 5-46
- state analyzer (BSA) 4-20
- BYTE (upper/lower byte option) 5-67, D-19

## **—C—**

- C (carry) flag 4-6, D-4
- Case outlines
  - 831A-01 (132-pin package) B-4
  - 863C-01 (144-pin package) B-5
  - 918-02 (144-pin package) B-6
- CCL D-42
- CCR 4-6
- CFSR D-44
- CH D-44, D-45, D-46
- CHANNEL D-44
- Channel
  - conditions latch (CCL) D-42
  - control registers 7-15
  - function select registers 7-15
  - interrupt
    - base vector (CIBV) D-43
    - enable
      - /disable field (CH) D-44
      - and status registers 7-15
    - request level (CIRL) D-43
    - status (CH) D-46
  - orthogonality 7-4
  - priority registers 7-17
  - register breakpoint flag (CHBK) D-43
- CHBK D-43
- Chip-select
  - base address
    - register boot ROM (CSBARBT) D-17
    - registers (CSBAR) 5-65, 5-66, D-17
    - reset values 5-71
  - operation 5-68
  - option
    - register boot ROM (CSORBT) D-18
    - registers (CSOR) 5-65, 5-67, D-18
    - reset values 5-71
  - pin
    - assignment registers (CSPAR) 5-65, D-15
    - field encoding 5-66, D-17
    - pin
      - assignments D-17
  - reset operation 5-70
  - signals for interrupt acknowledge 5-69
- CIBV D-43
- CIER 7-16, D-44
- CIRL D-43
- CISR 7-13, 7-16, D-46
- Clear (definition) 2-4
- CLKOUT 5-34, 5-49
- CLKRST (clock reset) 5-48
- CLKS D-42
- Clock

- control multipliers
  - 16.78 MHz 5-8
  - 20.97 MHz 5-10
  - 25.17 MHz 5-12
- mode
  - pin (MODCLK) 5-53
  - selection 5-53
- output (CLKOUT) 5-34
- phase (CPHA) D-33
- polarity (CPOL) D-33
- synthesizer
  - control register (SYNCR) D-8
  - operation 5-5
- Coherency 7-4
- COMM 7-12
- Command RAM 6-9
- Common in-circuit emulator 4-20
- Completed queue pointer (CPTQP) D-37
- Condition code register (CCR) 4-6, 7-5
- CONT D-38
- Contention 5-61
- Continue (CONT) D-38
- Continuous transfer mode 6-7
- Conventions 2-4
- CPHA 6-19, D-33
- CPOL 6-19, D-33
- CPR D-46
- CPTQP 6-10, D-37
- CPU space
  - address encoding 5-39
  - cycles 5-38
  - encoding for interrupt acknowledge 5-69
- CPU32 5-48
  - address registers/address organization in 4-5
  - addressing modes 4-9
  - block diagram 4-2
  - data registers 4-4
    - data organization 4-5
  - development support 4-18
  - exception processing 4-16
  - features 3-1
  - generated message encoding 4-26
  - instructions 4-10
    - LPSTOP 4-15
    - MOVEC 4-7
    - MOVES 4-7
    - RESET 5-49
    - special control instructions 4-15
    - table lookup and interpolate (TBL) 4-15
    - unimplemented MC68020 instructions 4-10
  - loop mode 4-15
  - memory organization 4-7
  - processing states 4-9
  - reference manual 4-1
  - register
    - model 4-3, D-2
  - registers 4-2
    - alternate function code registers (SFC/DFC) 4-7
    - condition code register (CCR) 4-6, D-3
    - control registers 4-6



- mnemonics 2-2
- program counter (PC) 4-1
- stack pointer (SP) 4-1
- status register (SR) 4-6, D-3
- vector base register (VBR) 4-7
- virtual memory 4-9
- CR D-38
- CREG D-22
- CSBAR D-17
- CSBARBT D-17
- CSBOOT 5-58, 5-64, 5-66
  - reset values 5-72
- CSOR D-18
- CSORBT D-18
- CSPAR D-15

**-D-**

- DATA 5-29
- Data
  - and size acknowledge ( $\overline{\text{DSACK}}$ ) 5-22, 5-31
  - bus
    - mode selection 5-50
    - signals (DATA) 5-29
  - frame 6-28
  - multiplexer 5-33
  - strobe ( $\overline{\text{DS}}$ ) 5-30
  - types 4-4
- DATA (definition) 2-4
- DBcc 4-16
- DCNR D-47
- DDRE 5-72, D-10
- DDRF 5-72, D-11
- DDRQS 6-4, 6-18, 6-22, D-31
- Delay
  - after transfer (DT) 6-20, D-38
  - before SCK (DSCKL) D-34
- Designated CPU space 5-30
- Development
  - support and test registers (TPU) 7-17
  - tools and support C-1
- DFC 4-7
- DIO 7-6
- Discrete input/output (DIO) 7-6
- Distributed register (DREG) D-22
- DIV8 clock 7-15
- Double
  - buffered 6-29, 6-31
  - bus fault 4-21, 5-44
  - row header 4-26
- DREG D-22
- Driver types 3-9
- $\overline{\text{DS}}$  5-30, 5-35, 5-45
- $\overline{\text{DSACK}}$  5-22, 5-35, 5-39, 5-61, 5-66, 5-68
  - assertion results 5-43
  - external/internal generation 5-38
  - option fields 5-38
  - signal effects 5-32
  - source specification in asynchronous mode 5-68, D-19
- DSCK D-38

- DSCKL D-34
- DSCLK 4-25
- DSCR D-41
- DSSR D-42
- DT D-38
- DTL D-35
- Dynamic bus sizing 5-32

**-E-**

- EBI 5-61
- ECLK 5-20
- EDIV 5-20, D-8
- EMU 7-5, 7-15, D-40
- Emulation
  - control (EMU) 7-15, D-40
  - support 7-5
- Encoded
  - one of three channel priority levels (CH) D-46
  - time function for each channel (CHANNEL) D-44
  - type of host service (CH) D-45
- Ending queue pointer (ENDQP) D-36
- ENDQP 6-10, D-36
- Error
  - conditions 6-31
  - detection circuitry 6-2
- Event timing 7-3
- Exception
  - instruction (RTE) 5-44
  - processing 4-16, 5-48
  - sequence 4-18
  - types of exceptions 4-17
  - vectors 4-16
    - exception vector assignments 4-17
  - vector 5-48, 7-6
- EXOFF D-7
- EXT D-9
- EXTAL 5-4
- External
  - bus
    - arbitration 5-46
    - clock
      - division (EDIV) D-8
      - division bit (EDIV) 5-20
      - operation during LPSTOP 5-20
      - signal (ECLK) 5-20
    - interface (EBI) 5-27
      - control signals 5-29
    - clock off (EXOFF) D-7
    - reset (EXT) D-9
- Externally
  - input clock frequency D-14
- EXTRST (external reset) 5-56

**-F-**

- Factory test 5-73
- FAR 4-23
- Fast
  - quadrature decode (FQD) 7-12
  - termination



cycles 5-34, 5-38  
FC 5-30  
FE 6-31, D-30  
FQD 7-12  
FQM 7-13  
Frame 6-28  
    size 6-32  
Framing error (FE) flag 6-31, D-30  
FREEZE  
    assertion response (FRZ)  
        QSM 6-3, D-25  
        SIM 5-3  
        TPU D-42  
    bus monitor (FRZBM) 5-3, D-7  
    software enable (FRZSW) 5-3, D-7  
 $f_{ref}$  5-4  
Frequency  
    control  
        counter (Y) D-8  
        prescaler (X) D-8  
        VCO (W) D-8  
    measurement (FQM) 7-13  
FRZ D-25, D-42  
FRZBM 5-3, D-7  
FRZSW 5-3, D-7  
 $f_{sys}$  5-4, D-8  
F-term encoding 5-38  
Function  
    code (FC) signals 5-30, 5-38  
    library for TPU 7-5  
 $f_{VCO}$  5-6



Hall effect decode (HALLD) 7-13  
HALLD 7-13  
HALT D-36  
HALT 5-23, 5-31, 5-35, 5-45  
    assertion results 5-43  
Halt  
    acknowledge flag (HALTA) D-37  
    monitor  
        enable (HME) 5-23, D-13  
        reset (HLT) D-9  
    operation 5-45  
        negating/reasserting 5-45  
    QSPI (HALT) D-36  
HALTA D-37  
HALTA/MODF interrupt enable (HMIE) bit D-36  
Handshaking 5-34  
Hang on T4 (HOT4) D-41  
Hardware breakpoints 5-39  
HCMOS 1-1  
High-density complementary metal-oxide semiconductor (HCMOS) 1-1  
HLT D-9  
HME 5-23, D-13  
HMIE D-36  
Host  
    sequence registers 7-17  
    service registers 7-17

HOT4 D-41  
HSQR D-45  
HSSR D-45  
Hysteresis 5-60



IARB  
    QSM D-25  
    SIM 5-2, 5-3, 5-60, D-7  
    TPU 7-5, D-41  
ICD16/ICD32 C-1  
 $I_{DD}$  5-54  
IDLE 6-32, D-29  
Idle  
    frame 6-28  
    -line  
        detect type (ILT) D-28  
        detected (IDLE) 6-32, D-29  
        detection process 6-32  
        interrupt enable (ILIE) 6-32, D-28  
        type (ILT) bit 6-32  
ILIE 6-32, D-28  
ILQSPI D-25  
ILSCI D-25  
ILT 6-32, D-28  
In-circuit debugger (ICD16/ICD32) C-1  
Input  
    capture/input transition counter (ITC) 7-6  
    clock ( $f_{ref}$ ) 5-4  
Interchannel communication 7-4  
Intermodule bus (IMB) 3-2  
Internal  
    bus  
        error ( $\overline{BERR}$ ) 5-22, 5-23  
        monitor 5-22  
        register map 3-14  
Interrupt  
    acknowledge  
        and arbitration 5-60  
        bus cycles 5-62  
    arbitration 5-2, 6-3  
    IARB field  
        QSM D-25  
        SIM 5-2, 5-3, 5-60, D-7  
        TPU 7-5, D-41  
    exception processing 5-59  
    level (IL)  
        for QSPI (ILQSPI) D-25  
        for SCI (ILSCI) D-25  
    priority  
        and recognition 5-59  
        level field (IPL) 5-68, D-20  
        mask (IP) field 4-6, 5-59, 6-3, 7-5, D-4  
    processing summary 5-61  
    vector  
        number 6-3  
        field (INTV) D-26  
Interrupts  
    QSM 6-3  
    SIM 5-58



TPU 7-5  
Inter-transfer delay 6-6  
INTV D-26  
IP 6-3, 7-5  
IPL D-20  
IRQ 5-59, 5-61, 7-5  
ITC 7-6

—L—

Length of delay after transfer (DTL) D-35  
Level-sensitivity 5-59  
LOC D-9  
Logic  
    analyzer pod connectors C-2  
    levels (definition) 2-4  
Loop  
    mode 4-15  
        (LOOPS) D-27  
        instruction sequence 4-15  
LOOPQ D-36  
LOOPS D-27  
Loss of clock reset (LOC) D-9  
Low power stop (LPSTOP)  
    broadcast cycle 5-42  
    CPU space cycle 4-42  
    CPU32 4-15  
    interrupt mask level 5-42  
    SIM 5-27  
    TPU 7-15  
    TPURAM 8-3  
Low-power  
    stop mode enable (STOP)  
        QSM 6-2, D-24  
        TPU D-40  
        TPURAM D-22  
LPSTOP 1-1, 4-15, 5-20, 5-27, 5-42  
LR D-46  
LSB 2-4, 4-4  
LSW 2-4

—M—

M 6-28, D-28  
M68000 family  
    compatibility 4-14  
    development support 4-19  
M68MEVB1632 C-1  
    modular evaluation board (MEVB) C-1  
M68MMDS1632 C-1  
Master  
    /slave mode select (MSTR) D-32  
    shift registers (TSTMSR) D-21  
Maximum system clock 1-1  
MC68010 4-14  
MC68020 4-10, 4-14  
MC68332  
    132-pin package 3-4, B-2  
    144-pin package 3-5, B-3  
    address map 3-14  
    block diagram 3-3

driver types 3-9  
memory maps  
    overall 3-15  
    separate supervisor and user space 3-16  
    supervisor space 3-17  
    user space 3-18

pin  
    characteristics 3-6  
    functions 3-10

MCU personality board (MPB) C-1

Mechanical information B-7

Memory

    CPU32 organization 4-7  
    virtual 4-9

Memory maps

    internal register map 3-14  
    overall 3-15  
    separate supervisor and user space 3-16  
    supervisor space 3-17  
    user space 3-18

Misaligned operand 5-33

MISO 6-18, 6-22

MM D-7

MMDS C-1

Mnemonics

    range (definition) 2-4  
    specific (definition) 2-4

MODCLK 5-4, 5-5, 5-57

MODE 5-67, D-18

Mode

    fault flag (MODF) 6-11, D-37  
    select (M) D-28

MODF 6-11, D-37

Modular platform board C-1

Module

    address map D-1  
    mapping (MM) bit 5-2, D-7  
    pin functions 5-53

Modulus counter 6-28

MOSI 6-18, 6-22

Motorola

*Microcontroller Development Tools Directory*

        (MCUDEVTLDIR/D Rev. 3) C-1

    modular development system (MMDS) C-1

MPB C-1

MSB 2-4, 4-4

MSTR D-32

MSTRST (master reset) 5-49, 5-56, 5-58

MSW 2-4

Multichannel pulse width modulation (MCPWM) 7-11

Multimaster operation 6-11

—N—

N (negative) flag 4-6, D-4

Negated (definition) 2-4

New

    input capture/transition counter (NITC) 7-11  
    queue pointer value (NEWQP) D-36

NEWQP 6-10, 6-23, D-36

NF 6-31, D-30



NITC 7-11  
Noise  
    error (NF) flag 6-31  
    error flag (NF) D-30  
Nomenclature 2-1  
Non-maskable interrupt 5-59  
NRZ 6-2

—O—

OC 7-7  
On-chip breakpoint hardware 4-27  
OP (1 through 3) 5-33  
Opcode tracking 4-27  
Operand  
    alignment 5-33  
    byte order 5-33  
    destination 4-4  
    misaligned 5-33  
    source 4-4  
    transfer cases 5-34  
Operators 2-1  
OR D-30  
Ordering information B-7  
Output  
    compare (OC) 7-7  
Overrun error (OR) D-30  
Overview information 3-1

—P—

Parallel I/O ports 5-72  
Parentheses (definition) 2-4  
Parity  
    checking 6-29  
    enable (PE) D-28  
    error (PF) bit D-30  
    error (PF) flag 6-31  
    type (PT) 6-29, D-28  
PCBK D-43  
PCC 4-23  
PCS D-39  
    to SCK delay (DSCK) D-38  
PCS0/SS 6-22  
PE D-28  
PEPAR 5-72, D-10  
Period  
    /pulse width accumulator (PPWA) 7-9  
    measurement  
        additional transition detect (PMA) 7-7  
        missing transition detect (PMM) 7-8  
Periodic  
    interrupt  
        control register (PICR) 5-26, D-13  
        modulus counter 5-26  
        priority 5-27  
        request level (PIRQL) 5-26, D-13  
        timer 5-25  
            components 5-25  
            modulus (PITM) field 5-26  
            PIT period calculation 5-26, D-14

    register (PITR) D-14  
    timing modulus (PITM) D-14  
    vector (PIV) 5-26, D-13  
    timer prescaler control (PTP) 5-26, D-14  
Peripheral  
    breakpoints 4-21  
    chip-selects (PCS) D-39  
Peripheral chip-selects (PCS) 6-23  
PF 6-31, D-30  
PFPAR 5-72, D-12  
Phase-locked loop (PLL) 1-1, 5-4  
PICR 5-26, 5-61, D-13  
Pin  
    electrical state 5-54  
    function 5-54  
    reset states 5-55  
PIRQL 5-26, D-13  
PITM 5-26, D-14  
PITR 5-26, D-14  
PIV 5-26, D-13  
PLL 1-1, 5-4  
PMA 7-7  
PMM 7-8  
Pointer 6-7  
Port  
    parallel I/O in SIM 5-72  
    replacement unit (PRU) C-2  
    size 5-66  
Port C data register (PORTC) 5-68, D-15  
Port E  
    data direction register (DDRE) 5-72, D-10  
    data register (PORTE) 5-72, D-10  
    pin assignment register (PEPAR) 5-72, D-10  
Port F  
    data direction register (DDRF) 5-72, D-11  
    data register (PORTF) 5-72, D-11  
    pin assignment register (PFPAR) 5-72, D-12  
PORTC D-15  
PORTE 5-72, D-10  
PORTF 5-72, D-11  
PORTQS 6-4, D-30  
Position-synchronized pulse generator (PSP) 7-8  
POW D-9  
Power  
    consumption reduction 5-20  
    -up reset (POW) D-9  
PPWA 7-9  
PQSPAR 6-4, 6-18, 6-22, D-31  
Prescaler  
    clock  
        (PSCK) D-41  
    control  
        for TCR1 7-13  
        for TCR2 7-14  
Program counter (PC) 4-1, 4-6  
Programmable  
    channel service priority 7-4  
    time accumulator (PTA) 7-11  
    transfer length 6-6  
PRU C-2



PSCK 7-13, D-41  
PSP 7-8  
PT 6-29, D-28  
PTA 7-11  
PTP D-14  
Pulse width modulation  
    TPU waveform (PWM) 7-7  
PWM 7-7

—Q—

QDEC 7-10  
QILR 6-2, D-25  
QIVR 6-2, D-25  
QOM 7-11  
QSM  
    address map 6-2, D-23, D-24  
    block diagram 6-1  
    features 3-1  
    general 6-1  
    interrupts 6-3  
    pin function 6-5, D-32  
    QSPI 6-5  
        operating modes 6-10  
        operation 6-9  
        pins 6-9  
        RAM 6-8  
        registers 6-7  
    reference manual 6-1  
    registers  
        command RAM (CR) D-38  
        global registers 6-2  
        interrupt  
            level register (QILR) 6-2, D-25  
            vector register (QIVR) 6-2, D-25  
        test register (QTEST) 6-2  
        module configuration register (QSMCR) D-24  
        pin control registers 6-4  
        port QS  
            data direction register (DDRQS) 6-4, D-31  
            data register (PORTQS) 6-4, D-30  
            pin assignment register (PQSPAR) D-31  
    QSPI  
        control register 0 (SPCR0) D-32  
        control register 1 (SPCR1) D-34  
        control register 2 (SPCR2) D-35  
        control register 3 (SPCR3) D-36  
        status register (SPSR) D-36  
        receive data RAM (RR) D-37  
    SCI  
        control register 0 (SCCR0) D-27  
        control register 1 (SCCR1) D-27  
        data register (SCDR) D-30  
        status register (SCSR) D-29  
        test register (QTEST) D-25  
        transmit data RAM (TR) D-38  
        types 6-2  
    SCI 6-23  
        operation 6-27

    pins 6-27  
    registers 6-24  
QSMCR D-24  
QSPI 6-1, 6-2, 6-5  
    block diagram 6-6  
    command RAM 6-9  
    enable (SPE) D-34  
    finished flag (SPIF) D-37  
    initialization operation 6-12  
    loop mode (LOOPQ) D-36  
    master operation flow 6-13  
    operating modes 6-10  
        master mode 6-10, 6-18  
        wraparound mode 6-21  
    slave mode 6-10, 6-22  
        wraparound mode 6-23  
    operation 6-9  
    peripheral chip-selects 6-23  
    pins 6-9  
    RAM 6-8  
        receive RAM 6-8  
        transmit RAM 6-9  
    registers 6-7  
        control registers 6-7  
        status register 6-8  
QTEST 6-2, D-25  
Quadrature decode (QDEC) 7-10  
Quad-word data 4-4  
Queue pointers  
    completed queue pointer (CPTQP) 6-10  
    end queue pointer (ENDQP) 6-10  
    new queue pointer (NEWQP) 6-10  
Queued  
    output match (QOM) 7-11  
Queued serial  
    module (QSM). *See* QSM 6-1  
    peripheral interface (QSPI) *See* QSPI. 6-1, 6-5

—R—

R/W 5-30, 5-35  
    field 5-68, D-19  
RAF D-29  
RAM  
    array  
        disable (RAMDS) D-23  
RAMDS 8-1, D-23  
RASP D-22  
RDR 6-27  
RDRF 6-31, D-29  
RE 6-31, D-28  
Read  
    /write signal (R/W) 5-30  
    cycle 5-36  
        flowchart 5-36  
    system register command (RSREG) 4-22  
Receive  
    data  
        (RXD) pin — QSM 6-27  
        register full (RDRF) D-29  
    RAM 6-8



time sample clock (RT) 6-29, 6-31

## Receiver

active (RAF) D-29

data register (RDRF) flag 6-31

enable (RE) 6-31, D-28

interrupt enable (RIE) D-28

wakeup (RWU) 6-32, D-28

## Register bit and field mnemonics 2-2

**RESET** 4-20, 5-48, 5-50, 5-54, 5-56

## Reset

control logic in SIM 5-48

exception processing 5-48

mode selection

use in determining SIM configuration 5-49

module pin function out of reset 5-53

operation in SIM 5-48

power-on 5-56

processing summary 5-58

source summary in SIM 5-49

states of pins assigned to other MCU modules 5-55

status register (RSR) 5-22, 5-58, D-9

timing 5-56

Retry operation 5-45

**RIE** D-28

**RMC** 5-46

**RPC** 4-23

**RR** D-37

**RS-232C** terminal C-2

**RSR** 5-22, D-9

**RSREG** 4-22

**RT** 6-31

**RTE** 5-44

**RWU** 6-32, D-28

**RXD** (QSM) 6-27

—S—

**S** D-4

**SBK** 6-30, D-29

**SCBR** D-27

**SCCR** 6-24

**SCCR0** D-27

**SCCR1** D-27

**SCDR** 6-27, D-30

**SCI** 6-1, 6-2, 6-18, 6-23

baud

clock 6-28

rate (SCBR) D-27

equation D-27

idle-line detection 6-32

internal loop 6-33

operation 6-27

parity checking 6-29

pins (QSM) 6-27

receiver

block diagram

QSM 6-26

operation 6-31

wakeup 6-32

registers 6-24

control registers — QSM (SCCR) 6-24

data register

QSM (SCDR) 6-27

status register

QSM (SCSR) 6-27

transmitter

block diagram

QSM 6-25

operation 6-29

**SCK** 6-18, 6-22

actual delay before SCK (equation) 6-19

baud rate (equation) 6-19

**SCSR** 6-27, D-29

Send break (SBK) 6-30, D-29

## Serial

clock baud rate (SPBR) D-34

communication interface (SCI) 6-1, 6-23

formats 6-28

interface 4-24

mode (M) bit 6-28

shifter 6-27, 6-29

## Service

request breakpoint flag (SRBK) D-43

Set (definition) 2-4

**SFC** 4-7

**SGLR** D-47

**SHEN** 5-47, D-7

Show cycle

enable (SHEN) 5-3, 5-47, D-7

operation 5-47

## SIM 5-1

address map D-5

block diagram 5-2

bus operation 5-34

chip-selects 5-62

external bus interface (EBI) 5-27

features 3-1

functional blocks 5-1

halt monitor 5-23

interrupt arbitration 5-3

interrupts 5-58

low-power stop operation 5-27

module configuration register (SIMCR) D-6

parallel I/O ports 5-72

periodic interrupt timer 5-25

block diagram (with software watchdog) 5-25

register access 5-3

registers

chip-select

base address

register boot ROM (CSBARBT) D-17

registers (CSBAR) 5-65, 5-66, D-17

option

register boot ROM (CSORBT) D-18

registers (CSOR) 5-65, 5-67, D-18

pin assignment registers (CSPAR) 5-65,  
D-15

clock synthesizer control register (SYNCR) D-8

distributed register (DREG) D-22

master shift register A/B (TSTMSRA/B) D-21

module configuration register (SIMCR) 5-2





periodic interrupt  
  control register (PICR) D-13  
  timer register (PITR) 5-26, D-14  
port C data register (PORTC) 5-68, D-15  
port E  
  data direction register (DDRE) 5-72, D-10  
  data register (PORTE) 5-72, D-10  
  pin assignment register (PEPAR) 5-72, D-10  
port F  
  data direction register (DDRF) 5-72, D-11  
  data register (PORTF) 5-72, D-11  
  pin assignment register (PFPAR) 5-72, D-12  
reset status register (RSR) D-9  
software service register (SWSR) D-15  
system  
  integration  
    test register - ECLK (SIMTRE) D-9  
    test register (SIMTR) D-8  
    protection control register (SYPCR) D-12  
  test  
    module  
      repetition count (TSTRC) D-21  
      shift count register (TSTSC) D-21  
      submodule control register (CREG) D-22  
reset 5-48  
  state of pins 5-54  
software watchdog 5-23  
  block diagram (with PIT) 5-23  
spurious interrupt monitor 5-23  
system  
  clock 5-4  
    block diagram 5-4  
    synthesizer operation 5-5  
  configuration 5-2  
  protection 5-21  
*SIM Reference Manual* 5-62  
SIMCR 5-2, 8-1, D-6  
SIMTR D-8  
SIMTRE D-9  
SIZ 5-30, 5-33, 5-48  
Size signals (SIZ) 5-30  
  encoding 5-30  
Slave select signal ( $\overline{SS}$ ). See  $\overline{SS}$  6-22  
SLOCK 5-6, D-8  
Slow reference frequency 5-4, 5-26, D-14  
SM 7-9  
Software  
  breakpoints 5-39  
  service register (SWSR) D-15  
  watchdog 5-23  
    block diagram 5-25  
    clock rate 5-24  
    enable (SWE) D-12  
    enable (SWE) bit 5-23  
    prescale (SWP) D-12  
    prescale (SWP) bit 5-24  
    ratio of SWP and SWT bits 5-24  
    reset (SW) D-9  
    timeout period calculation 5-24  
    timing field (SWT) 5-24, D-13  
SPACE (address space select) 5-68, D-20  
SPBR D-34  
SPCR0 D-32  
SPCR1 D-34  
SPCR2 D-35  
SPCR3 D-36  
SPE 6-7, D-34  
SPI 4-25  
  finished interrupt enable (SPIFIE) D-35  
SPIF D-37  
SPIFIE D-35  
SPSR D-36  
SPWM 7-7  
SR 4-6  
SRBK D-43  
 $\overline{SS}$  6-22, 6-23  
SSP 4-10  
Stack pointer (SP) 4-1  
Standard  
  nonreturn to zero (NRZ) 6-2  
Standby RAM module w/ TPU emulation (TPURAM). See TPURAM 8-1  
Start bit (beginning of data frame) 6-27  
State machine 6-31  
Stepper motor (SM) 7-9  
STEXT 5-20, D-9  
STF D-41  
STOP 6-2, D-22, D-24, D-40  
Stop  
  clocks to TCRs (CLKS) D-42  
  enable (STOP) bit  
    QSM 6-2  
    TPU 7-15  
  flag (STF) D-41  
  mode  
    external clock (STEXT) 5-20, D-9  
    SIM clock (STSIM) 5-20, D-9  
  SCI end of data frame bit 6-27  
STRB (address strobe/data strobe) bit 5-38, 5-68, D-19  
STSIM 5-20, D-9  
Supervisor  
  /unrestricted data space (SUPV)  
    CPU32 D-4  
    QSM D-25  
    SIM 5-3, D-7  
    TPU D-41  
  stack pointer (SSP) 4-10  
SUPV 5-3, D-25  
SW D-9  
SWE 5-23, D-12  
SWP 5-24, D-12  
SWSR D-15  
SWT 5-24, D-13  
Symbols 2-1  
Synchronized pulse width modulation (SPWM) 7-7  
SYNCR D-8  
Synthesizer lock flag (SLOCK) D-8  
SYPCR D-12

SYS D-9  
 SYSRST (system reset) 5-49  
 System  
   clock 1-1, 5-4  
     block diagram 5-4  
     output (CLKOUT) 5-34  
     sources 5-4  
   frequencies  
     16.78 MHz 5-14  
     20.97 MHz 5-16  
     25.17 MHz 5-18  
   integration  
     module. *See* SIM D-5  
     module. *See* SIM 5-1  
     test register - ECLK (SIMTRE) D-9  
   memory maps. *See* Memory maps 3-14  
   protection control register (SYPCR) D-12  
   reset (SYS) D-9

## -T-

T D-3  
 T2CG 7-14, D-41  
 Table stepper motor (TSM) 7-10  
 TBL 4-15  
 TC 6-30, D-29  
 TCIE 6-31, D-28  
 TCR D-41  
 TCR1P 7-13, D-40  
 TCR2 clock/gate control (T2CG) D-41  
 TCR2P D-40  
 TDR 6-27  
 TDRE 6-30, D-29  
 TE D-28  
 Temporary register A (ATEMP) 4-21  
 Test  
   module  
     repetition count (TSTRC) D-21  
     shift count register (TSTSC) D-21  
   submodule  
     control register (CREG) D-22  
     reset (TST) D-9  
 Three-state control (TSC) 5-57  
 TICR 7-13, D-43  
 TIE 6-31, D-28  
 Time  
   processor unit. *See* TPU 7-1  
 Timer  
   count register  
     1 prescaler control (TCR1P) D-40  
     2 prescaler control (TCR2P) D-40  
 TPU  
   A mask functions 7-6  
   discrete input/output (DIO) 7-6  
   input capture/input transition counter (ITC) 7-6  
   output compare (OC) 7-7  
   period  
     /pw accumulator (PPWA) 7-9  
   measurement  
     add transition detect (PMA) 7-7  
     missing transition detect (PMM) 7-8

  position-synch pulse generator (PSP) 7-8  
   pulse width modulation (PWM) 7-7  
   quadrature decode (QDEC) 7-10  
   stepper motor (SM) 7-9  
   synch pw modulation (SPWM) 7-7  
 address map D-39  
 block diagram 7-1  
 components 7-2  
 features 3-2  
 FREEZE flag (TPUF) D-43  
 function library 7-5  
 G mask functions 7-10  
   brushless motor commutation (COMM) 7-12  
   fast quadrature decode (FQD) 7-12  
   frequency measurement (FQM) 7-13  
   hall effect decode (HALLD) 7-13  
   multichannel pulse width modulation (PCPWM)  
     7-11  
   new input capture/transition counter (NITC) 7-11  
   programmable time accumulator (PTA) 7-11  
   queued output match (QOM) 7-11  
   table stepper motor (TSM) 7-10  
   universal asynchronous receiver/transmitter  
     (UART) 7-12  
 host interface 7-3  
 interrupts 7-5  
 microengine 7-3  
 operation 7-3  
   coherency 7-4  
   emulation support 7-5  
   event timing 7-3  
   interchannel communication 7-4  
   programmable channel service priority 7-4  
 overview 7-1  
 parameter RAM 7-3, D-47  
   address map D-47  
 registers  
   channel  
     function select registers (CFSR) D-44  
     interrupt  
       enable register (CIER) 7-5, D-44  
       status register (CISR) 7-5, D-46  
     priority registers (CPR) D-46  
   decoded channel number register (DCNR) D-47  
   development  
     support control register (DSCR) D-41  
     support status register (DSSR) D-42  
   host  
     sequence registers (HSQR) D-45  
     service request registers (HSSR) D-45  
   link register (LR) D-46  
   module configuration register (TPUMCR) D-40  
   service grant latch register (SGLR) D-47  
   test configuration register (TCR) D-41  
   TPU interrupt configuration register (TICR) D-43  
 scheduler 7-3  
 time  
   bases 7-2  
   timer channels 7-2  
   timing (electricals) A-43



TPU Reference Manual 7-3, 7-17

TPUF D-43

TPUMCR 7-13, D-40

TPURAM

address map D-22

array

address mapping 8-1

base address (ADDR) D-23

space (RASP) D-22

features 3-2

general 8-1

operation

normal 8-2

standby 8-2

privilege level 8-2

register block 8-1

registers

base address and status register (TRAMBAR)  
D-23

module configuration register (TRAMMCR) D-22

test register (TRAMTST) D-23

reset 8-3

TPU microcode emulation 8-3

TR D-38

Trace

enable field (T) D-3

on instruction execution 4-19

TRAMBAR 8-1, D-23

TRAMMCR 8-1, D-22

TRAMTST 8-1, D-23

Transfer length options 6-19

Transistion-sensitivity 5-59

Transmit

complete

(TC) flag

QSM 6-30

bit (TC) D-29

interrupt enable (TCIE) D-28

QSM 6-31

data

(TXD) pin — QSM 6-27

register empty (TDRE) flag D-29

QSM 6-30

enable (TE)

QSM 6-29

interrupt enable (TIE) D-28

QSM 6-31

RAM 6-9

Transmitter enable (TE) D-28

TSC 5-57

TSM 7-10

TST D-9

TSTMSR D-21

TSTRC D-21

TSTSC D-21

TXD (QSM) 6-27

—U—

UART 7-12

Unimplemented instruction emulation 4-19

Universal asynchronous receiver/transmitter (UART)  
7-12

User stack pointer (USP) 4-10

Using the TPU Function Library and TPU Emulation  
Mode 7-5

USP 4-10

—V—

V (overflow) flag 4-6, D-4

VBR 4-7, 4-16

VCO frequency ( $f_{VCO}$ ) 5-6

$V_{DD}$  5-56, 8-1

ramp time 5-57

$V_{DDSYN}$  5-5, 5-56

Vector base register (VBR) 3-14, 4-7, 4-16, 5-59

Virtual memory 4-9

Voltage

controlled oscillator (VCO) 5-6

frequency ramp time 5-57

$V_{PP}$  C-2

$V_{SS}$  8-2

$V_{STBY}$  8-1, 8-2

—W—

W bit D-8

WAKE 6-33, D-28

Wakeup

address mark (WAKE) 6-33, D-28

functions 6-2

Wired-OR

mode

for QSPI pins (WOMQ) D-33

for SCI pins (WOMS) D-28

QSM 6-29

WOMQ D-33

WOMS 6-29, D-28

Wrap

enable (WREN) D-35

to (WRTO) D-35

Wraparound mode 6-7

master 6-21

slave 6-23

WREN D-35

Write cycle 5-37

flowchart 5-37

WRTO D-35

—X—

X

(extend) flag 4-6, D-4

bit in SYNCR D-8

XFC 5-6

XTRST (external reset) 5-48

—Y—

Y field D-8



-Z-

Z (zero) flag 4-6, D-4

