



INDEX

—A—

AC timing (electricals) A-6
ACKERR D-91
Acknowledge error (ACKERR) D-91
ADDR D-80
 bus signals 5-20
 definition 2-7
 signal 5-24
 starting address D-17
Address
 bus (ADDR) 5-20
 -mark wakeup 9-31
 space 8-7
 encoding 5-21
 maps 3-13—3-17
 strobe (\overline{AS}) 5-20
Advanced Microcontroller Unit (AMCU) Literature 1-1
AN 8-3, 8-5
Analog
 front-end multiplexer 8-15
 input
 multiplexed 8-5
 port A 8-3
 port B 8-4
 section contents 8-1
 submodule block diagram 8-12
 supply pins 8-5
APS D-84
Arbitration 9-3
 \overline{AS} 5-20, 5-26, 5-29, 5-36
ASPC 7-2, 7-3, D-24
Asserted (definition) 2-7
ATEMP 4-21
Auto power save (APS) D-84
 \overline{AVEC} 5-13, 5-22, 5-52, 5-57
 enable bit 5-59, D-20

—B—

Background
 debug mode 4-19, 5-30
 commands 4-22
 connector pinout 4-26
 enabling 4-20
 entering 4-21
 registers
 fault address register (FAR) 4-23
 instruction program counter (PCC) 4-23
 return program counter (RPC) 4-23
 returning from 4-24
 serial

 data word 4-26
 I/O block diagram 4-25
 interface 4-24
 peripheral interface protocol (SPI) 4-25
 sources 4-20
 debugging mode
 freeze assertion diagram A-18
 serial
 communication diagram A-18
 timing A-18
Base ID mask bits D-90
Basic operand size 5-24
Baud
 clock 9-27
 rate generator 9-2
BC D-74
BCD 4-4
Beginning of queue 2 (BQ2) D-34
Berg connector (male) 4-26
 \overline{BERR} 5-25, 5-26, 5-30, 5-35, 5-36, 5-52
 assertion results 5-34
 \overline{BG} 5-37, 5-57
 \overline{BGACK} 5-37, 5-57
BGND instruction 4-21
BH D-74
Binary
 -coded decimal (BCD) 4-4
 divider 8-23
 -weighted capacitors 8-15
Bit stuff error (STUFFERR) D-92
BITERR D-91
BITS D-48
 encoding field 9-19
Bits per transfer
 enable (BITSE) D-53
 field (BITS) D-48
BITSE 9-21, D-53
Bit-time 9-26
BIUMCR D-55
BIUSM 10-3
 FREEZE D-55
 interrupt vector base number (VECT) D-56
 LPSTOP 10-4
 registers 10-4
 module configuration register (BIUMCR) D-55
 test configuration register (BIUTEST) D-56
 time base register (BIUTBR) D-56
 STOP 10-3, D-55
BIUTBR D-56
BIUTEST D-56
 \overline{BKPT} 4-20, 5-30, 5-40, 5-49



- external signal 4-21
- BKPT (TPU asserted) D-74
- BL D-74
- BLC D-73
- Block size (BLKSZ) 5-57, D-17
 - encoding 5-58, D-17
- BM D-74
- BME 5-14, D-12
- BMT 5-13, D-13
- BOFFINT D-92
- BOFFMSK D-85
- BOOT 7-3, D-24
- Boot ROM
 - control($\overline{\text{BOOT}}$) D-24
- Bootstrap words (ROMBS) 7-1
- Boundary conditions 8-19
- BP D-74
- BQ2 D-34
- $\overline{\text{BR}}$ 5-36, 5-37, 5-57
- Branch latch control (BLC) D-73
- Break frame 9-27
- Breakpoint
 - acknowledge cycle 5-30
 - asserted flag (BKPT) D-74
 - enable bits D-74
 - flag (PCBK) D-74
 - hardware breakpoints 5-30
 - instruction 4-19
 - mode selection 5-44
 - operation 5-32
 - software breakpoints 5-30
- Brushless motor commutation (COMM) 11-12
- BSA 4-20
- BSL D-63
- BT D-74
- Built-in emulation memory C-1
- Bus
 - arbitration
 - single device 5-38
 - timing diagrams
 - active A-14
 - idle A-15
 - cycle
 - regular 5-26
 - termination sequences 5-33
 - error
 - exception processing 5-35
 - signal (BERR) 5-13, 5-22, 5-35
 - timing of 5-35
 - grant ($\overline{\text{BG}}$) 5-37
 - grant acknowledge ($\overline{\text{BGACK}}$) 5-37
 - interface
 - unit submodule. *See* BIUSM 10-1, 10-3
 - monitor 5-13
 - external enable (BME) D-12
 - timeout period 5-13
 - timing (BMT) 5-13, D-13
 - off interrupt
 - (BOFFINT) D-92
 - mask (BOFFMSK) D-85

- request ($\overline{\text{BR}}$) 5-37
- select (BSL) D-63
- state analyzer (BSA) 4-20
- BUSY 13-5, 13-15
- BYP 8-14, D-36
- Bypass mode 8-14
- BYTE (upper/lower byte option) 5-58, D-18

—C—

- C (carry) flag 4-6, D-4
- CAN2.0B
 - controller module. *See* TouCAN 13-1
 - protocol 13-1
 - system 13-2
- CANCTRL0 D-85
- CANCTRL1 D-87
- CANCTRL2 D-88
- CANICR D-85
- CANMCR D-82
- CANRX/TX pins 13-2
- CCL D-74
- CCR 4-6
- CCW 8-1, 8-28, D-36
- CF1 D-34
- CF2 D-34
- CFSR D-75
- CH D-75, D-77, D-78
- CHAN D-36
- CHANNEL D-76
- Channel
 - assignments
 - multiplexed D-38
 - nonmultiplexed D-37
 - conditions latch (CCL) D-74
 - control registers 11-15
 - function select registers 11-15
 - interrupt
 - base vector (CIBV) D-75
 - enable
 - /disable field (CH) D-75
 - and status registers 11-15
 - request level (CIRL) D-75
 - status (CH) D-78
 - invalid D-37
 - number (CHAN) D-36
 - orthogonality 11-4
 - priority registers 11-17
 - register breakpoint flag (CHBK) D-74
 - reserved D-37
- CHBK D-74
- Chip-select
 - base address
 - register boot ROM (CSBARBT) D-17
 - registers (CSBAR) 5-56, 5-57, D-17
 - reset values 5-62
 - operation 5-59
 - option
 - register boot ROM (CSORBT) D-18
 - registers (CSOR) 5-56, 5-58, D-18
 - reset values 5-62



- pin
 - assignment registers (CSPAR) 5-55, D-15
 - field encoding 5-57, D-16
 - pin
 - assignments D-16
 - reset operation 5-61
 - signals for interrupt acknowledge 5-60
 - timing diagram A-17
- CIBV D-75
- CIE1 D-31
- CIE2 D-32
- CIER 11-15, D-75
- CIRL D-75
- CISR 11-13, 11-15, D-78
- Clear (definition) 2-7
- CLK D-59, D-60, D-68
- CLKOUT 5-25, 5-40
 - output timing diagram A-8
- CLKRST (clock reset) 5-40
- CLKS D-73
- Clock
 - block diagram 8-24
 - control
 - multipliers 5-7
 - timing (electricals) A-3
 - generation 8-23
 - input pin status (FCSM) D-58
 - input pin status (MCSM) D-60
 - mode
 - pin (MODCLK) 5-43
 - selection 5-43
 - output (CLKOUT) 5-25
 - phase (CPHA) D-48
 - polarity (CPOL) D-48
 - rate selection (CLK) field D-68
 - synthesizer
 - control register (SYNCR) D-7
 - operation 5-5
- Code 13-4
- COF D-58, D-59
- Coherency 8-6, 8-22, 11-4
- COMM 11-12
- Command
 - RAM 9-9
 - word pointer (CWP) D-36
- Common in-circuit emulator 4-20
- Comparator 8-15
- Completed queue pointer (CPTQP) D-52
- Condition code register (CCR) 4-6, 11-5
- CONT D-53
- Contention 5-51
- Continue (CONT) D-53
- Continuous transfer mode 9-7
- Conventions 2-7
- Conversion
 - command word table (CCW) 8-1, 8-16, 8-28
 - cycle times 8-13
 - stages 8-30
- Counter
 - clock select (CLK) field
- FCSM D-59
- MCSM D-60
- overflow flag (COF) bit D-58, D-59
- prescaler submodule. *See* CPSM 10-4
- CPCR D-57
- CPHA 9-17, D-48
- CPOL 9-17, D-48
- CPR D-77
- CPSM 10-4
 - block diagram 10-5
 - registers 10-5
 - control register (CPCR) D-57
 - test register (CPTR) D-57
- CPTQP 9-9, D-52
- CPTR D-57
- CPU
 - space
 - address encoding 5-30
 - cycles 5-29
 - encoding for interrupt acknowledge 5-60
- CPU32 5-39
 - address registers/address organization in 4-5
 - addressing modes 4-9
 - block diagram 4-2
 - data registers 4-4
 - data organization 4-5
 - development support 4-18
 - exception processing 4-16
 - features 3-1
 - generated message encoding 4-26
 - instructions 4-10
 - LPSTOP 4-15
 - MOVEC 4-7
 - MOVES 4-7
 - RESET 5-40
 - special control instructions 4-15
 - table lookup and interpolate (TBL) 4-15
 - unimplemented MC68020 instructions 4-10
 - loop mode 4-15
 - memory organization 4-7
 - processing states 4-9
 - register
 - mnemonics 2-2
 - model 4-3, D-2
 - registers 4-2
 - alternate function code registers (SFC/DFC) 4-7
 - condition code register (CCR) 4-6, D-3
 - control registers 4-6
 - program counter (PC) 4-1
 - stack pointer (SP) 4-1
 - status register (SR) 4-6, D-3
 - vector base register (VBR) 4-7
 - virtual memory 4-9
- CPU32 Reference Manual* 4-1
- CR D-53
- CRCERR D-91
- CREG D-21
- CSBAR D-17
- CSBARBT D-17
- CSBOOT 5-49, 5-55, 5-57, 7-3



- reset values 5-63
- CSOR D-18
- CSORBT D-18
- CSPAR D-15
- CTD9 D-60
- CTM Reference Manual* 10-1
- CTM2C D-60
- CTM4
 - address map 10-2, D-54
 - block diagram 10-1
 - bus interface unit submodule (BIUSM) 10-3
 - components 10-1
 - counter prescaler submodule (CPSM) 10-4
 - double-action submodule (DASM) 10-10
 - features 3-2
 - free-running counter submodule (FCSM) 10-5
 - interrupt priority and vector/pin allocation 10-20
 - interrupts 10-19
 - modulus counter submodule (MCSM) 10-5, 10-7
 - pulse width modulation submodule (PWMSM) 10-13
- CWP D-36
- Cyclic redundancy check error (CRCERR) D-91

-D-

- DAC 8-1
- DASM 10-10
 - block diagram 10-12
 - channels 10-11
 - interrupts 10-12
 - mode flag status bit states D-62
 - modes of operation 10-11
 - registers 10-12
 - data register A (DASMA) D-65
 - data register B (DASMB) D-65
 - status/interrupt/control register (DASMSIC) D-62
 - timing (electricals) A-30
- DASMA D-65
 - operations D-65
- DASMB D-65
 - operations D-66
- DASMSIC D-62
- DATA 5-20
- Data
 - and size acknowledge (\overline{DSACK}) 5-13, 5-22
 - bus
 - mode selection 5-41
 - signals (DATA) 5-20
 - field for RX/TX frames (TouCAN) 13-4
 - frame 9-27
 - multiplexer 5-24
 - strobe (\overline{DS}) 5-20
 - types 4-4
- DATA (definition) 2-7
- DBcc 4-16
- DC characteristics (electricals) A-4
- DCNR D-78
- DDRE 5-63, D-9
- DDRF 5-63, D-11
- DDRQA 8-2, D-29
- DDRQS 9-4, 9-17, 9-21, D-46

- Delay
 - after transfer (DT) 9-19, D-53
 - before SCK (DSCKL) D-49
- Designated CPU space 5-21
- Development
 - support and test registers (TPU) 11-17
 - tools and support C-1
- DFC 4-7
- Digital
 - control section
 - contents 8-1, 8-16-??
 - input
 - /output port (PQA) 8-4
 - port (PQB) 8-4
 - to analog converter (DAC) 8-1, 8-15
- DIO 11-6
- DIS D-65, D-66
- Disabled mode 8-20
- Discrete input/output (DIO) 11-6
- Distributed register (DREG) D-21
- DIV8 clock 11-14
- Divide by 2/divide by 3 (DIV23) D-57
- Double
 - action submodule. See DASM 10-10
 - buffered 9-28, 9-30
 - bus fault 4-21, 5-35
 - row header 4-26
- DREG D-21
- Drive time base bus (DRV) D-58, D-60
- DRV D-58, D-60
- \overline{DS} 5-20, 5-26, 5-36
- \overline{DSACK} 5-13, 5-25, 5-26, 5-30, 5-52, 5-57, 5-59
 - assertion results 5-34
 - external/internal generation 5-29
 - option fields 5-29
 - signal effects 5-23
 - source specification in asynchronous mode 5-59, D-19
- DSCK D-54
- DSCKL D-49
- DSCLK 4-25
- DSCR D-73
- DSSR D-74
- DT D-53
- DTL D-50
- Dynamic bus sizing 5-23

-E-

- EBI 5-51
- ECLK 5-10
 - bus timing A-19
 - output timing diagram A-9
 - timing diagram A-20
- Edge polarity (EDPOL) bit D-64
- EDGEN D-60
- EDGEPR D-60
- EDIV 5-10, D-8
- EDPOL D-64
- EMPTY 13-5
- EMU 11-5, 11-15, D-72



- EMUL D-24
- Emulation
 - control (EMU) 11-15, D-72
 - mode control (EMUL) D-24
 - support 11-5
- EN D-68
- Encoded
 - one of three channel priority levels (CH) D-77
 - time function for each channel (CHANNEL) D-76
 - type of host service (CH) D-77
- Ending queue pointer (ENDQP) D-51
- End-of-
 - frame (EOF) 13-16
 - queue condition 8-30
- ENDQP 9-9, D-51
- EOF 13-16
- ERRINT D-93
- ERRMSK D-86
- Error
 - conditions 9-30
 - counters 13-9
 - detection circuitry 9-2
 - interrupt (ERRINT) D-93
 - interrupt mask (ERRMSK) D-86
- ESTAT D-91
- ETRIG 8-4
- Event flag (FLAG) D-62
- Event timing 11-3
- Exception
 - instruction (RTE) 5-35
 - processing 4-16, 5-39
 - sequence 4-18
 - types of exceptions 4-17
 - vectors 4-16
 - exception vector assignments 4-17
 - vector 5-39, 11-6
- EXOFF D-6
- EXT D-9
- Extended message format 13-1
 - frames 13-4
- External
 - bus
 - arbitration 5-37
 - clock
 - division (EDIV) D-8
 - division bit (EDIV) 5-10
 - operation during LPSTOP 5-11
 - signal (ECLK) 5-10
 - interface (EBI) 5-18
 - control signals 5-20
 - clock input timing diagram A-8
 - clock off (EXOFF) D-6
 - digital supply pin 8-6
 - multiplexing 8-10
 - reset (EXT) D-9
 - trigger pins 8-4
- Externally
 - input clock frequency D-14
 - multiplexed mode (MUX) D-30
- EXTRST (external reset) 5-47
- Factory test 5-64
- FAR 4-23
- Fast
 - quadrature decode (FQD) 11-12
 - reference 5-4
 - circuit 5-4
 - termination
 - cycles 5-25, 5-28
 - read cycle timing diagram A-12
 - write cycle timing diagram A-13
- Fast reference frequency D-14
- Fault confinement state (FCS) 13-10, D-92
- FC 5-21
- FCS 13-10, D-92
- FCSM 10-5
 - block diagram 10-6
 - clock sources 10-6
 - counter 10-6
 - external event counting 10-7
 - interrupts 10-7
 - registers 10-7
 - counter register (FCSMCNT) D-59
 - status/interrupt/control register (FCSMSIC) D-58
 - time base bus drivers 10-7
 - timing (electricals) A-29
- FCSMCNT D-59
- FCSMSIC D-58
- FE 9-30, D-45
- Final sample time 8-13
- FLAG D-62, D-66
- FORCA D-63
- FORCB D-63
- Force (FORCA/B) D-63
- FORMERR D-91
- f_{PWM} 10-17
- f_{QCLK} 8-23
- FQD 11-12
- FQM 11-12
- Frame 9-27
 - size 9-30
- Frames
 - overload 13-16
 - remote 13-15
- Framing error (FE) flag 9-30, D-45
- Free-running counter submodule. *See* FCSM 10-5
- FREEZ ACK 13-16
- FREEZE
 - assertion response (FRZ)
 - BIUSM 10-3, D-55
 - QADC 8-7, D-27
 - QSM 9-3, D-40
 - SIM 5-3
 - TouCAN D-82
 - TPU D-73
 - bus monitor (FRZBM) 5-3, D-6
 - software enable (FRZSW) 5-3, D-6
- Frequency
 - control



- counter (Y) D-8
- prescaler (X) D-8
- VCO (W) D-8
- measurement (FQM) 11-12
- FRZ 8-7, 13-11, D-27, D-40, D-73, D-82
- FRZACK 13-11, D-83
- FRZBM 5-3, D-6
- FRZSW 5-3, D-6
- f_{sys} 8-24, 10-17, D-7
- F-term encoding 5-29
- FULL 13-5
- Function
 - code (FC) signals 5-21, 5-29
 - library for TPU 11-5

—G—

Global registers 8-2

—H—

- Hall effect decode (HALLD) 11-13
- HALLD 11-13
- HALT 13-11, D-51, D-83
- $\overline{\text{HALT}}$ 5-14, 5-22, 5-25, 5-26, 5-36
 - assertion results 5-34
- Halt
 - acknowledge flag (HALTA) D-52
 - monitor
 - enable (HME) 5-14, D-12
 - reset (HLT) D-9
 - operation 5-36
 - negating/reasserting 5-36
 - QSPI (HALT) D-51
 - TouCAN S-clock (HALT) D-83
- HALTA D-52
- HALTA/MODF interrupt enable (HMIE) bit D-51
- Handshaking 5-25
- Hang on T4 (HOT4) D-73
- Hardware breakpoints 5-30
- HLT D-9
- HME 5-14, D-12
- HMIE D-51
- Host
 - sequence registers 11-16
 - service registers 11-16
- HOT4 D-73
- HSQR D-76
- HSSR D-77
- Hysteresis 5-50

—I—

I/O port operation 8-8

- IARB
 - BIUSM D-56
 - QADC 8-8, D-28
 - QSM D-40
 - SIM 5-2, 5-3, 5-51, D-7
 - TouCAN D-85
 - TPU 11-5, D-73

- IARB3 D-58, D-60, D-62, D-67
- IC D-65, D-66
- ICD16/ICD32 C-1
- ID

- Extended (IDE) field 13-6
- HIGH field 13-6
- LOW field 13-6

I_{DD} 5-45

IDE 13-6

Identifier (ID) 13-1

- bit field 13-6

IDLE 9-30, D-44, D-92

Idle

- CAN status (IDLE) D-92

- frame 9-27

- line

- detect type (ILT) D-43

- detected (IDLE) 9-30, D-44

- detection process 9-30

- interrupt enable (ILIE) 9-31, D-43

- type (ILT) bit 9-31

IFLAG D-93

IL D-58, D-60, D-62, D-67

ILIE 9-31, D-43

ILQSPI D-41

ILSCI D-41

ILT 9-31, D-43

IMASK D-93

IMB 8-1, 10-1

IN D-58, D-63

IN1 D-60

IN2 D-60

In-circuit debugger (ICD16/ICD32) C-1

Information processing time (IPT) 13-9

Initial sample time 8-13

Input

- capture/input transition counter (ITC) 11-6

- pin status (IN)

- DASM D-63

- sample time (IST) 8-26, D-36

Interchannel communication 11-4

Intermission 13-16

Intermodule bus (IMB) 3-3, 8-1, 10-1

Internal

- bus

- error ($\overline{\text{BERR}}$) 5-13, 5-14

- monitor 5-13

- clock signals (PCLK) D-61

- register map 3-12

Interrupt

- acknowledge

- and arbitration 5-51

- bus cycles 5-53

- arbitration 5-2, 9-3

- IARB field

- BIUSM D-56

- QADC 8-8, D-28

- QSM D-40

- SIM 5-2, 5-3, 5-51, D-7

- TouCAN D-85



- TPU 11-5, D-73
 - IARB3 bit
 - DASM D-62
 - FCSM D-58
 - MCSM D-60
 - PWMSM D-67
 - exception processing 5-49
 - initializing 8-33
 - level (IL)
 - DASM D-62
 - FCSM D-58
 - for QSPI (ILQSPI) D-41
 - for SCI (ILSCI) D-41
 - MCSM D-60
 - PWMSM D-67
 - priority
 - and recognition 5-50
 - level field (IPL) 5-59, D-20
 - mask (IP) field 4-6, 5-50, 9-3, 11-5, D-3
 - processing summary 5-52
 - request level (IRL) bit field D-85
 - sources 8-31
 - vector
 - base (IVB) field D-28
 - base address (IVBA) field D-85
 - number 9-3
 - field (INTV) D-41
 - vectors for QADC 8-32
 - Interrupts
 - CTM4 10-19
 - DASM 10-12
 - FCSM 10-7
 - MCSM 10-9
 - QADC 8-31
 - QSM 9-3
 - SIM 5-49
 - TouCAN 13-18
 - TPU 11-5
 - Inter-transfer delay 9-6
 - INTV D-41
 - Invalid channel number D-37
 - IP 9-3, 11-5
 - IPL D-20
 - IPM D-65, D-66
 - IPT 13-9
 - IPWM D-65, D-66
 - IRL D-85
 - IRLQ1 D-28
 - IRLQ2 D-28
 - $\overline{\text{IRQ}}$ 5-50, 5-52, 11-5
 - I_{SB} 6-2
 - IST 8-26, D-36
 - ITC 11-6
 - IVB 8-32, D-28
 - IVBA D-85
- L-
- LBUF D-87
 - Least significant bit (LSB) 8-15
 - Left justified
- signed result word table (LJSRR) D-38
 - unsigned result word table (LJURR) D-38
 - Length of delay after transfer (DTL) D-50
 - Level-sensitivity 5-50
 - LJSRR D-38
 - LJURR D-38
 - LOAD D-67
 - LOC D-9
 - LOCK 7-3, D-24
 - Lock
 - /release/busy mechanism 13-14
 - registers (LOCK) D-24
 - Logic
 - analyzer pod connectors C-2
 - levels (definition) 2-7
 - LOOP D-87
 - Loop
 - back (LOOP) D-87
 - mode 4-15
 - (LOOPS) D-42
 - instruction sequence 4-15
 - LOOPQ D-51
 - LOOPS D-42
 - Loss of clock reset (LOC) D-9
 - Low power stop (LPSTOP)
 - BIUSM 10-4
 - broadcast cycle 5-33
 - CPU space cycle 5-33
 - CPU32 4-15
 - interrupt mask level 5-33
 - MRM 7-3
 - QADC 8-6
 - QSM 9-2
 - SIM 5-18
 - SRAM 6-2
 - TPU 11-15
 - TPURAM 12-3
 - Lowest buffer transmitted first (LBUF) D-87
 - Low-power
 - stop mode enable (STOP)
 - BIUSM D-55
 - MRM D-23
 - QADC D-27
 - QSM D-40
 - SRAM D-21
 - TouCAN D-82
 - TPU D-71
 - TPURAM D-80
 - LPSTOP 4-15, 5-11, 5-18, 5-33, 10-4
 - LR D-78
 - LSB 2-7, 4-4, 8-15
 - LSW 2-7
- M-
- M 9-27, D-43
 - M68000 family
 - compatibility 4-14
 - development support 4-19
 - M68MEVB1632 C-1
 - modular evaluation board (MEVB) C-1



M68MMDS1632 C-1
Mask
 examples for normal/extended messages 13-8
 registers (RX) 13-7
Masked ROM module (MRM). *See* MRM 7-1
Master
 /slave mode select (MSTR) D-47
 shift registers (TSTMSR) D-20
Maximum
 ratings (electrical) A-1
MC68010 4-14
MC68020 4-10, 4-14
MCSM 10-5, 10-7
 block diagram 10-8
 clock sources 10-9
 counter 10-8
 external event counting 10-9
 interrupts 10-9
 modulus latch 10-8
 registers 10-10
 counter register (MCSMCNT) D-61
 modulus latch register (MCSMML) D-61
 status/interrupt/control register (MCSMSIC) D-59
 time base bus drivers 10-9
 timing (electricals) A-29
MCSMCNT D-61
MCSMML D-61
MCSMSIC D-59
MCU
 basic system 5-19
 block diagram 3-4
 features 3-1
 personality board (MPB) C-1
 pin assignment package
 MC68336 160-pin package 3-5, B-1
 MC68376 160-pin package 3-6, B-2
Mechanical information B-4
Memory
 CPU32 organization 4-7
 maps
 overall memory 3-14
 separate supervisor and user space 3-15
 supervisor space (separate program/data space) 3-16
 user space (separate program/data space) 3-17
 virtual 4-9
Message
 buffer
 address map D-82
 code for RX/TX buffers 13-5
 deactivation 13-13
 structure 13-3
 format error (FORMERR) D-91
Mid-analog supply voltage 8-15
Misaligned operand 5-24
MISO 9-17, 9-21
MM 6-1, 7-1, 9-2, D-7
MMDS C-1
Mnemonics
 pin and signal 2-2
 range (definition) 2-7
 register 2-4
 specific (definition) 2-7
MODCLK 5-48
MODE 5-58, D-18, D-64
Mode
 fault flag (MODF) 9-10, D-52
 select (M) D-43
Modes
 disabled 8-20
 reserved 8-20
 scan. *See* Scan modes
MODF 9-10, D-52
Modular platform board C-1
Module
 mapping (MM) bit 5-2, 6-1, 7-1, 9-2, D-6, D-7
 pin functions 5-44
Modulus
 counter 9-27
 counter submodule (MCSM). *See* MCSM 10-5, 10-7
 load
 edge sensitivity (EDGEN, EDGE) bits D-60
 input pin status (IN1) D-60
MOSI 9-17, 9-21
Most significant bit (MSB) 8-15
Motorola
 Microcontroller Development Tools Directory
 (MCUDEVTLDIR/D Rev. 3) C-1
 modular development system (MMDS) C-1
MPB C-1
MQ1 D-31
MQ2 D-32
MRM 7-1
 address map D-23
 array address mapping 7-1
 features 3-1
 low-power stop operation 7-3
 normal access 7-2
 registers
 module configuration register (MRMCR) 7-1, D-23
 ROM
 array base address registers (ROM-BAH/BAL) 7-1, D-25
 bootstrap words (ROMBS) 7-1, D-26
 signature registers (RSIGHI/LO) 7-1, D-25, D-26
 reset 7-3
 ROM signature 7-3
MRMCR 7-1, D-23
MSB 2-7, 4-4, 8-15
MSTR D-47
MSTRST (master reset) 5-40, 5-47, 5-49
MSW 2-7
Multichannel pulse width modulation (MCPWM) 11-11
Multimaster operation 9-10
Multiplexed analog inputs 8-5
MUX 8-8, D-30



-N-

N (negative) flag 4-6, D-4
NCLOCK 10-17
Negated (definition) 2-7
New
 input capture/transition counter (NITC) 11-11
 queue pointer value (NEWQP) D-51
NEWQP 9-9, 9-22, D-51
NF 9-30, D-45
NITC 11-11
Noise
 error flag (NF) D-45
 errors 9-30
 flag (NF) 9-30
Non-maskable interrupt 5-50
NOT ACTIVE 13-5
Not ready (NOTRDY) 13-3
NOTRDY 13-3, 13-16, D-83
NPERIOD 10-17
NRZ 9-2

-O-

OC 11-7
OCAB D-65, D-66
OCB D-65, D-66
On-chip breakpoint hardware 4-27
OP (1 through 3) 5-23
Opcode tracking 4-26
Open drain drivers 8-4
Operand
 alignment 5-24
 byte order 5-24
 destination 4-4
 misaligned 5-24
 source 4-4
 transfer cases 5-24
Operators 2-1
OPWM D-65, D-66
OR D-44
Ordering information B-4
Output
 compare (OC) 11-7
 driver types 3-8
 flip-flop 10-14
 pin
 polarity control (POL) bit D-67
 status (PIN) bit D-67
Overload frames 13-16
OVERRUN 13-5
Overrun error (OR) D-44

-P-

P D-36
Parallel I/O ports 5-63
Parentheses (definition) 2-7
Parity
 (PF) flag 9-30
 checking 9-28

enable (PE) D-43
error (PF) bit D-45
errors 9-30
type (PT) D-43
type (PT) bit 9-28
Pause (P) 8-17, D-36
PCBK D-74
PCC 4-23
PCLK D-61
PCLK6 D-57
PCS D-54
 to SCK delay (DSCK) D-54
PCS0/SS 9-21
PE D-43
PEPAR 5-63, D-10
Period
 /pulse width accumulator (PPWA) 11-9
 and pulse width register load control (LOAD) bit D-67
 completion status (FLAG) bit D-66
 measurement
 additional transition detect (PMA) 11-7
 missing transition detect (PMM) 11-8
Periodic
 /interval timer 8-27
 interrupt
 control register (PICR) 5-17, D-13
 modulus counter 5-16
 priority 5-17
 request level (PIRQL) 5-17, D-13
 timer 5-16
 components 5-16
 modulus (PITM field 5-16
 PIT period calculation 5-17, D-14
 register (PITR) D-13
 timing modulus (PITM) D-13
 vector (PIV) 5-17, D-13
 timer prescaler control (PTP) 5-16, D-13
Peripheral
 breakpoints 4-21
 chip-selects (PCS) 9-22, D-54
PF 9-30, D-45
PF1 D-34
PF2 D-34
PFPAR 5-63, D-11
Phase buffer segment 1/2 (PSEG1/2) bit field D-88
PICR 5-17, 5-52, D-13
PIE1 D-31
PIE2 D-32
PIN D-67
Pin
 characteristics 3-7
 electrical state 5-45
 function 5-45
 reset states 5-46
PIRQL 5-17, D-13
PITM 5-16, D-13
PITR 5-16, D-13
PIV 5-17, D-13
PMA 11-7
PMM 11-8



Pointer 9-7
POL D-67
Port
 parallel I/O in SIM 5-63
 replacement unit (PRU) C-2
 size 5-57
Port C data register (PORTC) 5-59, D-14
Port E
 data direction register (DDRE) 5-63, D-9
 data register (PORTE) 5-63, D-9
 pin assignment register (PEPAR) 5-63, D-10
Port F
 data direction register (DDRF) 5-63, D-11
 data register (PORTF) 5-63, D-10
 pin assignment register (PFPAR) 5-63, D-11
PORTC D-14
PORTE 5-63, D-9
PORTF 5-63, D-10
PORTQA 8-2, D-29
PORTQB 8-2, D-29
PORTQS 9-4, D-45
Position-synchronized pulse generator (PSP) 11-8
POW D-9
Power
 connections 3-8
 consumption reduction 5-11
 -up reset (POW) D-9
PPWA 11-9
PQA 8-4, 8-9
PQB 8-4, 8-9
PQSPAR 9-4, 9-17, 9-21, D-46
Prescaler
 add a tick (PSA) 8-24, D-30
 clock
 (PSCK) D-73
 high time (PSH) 8-24, D-30
 low time (PSL) 8-24, D-30
 control
 for TCR1 11-13
 for TCR2 11-14
 divide
 factor field D-88
 register (PRESDIV) 13-8, D-88
 division ratio select (PSEL) D-57
 field values for QACR0 8-25
 running (PRUN) D-57
PRESDIV (bit field) D-88
PRESDIV (register) 13-8, 13-9, D-88
Program counter (PC) 4-1, 4-6
Programmable
 channel service priority 11-4
 time accumulator (PTA) 11-11
 transfer length 9-6
Propagation segment time (PROPSEG) D-87
PROPSEG 13-11, D-87
PRU C-2
PRUN D-57
PSA 8-24, 8-26, D-30
PSCK 11-13, D-73
PSEG1 D-88

PSEG2 13-9, 13-11, D-88
PSEGS1 13-11
PSEL D-57
PSH 8-24, D-30
PSL 8-24, D-30
PSP 11-8
PT 9-28, D-43
PTA 11-11
PTP D-13
Pulse width modulation
 submodule. See PWMSM 10-13
 TPU waveform (PWM) 11-7
PWM 11-7
 duty cycle boundary cases 10-18
PWMA D-69
PWMB D-69
PWMC D-70
PWMSIC D-66
PWMSM 10-13
 block diagram 10-14
 clock selection 10-14
 coherency 10-16
 counter 10-15
 enable (EN) D-68
 output flip-flop 10-14
 period registers and comparator 10-15
 pulse width registers and comparator 10-16
 PWM
 frequency 10-17
 period and pulse width register values 10-18
 pulse width 10-18
 registers 10-19
 PWM
 counter register (PWMC) D-70
 period register (PWMA) D-69
 pulse width register (PWMB) D-69
 status/interrupt/control register (PWMSIC)
 D-66
 timing (electricals) A-31

-Q-

QACR0 8-2, 8-27, D-30
QACR1 8-2, 8-28, D-31
QACR2 8-2, 8-28, D-32
QADC
 address map D-26
 clock (QCLK) 8-14
 conversion characteristics (operating) A-28
 electrical characteristics (operating)
 AC A-27
 DC A-26
 features 3-2
 maximum ratings A-25
 pin functions diagram 8-3
 registers
 control register 0 (QACR0) 8-2, 8-27, D-30
 control register 1 (QACR0) 8-2, 8-28
 control register 1 (QACR1) D-31
 control register 2 (QACR0) 8-2, 8-28
 control register 2 (QACR2) D-32



- conversion command word table (CCW) D-36
- interrupt register (QADCINT) 8-2, D-28
- module configuration register (QADCMCR) 8-2, 8-6, D-27
- port
 - A data register (PORTQA) 8-2
 - B data register (PORTQB) 8-2
 - data direction register (DDRQA) 8-2
 - QA data direction register (DDRQA) D-29
 - QA data register (PORTQA) D-29
 - QB data register (PORTQB) D-29
- result word table D-38
- status register (QASR) 8-2, 8-28, D-34
- test register (QADCTEST) 8-2, D-28
- QADCINT 8-2, D-28
- QADCMCR 8-2, 8-6, D-27
- QADCTEST 8-2, D-28
- QASR 8-2, 8-28, D-34
- QCLK 8-14, 8-23
 - frequency 8-23
- QDEC 11-10
- QILR 9-2, D-41
- QIVR 9-2, D-41
- QOM 11-11
- QS D-35
- QSM
 - address map 9-2, D-39
 - block diagram 9-1
 - features 3-2
 - general 9-1
 - initialization sequence 9-32
 - interrupts 9-3
 - pin function 9-5, D-47
 - QSPI 9-5
 - operating modes 9-10
 - operation 9-9
 - pins 9-9
 - RAM 9-8
 - registers 9-7
 - reference manual 9-1
 - registers
 - command RAM (CR) D-53
 - global registers 9-2
 - interrupt
 - level register (QILR) 9-2, D-41
 - vector register (QIVR) 9-2, D-41
 - test register (QTEST) 9-2
 - module configuration register (QSMCR) D-40
 - pin control registers 9-4
 - port QS
 - data direction register (DDRQS) 9-4, D-46
 - data register (PORTQS) 9-4, D-45
 - pin assignment register (PQSPAR) D-46
 - QSPI
 - control register 0 (SPCR0) D-47
 - control register 1 (SPCR1) D-49
 - control register 2 (SPCR2) D-50
 - control register 3 (SPCR3) D-51
 - status register (SPSR) D-51
 - receive data RAM (RR) D-52
 - SCI
 - control register 0 (SCCR0) D-42
 - control register 1 (SCCR1) D-42
 - data register (SCDR) D-45
 - status register (SCSR) D-44
 - test register (QTEST) D-40
 - transmit data RAM (TR) D-53
 - types 9-2
 - SCI 9-22
 - operation 9-26
 - pins 9-26
 - registers 9-22
 - QSMCR D-40
 - QSPI 9-1, 9-5
 - block diagram 9-6
 - enable (SPE) D-49
 - finished flag (SPIF) D-52
 - initialization operation 9-11
 - loop mode (LOOPQ) D-51
 - master operation flow 9-12
 - operating modes 9-10
 - master mode 9-10, 9-17
 - wraparound mode 9-20
 - slave mode 9-10, 9-20
 - wraparound mode 9-22
 - operation 9-9
 - peripheral chip-selects 9-22
 - pins 9-9
 - RAM 9-8
 - command RAM 9-9
 - receive RAM 9-8
 - transmit RAM 9-8
 - registers 9-7
 - control registers 9-7
 - status register 9-8
 - timing A-21
 - master A-22
 - slave A-23
 - QTEST 9-2, D-40
 - Quadrature decode (QDEC) 11-10
 - Quad-word data 4-4
 - Queue 8-16
 - pointers
 - completed queue pointer (CPTQP) 9-9
 - end queue pointer (ENDQP) 9-9
 - new queue pointer (NEWQP) 9-9
 - status (QS) D-35
 - Queue 1
 - completion
 - flag (CF1) D-34
 - interrupt enable (CIE1) D-31
 - interrupt level (IRLQ1) D-28
 - operating mode (MQ1) D-31
 - pause
 - flag (PF1) D-34
 - interrupt enable (PIE1) D-31
 - single-scan enable (SSE1) D-31
 - trigger overrun (TOR1) D-34



Queue 2
 completion
 flag (CF2) D-34
 interrupt enable (CIE2) D-32
 interrupt level (IRLQ2) D-28
 operating mode (MQ2) D-32
 pause
 flag (PF2) D-34
 interrupt enable (PIE2) D-32
 resume (RES) D-33
 single-scan enable bit (SSE2) D-32
 trigger overrun (TOR2) D-35
Queued
 analog-to-digital converter. *See* QADC 8-1
 output match (QOM) 11-11
 serial
 module (QSM). *See* QSM 9-1
 peripheral interface (QSPI) 9-1, 9-5

-R-

R \overline{W} 5-21, 5-26
 field 5-58, D-18
RAF D-44
RAM
 array
 disable (RAMDS) D-80
 space (RASP) D-22
 base address lock (RLCK) bit D-22
RAMBAH 6-1, D-22
RAMBAL 6-1, D-22
RAMDS 12-1, D-80
RAMMCR 6-1, D-21
RAMTST 6-1, D-22
RASP 6-1, D-22, D-80
 encoding D-22
RDR 9-26
RDRF 9-30, D-44
RE 9-30, D-43
Read
 /write signal (R \overline{W}) 5-21
 cycle 5-27
 flowchart 5-27
 timing diagram A-10
 system register command (RSREG) 4-22
Receive
 data
 (RXD) pin 9-26
 register full (RDRF) D-44
 error status flag (RXWARN) D-92
 pin configuration control (RXMODE) D-86
 RAM 9-8
 time sample clock (RT) 9-28, 9-30
Receiver
 active (RAF) D-44
 data register (RDRF) flag 9-30
 enable (RE) 9-30, D-43
 interrupt enable (RIE) D-43
 wake up (RWU) 9-31, D-43
Reception of transmitted frames 13-13
Remote

frames 13-15
 transmission request (RTR) 13-4, 13-6
RES 8-30, D-33
Reserved
 channel number D-37
 mode 8-20
 \overline{RESET} 4-20, 5-39, 5-41, 5-45, 5-46
Reset
 control logic in SIM 5-39
 exception processing 5-39
 mode selection
 timing diagram A-17
 use in determining SIM configuration 5-40
 module pin function out of reset 5-44
 operation in SIM 5-39
 power-on 5-47
 processing summary 5-48
 source summary in SIM 5-40
 states of pins assigned to other MCU modules 5-46
 status register (RSR) 5-13, 5-49, D-8
 timing 5-46
Resistor-divider chain 8-15
Resolution time 8-13
Result word table 8-1, 8-16, 8-31
Resynchronization jump width (RJW) bit field D-88
Retry operation 5-36
RIE D-43
Right justified, unsigned result word table (RJURR) D-38
RJURR D-38
RJW 13-11, D-88
RLCK 6-1, D-22
 \overline{RMC} 3-8, 3-10, 3-12, 5-37
ROM array space (ASPC) D-24
ROMBAH 7-1, D-25
ROMBAL 7-1, D-25
ROMBS 7-1
ROMBS0-3 D-26
RPC 4-23
RR D-52
RS-232C terminal C-2
RSIGHI 7-1, 7-3, D-25, D-26
RSIGLO 7-1, 7-3, D-25, D-26
RSR 5-13, D-8
RSREG 4-22
RT 9-30
RTE 5-35
RTR 13-4, 13-6, 13-15
RWU 9-31, D-43
RX
 Length 13-4
RX14MSKHI D-90
RX14MSKLO D-90
RX15MSKHI D-90
RX15MSKLO D-90
RXD 9-26
RXECTR D-94
RXGMSKHI D-90
RXGMSKLO D-90
RXMODE D-86
RXWARN D-92



- S D-3
- SAMP D-87
- Sample amplifier bypass (BYP) D-36
- Sampling mode (SAMP) D-87
- SAR 8-1, 8-16
- SASM
 - timing (electricals) A-30
- SBK 9-29, D-44
- Scan modes
- SCBR D-42
- SCCR 9-23
- SCCR0 D-42
- SCCR1 D-42
- SCDR 9-26, D-45
- SCI 9-1, 9-2, 9-17, 9-22
 - baud
 - clock 9-27
 - rate (SCBR) D-42
 - equation D-42
 - idle-line detection 9-30
 - internal loop 9-32
 - operation 9-26
 - parity checking 9-28
 - pins 9-26
 - receiver
 - block diagram 9-25
 - operation 9-30
 - wakeup 9-31
 - registers 9-22
 - control registers (SCCR) 9-23
 - data register (SCDR) 9-26
 - status register (SCSR) 9-26
 - transmitter
 - block diagram 9-24
 - operation 9-28
- SCK 9-16, 9-21
 - actual delay before SCK (equation) 9-18
 - baud rate (equation) 9-18
- S-clock 13-8
- SCSR 9-26, D-44
- Self wake enable (SELFWAKE) D-84
- Send break (SBK) 9-29, D-44
- Serial
 - clock baud rate (SPBR) D-49
 - communication interface (SCI) 9-1, 9-22
 - formats 9-27
 - interface 4-24
 - mode (M) bit 9-27
 - shifter 9-26, 9-28
- Service
 - request breakpoint flag (SRBK) D-74
- Set (definition) 2-7
- SFC 4-7
- SGLR D-78
- SHEN 5-38, D-6
- Show cycle
 - enable (SHEN) 5-3, 5-38, D-6
 - operation 5-38

- timing diagram A-16
- Signal
 - characteristics 3-9
 - functions 3-11
- Signature registers (RSIGHI/LO) 7-1
- SIM 5-1
 - address map D-4
 - block diagram 5-2
 - bus operation 5-25
 - chip-selects 5-53
 - external bus interface (EBI) 5-18
 - features 3-1
 - functional blocks 5-1
 - halt monitor 5-14
 - interrupt arbitration 5-3
 - interrupts 5-49
 - low-power stop operation 5-18
 - module configuration register (SIMCR) D-6
 - parallel I/O ports 5-63
 - periodic interrupt timer 5-16
 - block diagram (with software watchdog) 5-15
 - register access 5-3
 - registers
 - chip-select
 - base address
 - register boot ROM (CSBARBT) D-17
 - registers (CSBAR) 5-56, 5-57, D-17
 - option
 - register boot ROM (CSORBT) D-18
 - registers (CSOR) 5-56, 5-58, D-18
 - pin assignment registers (CSPAR) 5-56, D-15
 - clock synthesizer control register (SYNCR) D-7
 - distributed register (DREG) D-21
 - master shift register A/B (TSTMSRA/B) D-20
 - module configuration register (SIMCR) 5-2
 - periodic interrupt
 - control register (PICR) D-13
 - timer register (PITR) 5-16, D-13
 - port C data register (PORTC) 5-59, D-14
 - port E
 - data direction register (DDRE) 5-63, D-9
 - data register (PORTE) 5-63, D-9
 - pin assignment register (PEPAR) 5-63, D-10
 - port F
 - data direction register (DDRF) 5-63, D-11
 - data register (PORTF) 5-63, D-10
 - pin assignment register (PFPAR) 5-63, D-11
 - reset status register (RSR) D-8
 - software service register (SWSR) D-14
 - system
 - integration
 - test register - ECLK (SIMTRE) D-9
 - test register (SIMTR) D-7
 - protection control register (SYPCR) D-12
 - test
 - module
 - repetition count (TSTRC) D-21



- shift count register (TSTSC) D-21
- submodule control register (CREG) D-21
- reset 5-39
 - state of pins 5-45
- software watchdog 5-14
 - block diagram (with PIT) 5-14
- spurious interrupt monitor 5-14
- system
 - clock 5-3
 - block diagram 5-4
 - synthesizer operation 5-5
 - configuration 5-2
 - protection 5-12
- SIM Reference Manual* 5-53
- SIMCR 5-2, 9-2, 12-1, D-6
- SIMTR D-7
- SIMTRE D-9
- SIZ 5-21, 5-24, 5-39
- Size signals (SIZ) 5-21
 - encoding 5-21
- Slave select signal (\overline{SS}) 9-21
- SLOCK D-8
- SM 11-9
- SMB 10-1
- SOF 13-9
- Soft reset (SOFRST) D-83
- SOFRST 13-11, D-83
- Software
 - breakpoints 5-30
 - service register (SWSR) D-14
 - watchdog 5-14
 - block diagram 5-15
 - clock rate 5-14
 - enable (SWE) D-12
 - enable (SWE) bit 5-14
 - prescale (SWP) D-12
 - prescale (SWP) bit 5-14
 - ratio of SWP and SWT bits 5-15
 - reset (SW) D-9
 - timeout period calculation 5-15
 - timing field (SWT) 5-14, D-12
- SPACE (address space select) 5-59, D-19
- SPBR D-49
- SPCR0 D-47
- SPCR1 D-49
- SPCR2 D-50
- SPCR3 D-51
- SPE 9-7, D-49
- SPI 4-25
 - finished interrupt enable (SPIFIE) D-50
- SPIF D-52
- SPIFIE D-50
- SPSR D-51
- SPWM 11-7
- SR 4-6
- SRAM
 - address map D-21
 - array address mapping 6-1
 - features 3-1
 - normal access 6-2
- registers
 - array base address register
 - high (RAMBAH) 6-1, D-22
 - low (RAMBAL) 6-1, D-22
 - module configuration register (RAMMCR) 6-1, D-21
 - test register (RAMTST) 6-1, D-22
- reset 6-3
- standby and low-power stop operation 6-2
- SRBK D-74
- SRR 13-6
- SS 9-21
- SSE1 D-31
- SSE2 D-32
- SSP 4-10
- Stack pointer (SP) 4-1
- Standard
 - message format 13-1
 - frames 13-4
 - nonreturn to zero (NRZ) 9-2
- Standby RAM module w/ TPU emulation (TPURAM). *See* TPURAM 12-1
- Start
 - bit (beginning of data frame) 9-27
 - of-frame (SOF) symbol 13-9
- State machine 8-23, 9-30
- Stepper motor (SM) 11-9
- STEXT 5-11, D-8
- STF D-72
- STOP 13-17, D-21, D-23, D-27, D-40, D-55, D-71, D-80, D-82
- Stop
 - acknowledge (STOPACK) D-84
 - clocks to TCRs (CLKS) D-73
 - enable (STOP) bit
 - BIUSM 10-3
 - QADC 8-6
 - QSM 9-2
 - SRAM 6-2
 - TouCAN 13-17
 - TPU 11-15
 - flag (STF) D-72
 - mode
 - external clock (STEXT) 5-11, D-8
 - SIM clock (STSIM) 5-11, D-8
 - SCI end of data frame bit 9-27
- STOPACK D-84
- STRB (address strobe/data strobe) bit 5-29, 5-59, D-19
- STSIM 5-11, D-8
- STUFFERR D-92
- Submodule bus (SMB) 10-1
- Subqueue 8-17
- Substitute remote request (SRR) 13-6
- Successive approximation register (SAR) 8-1, 8-16
- Supervisor
 - /unrestricted data space (SUPV)
 - CPU32 D-3
 - QADC D-27
 - QSM D-40
 - SIM 5-3, D-7



- TouCAN D-84
- TPU D-72
 - stack pointer (SSP) 4-10
- SUPV 5-3, 8-7, D-27, D-28, D-40, D-84
- SW D-9
- SWE 5-14, D-12
- SWP 5-14, D-12
- SWSR D-14
- SWT 5-14, D-12
- Symbols 2-1
- Synchronized pulse width modulation (SPWM) 11-7
- SYNCR D-7
- Synthesizer lock flag (SLOCK) D-8
- SYPCR D-12
- SYS D-9
- SYSRST (system reset) 5-40
- System
 - clock 5-3
 - block diagram 5-4
 - output (CLKOUT) 5-25
 - sources 5-4
 - frequencies 5-9
 - integration
 - module. *See* SIM 5-1, D-4
 - test register - ECLK (SIMTRE) D-9
 - memory maps. *See* Memory maps 3-13
 - protection control register (SYPCR) D-12
 - reset (SYS) D-9

-T-

- T D-3
- T2CG 11-14, D-72
- Table stepper motor (TSM) 11-10
- TBB 10-1
- TBL 4-15
- TBRS1 D-56
- TBRS2 D-56
- TC 9-29, D-44
- TCIE 9-29, D-43
- TCR D-73
- TCR1P 11-13, D-71
- TCR2 clock/gate control (T2CG) D-72
- TCR2P D-72
- TDR 9-26
- TDRE 9-28, D-44
- TE D-43
- Temporary register A (ATEMP) 4-21
- Test
 - module
 - repetition count (TSTRC) D-21
 - shift count register (TSTSC) D-21
 - submodule
 - control register (CREG) D-21
 - reset (TST) D-9
- Thermal characteristics A-2
- Three-state control (TSC) 5-48
- TICR 11-13, D-75
- TIE 9-29, D-43
- Time
 - base

- bus driver for MCSM 10-9
- buses (TBB) 10-1, 10-2
 - allocation 10-3
 - register bus select bits (TBRS1/0) D-56
- processor unit. *See* TPU 11-1
- quanta clock 13-8
- stamp 13-4, 13-10
- TIMER D-89
- Timer
 - count register
 - 1 prescaler control (TCR1P) D-71
 - 2 prescaler control (TCR2P) D-72
 - synchronize mode (TSYNC) D-87
- TOR1 D-34
- TOR2 D-35
- TouCAN
 - address
 - map D-80
 - space 13-2
 - bit timing configuration 13-8
 - operation 13-9
 - block diagram 13-1
 - disable (FRZACK) D-83
 - external pins 13-2
 - features 3-3
 - function 13-1
 - initialization sequence 13-11
 - interrupts 13-18
 - message buffer address map D-82
 - not ready (NOTRDY) D-83
 - operation 13-3
 - receive process 13-13
 - registers
 - control register 0 (CANCTRL0) D-85
 - control register 1 (CTRL1) 13-8
 - control register 1 (CANCTRL1) D-87
 - control register 2 (CANCTRL2) D-88
 - control register 2 (CTRL2) 13-8
 - error and status register (ESTAT) D-91
 - free running timer register (TIMER) D-89
 - interrupt
 - configuration register (CANICR) D-85
 - flag register (IFLAG) D-93
 - mask register (IMASK) D-93
 - module configuration register (CANMCR) D-82
 - receive
 - buffer 14 mask registers (RX14MSKHI/LO) D-90
 - buffer 15 mask registers (RX15MSKHI/LO) D-90
 - global mask registers (RXGMSKLO/HI) D-90
 - RX/TX error counter registers (RXECTR/TXECTR) D-94
 - test configuration register (CANTCR) D-85
 - special operating modes 13-16
 - auto power save mode 13-18
 - debug mode 13-16
 - low-power stop mode 13-17
 - transmit process 13-12

TPU

- A mask functions 11-6
 - discrete input/output (DIO) 11-6
 - input capture/input transition counter (ITC) 11-6
 - output compare (OC) 11-7
 - period
 - /pw accumulator (PPWA) 11-9
 - measurement
 - add transition detect (PMA) 11-7
 - missing transition detect (PMM) 11-8
 - position-synch pulse generator (PSP) 11-8
 - pulse width modulation (PWM) 11-7
 - quadrature decode (QDEC) 11-10
 - stepper motor (SM) 11-9
 - synch pw modulation (SPWM) 11-7
- address map D-70, D-71
- block diagram 11-1
- components 11-2
- features 3-2
- FREEZE flag (TPUF) D-75
- function library 11-5
- G mask functions 11-10
 - brushless motor commutation (COMM) 11-12
 - fast quadrature decode (FQD) 11-12
 - frequency measurement (FQM) 11-12
 - hall effect decode (HALLD) 11-13
 - multichannel pulse width modulation (PCPWM) 11-11
 - newinputcapture/transitioncounter(NITC) 11-11
 - programmable time accumulator (PTA) 11-11
 - queued output match (QOM) 11-11
 - table stepper motor (TSM) 11-10
 - universal asynchronous receiver/transmitter (UART) 11-12
- host interface 11-3
- interrupts 11-5
- microengine 11-3
- operation 11-3
 - coherency 11-4
 - emulation support 11-5
 - event timing 11-3
 - interchannel communication 11-4
 - programmable channel service priority 11-4
- overview 11-1
- parameter RAM 11-3, D-78
 - address map D-79
- registers
 - channel
 - function select registers (CFSR) D-75
 - interrupt
 - enable register (CIER) 11-5, D-75
 - status register (CISR) 11-5, D-78
 - priority registers (CPR) D-77
 - decoded channel number register (DCNR) D-78
- development
 - support control register (DSCR) D-73
 - support status register (DSSR) D-74
- host
 - sequence registers (HSQR) D-76
 - service request registers (HSSR) D-77

- link register (LR) D-78
- module configuration register (TPUMCR) D-71
- service grant latch register (SGLR) D-78
- test configuration register (TCR) D-73
- TPU interrupt configuration register (TICR) D-75

- scheduler 11-3

- time

- bases 11-2

- timer channels 11-2

- timing (electricals) A-24

- TPU Reference Manual* 11-3, 11-16, 11-17

- TPUF D-75

- TPUMCR 11-13, D-71

- TPURAM

- address map D-79

- array

- address mapping 12-1

- base address (ADDR) D-80

- space (RASP) D-80

- features 3-2

- general 12-1

- operation

- normal 12-2

- standby 12-2

- privilege level 12-2

- register block 12-1

- registers

- base address and status register (TRAMBAR) D-80

- module configuration register (TRAMMCR) D-80

- test register (TRAMTST) D-80

- reset 12-3

- TPU microcode emulation 12-3

- tPWMAX 10-18

- tPWMIN 10-18

- TR D-53

- Trace

- enable field (T) D-3

- on instruction execution 4-19

- TRAMBAR 12-1, D-80

- TRAMMCR 12-1, D-80

- TRAMTST 12-1, D-80

- Transfer

- length options 9-18

- time 8-13

- Transistion-sensitivity 5-50

- Transmission

- complete

- (TC) flag 9-29

- interrupt enable (TCIE) 9-29

- Transmit

- /receive status (TX/RX) D-92

- bit error (BITERR) D-91

- complete

- bit (TC) D-44

- interrupt enable (TCIE) D-43

- data

- (TXD) pin 9-26

- register empty (TDRE) flag 9-28, D-44

- error status flag (TXWARN) D-92





interrupt enable (TIE) 9-29, D-43
pin configuration control (TXMODE) D-86
RAM 9-8
Transmitter enable (TE) 9-28, D-43
Trigger event 8-29
TSC 5-48
TSM 11-10
T_{SR} 8-6
TST D-9
TSTME 3-8, 3-10, 3-12
TSTMSR D-20
TSTRC D-21
TSTSC D-21
TSYNC D-87
TX
 Length 13-4
TX/RX D-92
TXD 9-26
TXECTR D-94
TXMODE D-86
TXWARN D-92
Typical ratings (electrical) A-2

–U–

UART 11-12
Unimplemented instruction emulation 4-19
Universal asynchronous receiver/transmitter (UART)
 11-12
User stack pointer (USP) 4-10
Using the TPU Function Library and TPU Emulation
 Mode 11-5
USP 4-10

–V–

V (overflow) flag 4-6, D-4
Variable pulse width signal generator (prescaler) 8-25
VBR 4-7, 4-16
V_{DD} 3-8, 5-47, 6-1, 8-6, 12-1
 ramp time 5-47
V_{DDA} 3-8, 8-5
V_{DDA/2} 8-15
V_{DDSYN} 3-8, 5-47
VECT D-56
Vector base register (VBR) 3-13, 4-7, 4-16, 5-49
V_{IH} 8-8
V_{IL} 8-8
Virtual memory 4-9
Voltage
 controlled oscillator (VCO)
 frequency ramp time 5-47
 reference pins 8-5
V_{PP} C-2
V_{RH} 3-8, 8-5, 8-15, D-37
V_{RL} 3-8, 8-5, 8-15, D-37
V_{SS} 3-8, 8-6, 12-2
V_{SSA} 3-8, 8-5
V_{STBY} 3-8, 6-2, 12-1, 12-2

–W–

W bit D-8
WAIT 7-3, D-24
Wait states (WAIT) D-24
WAKE 9-31, D-43
Wake interrupt (WAKEINT) D-93
WAKEINT 13-17, D-93
WAKEMSK 13-17, D-83
Wakeup
 address mark (WAKE) 9-31, D-43
 functions 9-2
 interrupt mask (WAKEMSK) D-83
Wired-OR
 mode
 for QSPI pins (WOMQ) D-48
 for SCI pins (WOMS) 9-28, D-43
 mode (WOR) D-62
WOMQ D-48
WOMS 9-28, D-43
WOR D-62
Wrap
 enable (WREN) D-50
 to (WRTO) D-50
Wraparound mode 9-7
 master 9-20
 slave 9-22
WREN D-50
Write cycle 5-27
 flowchart 5-28
 timing diagram A-11
WRTO D-50

–X–

X
 (extend) flag 4-6, D-4
 bit in SYNCR D-8
XTRST (external reset) 5-40

–Y–

Y field D-8

–Z–

Z (zero) flag 4-6, D-4

