



PREFACE

**Section 1
OVERVIEW**

1.1	Block Diagram	1-1
1.2	MPC555 / MPC556 Features	1-2
1.2.1	RISC MCU Central Processing Unit (RCPU)	1-2
1.2.2	Four-Bank Memory Controller	1-3
1.2.3	U-Bus System Interface Unit (USIU)	1-3
1.2.4	Flexible Memory Protection Unit.	1-3
1.2.5	448 Kbytes of CDR MoneT Flash EEPROM Memory (CMF)	1-3
1.2.6	26 Kbytes of Static RAM.	1-3
1.2.7	General-Purpose I/O Support.	1-4
1.2.8	Two Time Processor Units (TPU3).	1-4
1.2.9	18-Channel Modular I/O System (MIOS1)	1-4
1.2.10	Two Queued Analog-to-Digital Converter Modules (QADC)	1-4
1.2.11	Two CAN 2.0B Controller Modules (TouCANs)	1-5
1.2.12	Queued Serial Multi-Channel Module (QSMCM)	1-5
1.3	MPC555 / MPC556 Address Map	1-5

**Section 2
SIGNAL DESCRIPTIONS**

2.1	Packaging and Pinout Descriptions	2-1
2.2	Pin Functionality.	2-6
2.3	Signal Descriptions	2-12
2.3.1	USIU Pads	2-12
2.3.1.1	ADDR[8:31]/SGPIOA[8:31].	2-12
2.3.1.2	DATA[0:31]/SGPIOD[0:31].	2-13
2.3.1.3	$\overline{\text{IRQ}}[0]/\text{SGPIOC}[0]$	2-13
2.3.1.4	$\overline{\text{IRQ}}[1]/\overline{\text{RSV}}/\text{SGPIOC}[1]$	2-13
2.3.1.5	$\overline{\text{IRQ}}[2]/\overline{\text{CR}}/\text{SGPIOC}[2]/\overline{\text{MTS}}$	2-13
2.3.1.6	$\overline{\text{IRQ}}[3]/\overline{\text{KR}}/\overline{\text{RETRY}}/\text{SGPIOC}[3]$	2-13
2.3.1.7	$\overline{\text{IRQ}}[4]/\text{AT}[2]/\text{SGPIOC}[4]$	2-14
2.3.1.8	$\overline{\text{IRQ}}[5]/\text{SGPIOC}[5]/\text{MODCK}[1]$	2-14
2.3.1.9	$\overline{\text{IRQ}}[6:7]/\text{MODCK}[2:3]$	2-14
2.3.1.10	TSIZ[0:1].	2-14
2.3.1.11	$\text{RD}/\overline{\text{WR}}$	2-15
2.3.1.12	$\overline{\text{BURST}}$	2-15
2.3.1.13	$\overline{\text{BDIP}}$	2-15
2.3.1.14	$\overline{\text{TS}}$	2-15
2.3.1.15	$\overline{\text{TA}}$	2-15



2.3.1.16	$\overline{\text{TEA}}$	2-15
2.3.1.17	$\overline{\text{RSTCONF/TEXP}}$	2-16
2.3.1.18	$\overline{\text{OE}}$	2-16
2.3.1.19	$\overline{\text{BI/STS}}$	2-16
2.3.1.20	$\overline{\text{CS}}[0:3]$	2-16
2.3.1.21	$\overline{\text{WE}}[0:3]/\overline{\text{BE}}[0:3]/\overline{\text{AT}}[0:3]$	2-16
2.3.1.22	$\overline{\text{PORESET}}$	2-17
2.3.1.23	$\overline{\text{HRESET}}$	2-17
2.3.1.24	$\overline{\text{SRESET}}$	2-17
2.3.1.25	$\text{SGPIOC}[6]/\overline{\text{FRZ/PTR}}$	2-17
2.3.1.26	$\text{SGPIOC}[7]/\overline{\text{IRQOUT/LWP}}[0]$	2-18
2.3.1.27	$\overline{\text{BG/VF}}[0]/\text{LWP}[1]$	2-18
2.3.1.28	$\overline{\text{BR/VF}}[1]/\text{IWP}[2]$	2-18
2.3.1.29	$\overline{\text{BB/VF}}[2]/\text{IWP}[3]$	2-18
2.3.1.30	$\text{IWP}[0:1]/\text{VFLS}[0:1]$	2-19
2.3.1.31	TMS	2-19
2.3.1.32	TDI/DSDI	2-19
2.3.1.33	TCK/DSCK	2-19
2.3.1.34	TDO/DSDO	2-19
2.3.1.35	$\overline{\text{TRST}}$	2-20
2.3.1.36	XTAL	2-20
2.3.1.37	EXTAL	2-20
2.3.1.38	XFC	2-20
2.3.1.39	CLKOUT	2-20
2.3.1.40	EXTCLK	2-20
2.3.1.41	VDDSYN	2-20
2.3.1.42	VSSSYN	2-20
2.3.1.43	ENGCLK/BUCLK	2-21
2.3.2	QSMCM PADS	2-21
2.3.2.1	$\text{PCS0}/\overline{\text{SS}}/\text{QGPI0}[0]$	2-21
2.3.2.2	$\text{PCS}(1:3)/\text{QGPI0}[1:3]$	2-21
2.3.2.3	$\text{MISO/QGPI0}[4]$	2-21
2.3.2.4	$\text{MOSI/QGPI0}[5]$	2-21
2.3.2.5	$\text{SCK/QGPI0}[6]$	2-22
2.3.2.6	$\text{TXD}[1:2]/\text{QGPI0}[1:2]$	2-22
2.3.2.7	$\text{RXD}[1:2]/\text{QGPI0}[1:2]$	2-22
2.3.2.8	ECK	2-22
2.3.3	MIOS PADS	2-22
2.3.3.1	$\text{MDA}[11], [13]$	2-22
2.3.3.2	$\text{MDA}[12], [14]$	2-23
2.3.3.3	$\text{MDA}[15], [27:31]$	2-23
2.3.3.4	$\text{MPWM}[0:3], [16:19]$	2-23
2.3.3.5	$\text{VF}[0:2]/\text{MPIO32B}[0:2]$	2-23

Paragraph Number

Page Number



2.3.3.6	VFLS[0:1]/MPIO32B[3:4]	2-23
2.3.3.7	MPIO32B[5:15]	2-24
2.3.4	TPU_A/TPU_B PADS	2-24
2.3.4.1	TPUCH[0:15]_[A:B]	2-24
2.3.4.2	T2CLK	2-24
2.3.5	QADC_A/QADC_B PADS	2-24
2.3.5.1	ETRIG[1:2]	2-24
2.3.5.2	AN[0]/ANW/PQB[0]_[A:B]	2-24
2.3.5.3	AN[1]/ANX/PQB[1]_[A:B]	2-24
2.3.5.4	AN[2]/ANY/PQB[2]_[A:B]	2-25
2.3.5.5	AN[3]/ANZ/PQB[3]_[A:B]	2-25
2.3.5.6	AN[48:51]/PQB[4:7]_[A:B]	2-25
2.3.5.7	AN[52:54]/MA[0:2]/PQA[0:2]_[A:B]	2-25
2.3.5.8	AN[55:59]/PQA[3:7]_[A:B]	2-26
2.3.5.9	VRH	2-26
2.3.5.10	VRL	2-26
2.3.5.11	VDDA	2-26
2.3.5.12	VSSA	2-26
2.3.6	TOUCAN_A/TOUCAN_B PADS	2-26
2.3.6.1	CNTX0_[A:B]	2-26
2.3.6.2	CNRX0_[A:B]	2-26
2.3.7	CMF PADS	2-27
2.3.7.1	EPEE	2-27
2.3.7.2	VPP	2-27
2.3.7.3	VDDF	2-27
2.3.7.4	VSSF	2-27
2.3.8	GLOBAL POWER SUPPLIES	2-27
2.3.8.1	VDDL	2-27
2.3.8.2	VDDH	2-27
2.3.8.3	VDDI	2-27
2.3.8.4	VSSI	2-27
2.3.8.5	KAPWR	2-28
2.3.8.6	VDDSRAM	2-28
2.3.8.7	VSS	2-28
2.4	Reset State	2-28
2.4.1	Pin Functionality Out of Reset	2-28
2.4.2	Pad Module Configuration Register (PDMCR)	2-28
2.4.3	Pin State During Reset	2-29
2.4.4	Power-On Reset and Hard Reset	2-30
2.4.5	Pull-Up and Pull-Down Enable and Disable for 5-V Only Pins	2-30
2.4.6	Pull-Up and Pull-Down Enable and Disable for 3-V / 5-V Multiplexed Pins	2-30
2.4.6.1	PRDS Signal	2-30
2.4.6.2	Encoded 3-V / 5-V Select	2-31

Paragraph Number

Page Number



2.4.6.3 Examples	2-31
2.4.7 Special Pull Resistor Disable Control (SPRDS)	2-31
2.4.8 Pin Reset States	2-32
2.5 Pad Types	2-37
2.5.1 Pad Interface Signals	2-37
2.5.2 Three-Volt Output Pad	2-38
2.5.2.1 Type A Interface	2-38
2.5.2.2 Type B Interface (Clock Pad)	2-39
2.5.3 Three-Volt Input Pad	2-39
2.5.3.1 Type C Interface	2-40
2.5.3.2 Type CH Interface	2-40
2.5.3.3 Type CNH Interface	2-41
2.5.3.4 Type D Interface	2-41
2.5.4 Three-Volt Input/Output Pad	2-41
2.5.4.1 Type E Interface	2-42
2.5.4.2 Type EOH Interface	2-42
2.5.4.3 Type F Interface	2-43
2.5.4.4 Type G Interface	2-44
2.5.5 Five-Volt Input/Output Pad	2-45
2.5.5.1 Type H Interface	2-45
2.5.5.2 Type I Interface	2-46
2.5.5.3 Type IH Interface	2-48
2.5.5.4 Type J Interface	2-49
2.5.5.5 Type JD Interface	2-49
2.5.6 Type K Interface (EPEE Pad)	2-50
2.5.7 Analog Pads	2-51
2.5.7.1 Type L Interface (QADC Port A)	2-51
2.5.7.2 Type M Interface (QADC Port B)	2-52
2.5.7.3 Type N Interface (ETRIG)	2-53
2.5.8 Pads with Fast Mode	2-53
2.5.8.1 Type O Interface (QSMCM Pads)	2-53
2.5.8.2 Type P Interface (TPU and MIOS Pads)	2-54
2.5.9 5V Input, 5V Output Pads	2-55
2.5.9.1 5V Output (Type Q)	2-55
2.5.9.2 Type R Interface	2-56
2.5.9.3 5V Output for Clock Pad	2-57
2.6 Pad Groups	2-57
2.7 Pin Names and Abbreviations	2-58

Section 3 CENTRAL PROCESSING UNIT

3.1 RCPU Features	3-1
3.2 RCPU Block Diagram	3-2

Paragraph Number

Page Number



3.3 Instruction Sequencer	3-3
3.4 Independent Execution Units	3-4
3.4.1 Branch Processing Unit (BPU)	3-5
3.4.2 Integer Unit (IU)	3-5
3.4.3 Load/Store Unit (LSU)	3-6
3.4.4 Floating-Point Unit (FPU)	3-6
3.5 Levels of the PowerPC Architecture	3-7
3.6 RCPU Programming Model	3-7
3.7 PowerPC UISA Register Set	3-11
3.7.1 General-Purpose Registers (GPRs)	3-12
3.7.2 Floating-Point Registers (FPRs)	3-12
3.7.3 Floating-Point Status and Control Register (FPSCR)	3-12
3.7.4 Condition Register (CR)	3-15
3.7.4.1 Condition Register CR0 Field Definition	3-16
3.7.4.2 Condition Register CR1 Field Definition	3-16
3.7.4.3 Condition Register CR n Field — Compare Instruction	3-17
3.7.5 Integer Exception Register (XER)	3-17
3.7.6 Link Register (LR)	3-18
3.7.7 Count Register (CTR)	3-19
3.8 PowerPC VEA Register Set — Time Base	3-19
3.9 PowerPC OEA Register Set	3-20
3.9.1 Machine State Register (MSR)	3-20
3.9.2 DAE/Source Instruction Service Register (DSISR)	3-22
3.9.3 Data Address Register (DAR)	3-22
3.9.4 Time Base Facility (TB) — OEA	3-23
3.9.5 Decrementer Register (DEC)	3-23
3.9.6 Machine Status Save/Restore Register 0 (SRR0)	3-24
3.9.7 Machine Status Save/Restore Register 1 (SRR1)	3-24
3.9.8 General SPRs (SPRG0–SPRG3)	3-25
3.9.9 Processor Version Register (PVR)	3-25
3.9.10 Implementation-Specific SPRs	3-26
3.9.10.1 EIE, EID, and NRI Special-Purpose Registers	3-26
3.9.10.2 Floating-Point Exception Cause Register (FPECR)	3-26
3.9.10.3 Additional Implementation-Specific Registers	3-27
3.10 Instruction Set	3-28
3.10.1 Instruction Set Summary	3-29
3.10.2 Recommended Simplified Mnemonics	3-33
3.10.3 Calculating Effective Addresses	3-33
3.11 Exception Model	3-34
3.11.1 Exception Classes	3-34
3.11.2 Ordered Exceptions	3-34
3.11.3 Unordered Exceptions	3-34
3.11.4 Precise Exceptions	3-35

Paragraph Number

Page Number



3.11.5 Exception Vector Table	3-35
3.12 Instruction Timing	3-36
3.13 PowerPC User Instruction Set Architecture (UISA)	3-38
3.13.1 Computation Modes	3-38
3.13.2 Reserved Fields	3-38
3.13.3 Classes of Instructions	3-38
3.13.4 Exceptions	3-39
3.13.5 The Branch Processor	3-39
3.13.6 Instruction Fetching	3-39
3.13.7 Branch Instructions	3-39
3.13.7.1 Invalid Branch Instruction Forms	3-39
3.13.7.2 Branch Prediction	3-39
3.13.8 The Fixed-Point Processor	3-39
3.13.8.1 Fixed-Point Instructions	3-39
3.13.9 Floating-Point Processor	3-40
3.13.9.1 General	3-40
3.13.9.2 Optional instructions	3-40
3.13.10 Load/Store Processor	3-40
3.13.10.1 Fixed-Point Load With Update and Store With Update Instructions	3-41
3.13.10.2 Fixed-Point Load and Store Multiple Instructions	3-41
3.13.10.3 Fixed-Point Load String Instructions	3-41
3.13.10.4 Storage Synchronization Instructions	3-41
3.13.10.5 Floating-Point Load and Store With Update Instructions	3-41
3.13.10.6 Floating-Point Load Single Instructions	3-41
3.13.10.7 Floating-Point Store Single Instructions	3-41
3.13.10.8 Optional Instructions	3-42
3.13.10.9 Little-Endian Byte Ordering	3-42
3.14 PowerPC Virtual Environment Architecture (VEA)	3-42
3.14.1 Atomic Update Primitives	3-42
3.14.2 Effect of Operand Placement on Performance	3-42
3.14.3 Storage Control Instructions	3-42
3.14.4 Instruction Synchronize (isync) Instruction	3-42
3.14.4.1 Enforce In-Order Execution of I/O (eieio) Instruction	3-43
3.14.5 Timebase	3-43
3.15 POWERPC Operating Environment Architecture (OEA)	3-43
3.15.1 Branch Processor Registers	3-43
3.15.1.1 Machine State Register (MSR)	3-43
3.15.1.2 Branch Processors Instructions	3-43
3.15.2 Fixed-Point Processor	3-43
3.15.2.1 Special Purpose Registers	3-43
3.15.3 Storage Control Instructions	3-44
3.15.4 Interrupts	3-44
3.15.4.1 System Reset Interrupt	3-44



3.15.4.2 Machine Check Interrupt	3-45
3.15.4.3 Data Storage Interrupt	3-45
3.15.4.4 Instruction Storage Interrupt	3-46
3.15.4.5 Alignment Interrupt	3-46
3.15.4.6 Floating-Point Enabled Exception Type Program Interrupt	3-46
3.15.4.7 Illegal Instruction Type Program Interrupt	3-46
3.15.4.8 Privileged Instruction Type Program interrupt	3-46
3.15.4.9 Floating-Point Unavailable Interrupt	3-47
3.15.4.10 Trace Interrupt	3-47
3.15.4.11 Floating-Point Assist Interrupt	3-47
3.15.4.12 Implementation-Dependent Software Emulation Interrupt	3-48
3.15.4.13 Implementation-Specific Instruction Storage Protection Error Interrupt	3-49
3.15.4.14 Implementation-Specific Data Storage Protection Error Interrupt	3-50
3.15.4.15 Implementation-Specific Debug Interrupts	3-51
3.15.4.16 Partially Executed Instructions	3-52
3.15.5 Timer Facilities	3-53
3.15.6 Optional Facilities and Instructions	3-53

Section 4 BURST BUFFER

4.1 Burst Buffer Block Diagram	4-1
4.2 Burst Buffer Features	4-2
4.3 Instruction VocabularyBased Compression Model Main Principles	4-3
4.3.1 Compression Model Features	4-3
4.3.2 Model Limitations	4-4
4.3.3 Vocabulary Based Instruction Compression Algorithm	4-4
4.3.4 Memory Organization	4-6
4.3.5 Compressed Code Address Format	4-8
4.3.6 Compressed Address Format – Direct Branches	4-9
4.3.7 Compressed Address Format – Indirect Branches	4-11
4.3.8 Compression Process	4-11
4.3.9 Decompression	4-13
4.3.10 Compression Environment Initialization	4-14
4.4 Modes Of Operation	4-14
4.4.1 Normal Operation	4-15
4.4.2 Slave Operation	4-15
4.4.3 Reset Operation	4-15
4.4.4 Debug Mode Operation	4-15
4.4.5 Standby Mode Operation	4-15
4.4.6 Burst Operation	4-15
4.4.7 Error Detection	4-16
4.5 Exception Table Relocation	4-16
4.5.1 Exception Table Relocation Operation	4-17



4.6	Burst Buffer Programming Model	4-20
4.6.1	Region Base Address Registers	4-21
4.6.2	Region Attribute Registers MI_RA[0:3] Description	4-21
4.6.3	Global Region Attribute Register Description (MI_GRA)	4-23
4.6.4	BBC Module Configuration Register (BBCMCR)	4-24

Section 5 UNIFIED SYSTEM INTERFACE UNIT

5.1	Module Overview	5-1
5.2	SIU Architecture	5-2
5.3	USIU Address Map	5-2
5.4	USIU PowerPC Memory Map	5-5

Section 6 SYSTEM CONFIGURATION AND PROTECTION

6.1	System Configuration	6-3
6.1.1	USIU Pins Multiplexing	6-3
6.1.2	Memory Mapping	6-3
6.1.3	Arbitration Support	6-4
6.2	External Master Modes	6-5
6.2.1	Operation of External Master Modes	6-5
6.2.2	Address Decoding for External Accesses	6-6
6.3	USIU General-Purpose I/O	6-6
6.4	Interrupt Controller	6-8
6.4.1	SIU Interrupt Sources Priority	6-11
6.5	Hardware Bus Monitor	6-12
6.6	MPC555 / MPC556 Decrementer	6-12
6.7	MPC555 / MPC556 Time Base (TB)	6-13
6.8	Real-Time Clock (RTC)	6-14
6.9	Periodic Interrupt Timer (PIT)	6-15
6.10	Software Watchdog Timer (SWT)	6-16
6.11	Freeze Operation	6-17
6.12	Low Power Stop Operation	6-17
6.13	System Configuration and Protection Registers	6-18
6.13.1	System Configuration Registers	6-18
6.13.1.1	SIU Module Configuration Register	6-18
6.13.1.2	Internal Memory Map Register	6-21
6.13.1.3	External Master Control Register (EMCR)	6-22
6.13.2	SIU Interrupt Registers	6-23
6.13.2.1	SIPEND Register	6-23
6.13.2.2	SIU Interrupt Mask Register (SIMASK)	6-24
6.13.2.3	SIU Interrupt Edge Level Register (SIEL)	6-25
6.13.2.4	SIU Interrupt Vector Register	6-25
6.13.3	System Protection Registers	6-26



6.13.3.1	System Protection Control Register (SYPCR)	6-26
6.13.3.2	Software Service Register (SWSR)	6-26
6.13.3.3	Transfer Error Status Register (TESR).	6-27
6.13.4	System Timer Registers	6-28
6.13.4.1	Decrementer Register	6-28
6.13.4.2	Time Base SPRs	6-28
6.13.4.3	Time Base Reference Registers.	6-29
6.13.4.4	Time Base Control and Status Register.	6-29
6.13.4.5	Real-Time Clock Status and Control Register	6-30
6.13.4.6	Real-Time Clock Register (RTC)	6-31
6.13.4.7	Real-Time Clock Alarm Register (RTCAL).	6-31
6.13.4.8	Periodic Interrupt Status and Control Register (PISCR).	6-32
6.13.4.9	Periodic Interrupt Timer Count Register (PITC)	6-32
6.13.4.10	Periodic Interrupt Timer Register (PITR)	6-33
6.13.5	General-Purpose I/O Registers	6-34
6.13.5.1	SGPIO Data Register 1 (SGPIODT1).	6-34
6.13.5.2	SGPIO Data Register 2 (SGPIODT2).	6-34
6.13.5.3	SGPIO Control Register (SGPIOCR).	6-35

Section 7 RESET

7.1	Reset Operation	7-1
7.1.1	Power On Reset	7-1
7.1.2	Hard Reset	7-2
7.1.3	Soft Reset.	7-2
7.1.4	Loss of Lock	7-3
7.1.5	On-Chip Clock Switch.	7-3
7.1.6	Software Watchdog Reset	7-3
7.1.7	Checkstop Reset	7-3
7.1.8	Debug Port Hard Reset	7-3
7.1.9	Debug Port Soft Reset	7-3
7.1.10	JTAG Reset	7-3
7.2	Reset Actions Summary.	7-3
7.3	Data Coherency During Reset	7-4
7.4	Reset Status Register	7-5
7.5	Reset Configuration	7-6
7.5.1	Hard Reset Configuration	7-6
7.5.2	Hard Reset Configuration Word	7-11
7.5.3	Soft Reset Configuration	7-12

Section 8 CLOCKS AND POWER CONTROL

8.1	Overview	8-1
8.2	System Clock Sources.	8-3

Paragraph Number

Page Number



8.3 System PLL	8-3
8.3.1 Frequency Multiplication	8-4
8.3.2 Skew Elimination	8-4
8.3.3 Pre-Divider	8-4
8.3.4 PLL Block Diagram	8-4
8.3.5 PLL Pins	8-5
8.4 System Clock During PLL Loss of Lock	8-6
8.5 Low-Power Divider	8-6
8.6 MPC555 / MPC556 Internal Clock Signals	8-7
8.6.1 General System Clocks	8-9
8.6.2 CLKOUT	8-12
8.6.3 Engineering Clock	8-12
8.7 Clock Source Switching	8-13
8.8 Low-Power Modes	8-15
8.8.1 Entering a Low-Power Mode	8-15
8.8.2 Power Mode Descriptions	8-16
8.8.3 Exiting from Low-Power Modes	8-16
8.8.3.1 Exiting from Normal-Low Mode	8-17
8.8.3.2 Exiting from Doze Mode	8-17
8.8.3.3 Exiting from Deep-Sleep Mode	8-17
8.8.3.4 Exiting from Power-Down Mode	8-18
8.8.3.5 Low-Power Modes Flow	8-18
8.9 Basic Power Structure	8-20
8.9.1 Clock Unit Power Supply	8-20
8.9.2 Chip Power Structure	8-20
8.9.2.1 VDDL	8-20
8.9.2.2 VDDI	8-20
8.9.2.3 VDDSYN, VSSSYN	8-21
8.9.2.4 KAPWR	8-21
8.9.2.5 VDDA, VSSA	8-21
8.9.2.6 VPP	8-21
8.9.2.7 VDDF, VSSF	8-21
8.9.2.8 VDDH	8-21
8.9.2.9 VDDSRAM	8-21
8.9.2.10 VSS	8-21
8.9.3 Keep Alive Power	8-22
8.9.3.1 Keep Alive Power Configuration	8-22
8.9.3.2 Keep Alive Power Registers Lock Mechanism	8-23
8.10 VDDSRAM Supply Failure Detection	8-25
8.11 Power Up/Down Sequencing	8-25
8.12 Clocks Unit Programming Model	8-29
8.12.1 System Clock Control Register (SCCR)	8-30
8.12.2 PLL, Low-Power, and Reset-Control Register (PLPRCR)	8-33



8.12.3 Change of Lock Interrupt Register (COLIR)	8-35
8.12.4 VDDSRAM Control Register (VSRMCR)	8-36

Section 9

EXTERNAL BUS INTERFACE

9.1 Features	9-1
9.2 Bus Transfer Signals	9-1
9.3 Bus Control Signals	9-2
9.4 Bus Interface Signal Descriptions	9-3
9.5 Bus Operations	9-7
9.5.1 Basic Transfer Protocol	9-8
9.5.2 Single Beat Transfer	9-8
9.5.2.1 Single Beat Read Flow	9-8
9.5.2.2 Single Beat Write Flow	9-11
9.5.2.3 Single Beat Flow with Small Port Size	9-14
9.5.3 Burst Transfer	9-15
9.5.4 Burst Mechanism	9-16
9.5.5 Alignment and Packaging of Transfers	9-28
9.5.6 Arbitration Phase	9-30
9.5.6.1 Bus Request	9-31
9.5.6.2 Bus Grant	9-32
9.5.6.3 Bus Busy	9-32
9.5.6.4 Internal Bus Arbiter	9-33
9.5.7 Address Transfer Phase Signals	9-35
9.5.7.1 Transfer Start	9-36
9.5.7.2 Address Bus	9-36
9.5.7.3 Read/Write	9-36
9.5.7.4 Burst Indicator	9-36
9.5.7.5 Transfer Size	9-37
9.5.7.6 Address Types	9-37
9.5.7.7 Burst Data in Progress	9-38
9.5.8 Termination Signals	9-38
9.5.8.1 Transfer Acknowledge	9-38
9.5.8.2 Burst Inhibit	9-39
9.5.8.3 Transfer Error Acknowledge	9-39
9.5.8.4 Termination Signals Protocol	9-39
9.5.9 Storage Reservation	9-40
9.5.10 Bus Exception Control Cycles	9-43
9.5.10.1 Retrying a Bus Cycle	9-43
9.5.10.2 Termination Signals Protocol Summary	9-47
9.5.11 Bus Operation in External Master Modes	9-47
9.5.12 Contention Resolution on External Bus	9-52
9.5.13 Show Cycle Transactions	9-54



Section 10 MEMORY CONTROLLER

10.1 Overview	10-1
10.2 Memory Controller Architecture	10-3
10.2.1 Associated Registers	10-4
10.2.2 Port Size Configuration.	10-5
10.2.3 Write-Protect Configuration	10-5
10.2.4 Address and Address Space Checking	10-5
10.2.5 Burst Support	10-5
10.3 Chip-Select Timing.	10-6
10.3.1 Memory Devices Interface Example.	10-7
10.3.2 Peripheral Devices Interface Example	10-8
10.3.3 Relaxed Timing Examples	10-10
10.3.4 Extended Hold Time on Read Accesses	10-14
10.3.5 Summary of GPCM Timing Options	10-18
10.4 Global (Boot) Chip-Select Operation	10-20
10.5 Write and Byte Enable Signals.	10-21
10.6 Dual Mapping of the Internal Flash EEPROM Array	10-21
10.7 Memory Controller External Master Support	10-24
10.8 Programming Model.	10-27
10.8.1 General Memory Controller Programming Notes	10-27
10.8.2 Memory Controller Status Registers (MSTAT).	10-28
10.8.3 Memory Controller Base Registers (BR0 – BR3)	10-28
10.8.4 Memory Controller Option Registers (OR0 – OR3)	10-30
10.8.5 Dual Mapping Base Register (DMBR)	10-31
10.8.6 Dual-Mapping Option Register	10-32

Section 11 L-BUS TO U-BUS INTERFACE (L2U)

11.1 General Features	11-1
11.2 DMPU Features	11-1
11.3 L2U Block Diagram	11-2
11.4 Modes Of Operation.	11-2
11.4.1 Normal Mode	11-3
11.4.2 Reset Operation	11-3
11.4.3 Factory Test Mode	11-3
11.4.4 Peripheral Mode	11-3
11.5 Data Memory Protection	11-4
11.5.1 Functional Description	11-4
11.5.2 Associated Registers	11-5
11.5.3 L-bus Memory Access Violations	11-7
11.6 Reservation Support	11-7
11.6.1 The Reservation Protocol.	11-7



11.6.2 L2U Reservation Support	11-7
11.6.3 Reserved Location (Bus) and Possible Actions	11-8
11.7 L-Bus Show Cycle Support	11-9
11.7.1 Programming Show Cycles	11-9
11.7.2 Performance Impact	11-9
11.7.3 Show Cycle Protocol	11-10
11.7.4 L-Bus Write Show Cycle Flow	11-10
11.7.5 L-Bus Read Show Cycle Flow	11-11
11.7.6 Show Cycle Support Guidelines	11-11
11.8 L2U Programming Model	11-12
11.8.1 U-bus Access	11-13
11.8.2 Transaction Size	11-13
11.8.3 L2U Module Configuration Register (L2U_MCR)	11-13
11.8.4 Region Base Address Registers (L2U_RBAx)	11-14
11.8.5 Region Attribute Registers (L2U_RAx)	11-15
11.8.6 Global Region Attribute Register	11-15

Section 12 U-BUS TO IMB3 BUS INTERFACE (UIMB)

12.1 Features	12-1
12.2 UIMB Block Diagram	12-2
12.3 Clock Module	12-2
12.4 Interrupt Operation	12-3
12.4.1 Interrupt Sources and Levels on IMB	12-4
12.4.2 IMB Interrupt Multiplexing	12-4
12.4.3 ILBS Sequencing	12-4
12.4.4 Interrupt Synchronizer	12-6
12.5 Programming Model	12-7
12.5.1 UIMB Module Configuration Register (UMCR)	12-7
12.5.2 Test control register (UTSTCREG)	12-8
12.5.3 Pending Interrupt Request Register (UIPEND)	12-8

Section 13 QUEUED ANALOG-TO-DIGITAL CONVERTER MODULE-64

13.1 Overview	13-1
13.2 Features	13-2
13.3 QADC64 Pin Functions	13-2
13.3.1 Port A Pin Functions	13-3
13.3.1.1 Port A Analog Input Pins	13-3
13.3.1.2 Port A Digital Input/Output Pins	13-3
13.3.2 Port B Pin Functions	13-4
13.3.2.1 Port B Analog Input Pins	13-4
13.3.2.2 Port B Digital Input Pins	13-4
13.3.3 External Trigger Input Pins	13-4

Paragraph Number

Page Number



13.3.4	Multiplexed Address Output Pins	13-4
13.3.5	Multiplexed Analog Input Pins	13-5
13.3.6	Voltage Reference Pins	13-5
13.3.7	Dedicated Analog Supply Pins	13-5
13.3.8	External Digital Supply Pin	13-5
13.3.9	Digital Supply Pins	13-5
13.4	QADC64 Bus Interface.	13-6
13.5	Module Configuration.	13-6
13.5.1	Low-Power Stop Mode	13-6
13.5.2	Freeze Mode	13-6
13.5.3	Supervisor/Unrestricted Address Space.	13-7
13.6	General-Purpose I/O Port Operation	13-7
13.6.1	Port Data Register	13-8
13.6.2	Port Data Direction Register.	13-8
13.7	External Multiplexing Operation.	13-9
13.8	Analog Input Channels.	13-10
13.9	Analog Subsystem.	13-11
13.9.1	Conversion Cycle Times.	13-12
13.9.1.1	Amplifier Bypass Mode Conversion Timing	13-13
13.9.2	Front-End Analog Multiplexer.	13-14
13.9.3	Digital-to-Analog Converter Array.	13-14
13.9.4	Comparator.	13-14
13.9.5	Successive Approximation Register.	13-14
13.10	Digital Control Subsystem	13-14
13.10.1	Queue Priority.	13-15
13.10.2	Queue Boundary Conditions	13-17
13.10.3	Scan Modes	13-18
13.10.3.1	Disabled Mode	13-18
13.10.3.2	Reserved Mode	13-18
13.10.3.3	Single-Scan Modes	13-18
13.10.3.4	Continuous-Scan Modes	13-21
13.10.4	QADC64 Clock (QCLK) Generation.	13-24
13.10.5	Periodic/Interval Timer	13-29
13.11	Interrupts	13-29
13.11.1	Interrupt Sources	13-30
13.11.2	Interrupt Register	13-31
13.11.3	Interrupt Levels and Time Multiplexing.	13-31
13.12	Programming Model.	13-31
13.12.1	QADC64 Module Configuration Register	13-33
13.12.2	QADC64 Test Register.	13-33
13.12.3	QADC64 Interrupt Register	13-33
13.12.4	Port A/B Data Register.	13-34
13.12.5	Port Data Direction Register.	13-35



13.12.6 QADC64 Control Register 0 (QACR0)	13-35
13.12.7 QADC64 Control Register 1 (QACR1)	13-36
13.12.8 QADC64 Control Register 2 (QACR2)	13-38
13.12.9 QADC64 Status Register 0 (QASR0)	13-40
13.12.10 QADC64 Status Register 1 (QASR1)	13-42
13.12.11 Conversion Command Word Table	13-43
13.12.12 Result Word Table	13-49

Section 14

QUEUED SERIAL MULTI-CHANNEL MODULE

14.1 Overview	14-1
14.2 Block Diagram	14-1
14.3 Signal Descriptions	14-2
14.4 Memory Map	14-2
14.5 QSMCM Global Registers	14-4
14.5.1 Low-Power Stop Operation	14-5
14.5.2 Freeze Operation	14-5
14.5.3 Access Protection	14-5
14.5.4 QSMCM Interrupts	14-6
14.5.5 QSMCM Configuration Register (QSMCMMCR)	14-7
14.5.6 QSMCM Test Register (QTEST)	14-8
14.5.7 QSMCM Interrupt Level Registers (QDSCI_IL, QSPI_IL)	14-8
14.6 QSMCM Pin Control Registers	14-9
14.6.1 Port QS Data Register (PORTQS)	14-10
14.6.2 PORTQS Pin Assignment Register (PQSPAR)	14-11
14.6.3 PORTQS Data Direction Register (DDRQS)	14-12
14.7 Queued Serial Peripheral Interface	14-13
14.7.1 QSPI Registers	14-15
14.7.1.1 QSPI Control Register 0	14-16
14.7.1.2 QSPI Control Register 1	14-18
14.7.1.3 QSPI Control Register 2	14-18
14.7.1.4 QSPI Control Register 3	14-19
14.7.1.5 QSPI Status Register	14-20
14.7.2 QSPI RAM	14-21
14.7.2.1 Receive RAM	14-22
14.7.2.2 Transmit RAM	14-22
14.7.2.3 Command RAM	14-22
14.7.3 QSPI Pins	14-23
14.7.4 QSPI Operation	14-24
14.7.4.1 Enabling, Disabling, and Halting the SPI	14-25
14.7.4.2 QSPI Interrupts	14-26
14.7.4.3 QSPI Flow	14-26
14.7.5 Master Mode Operation	14-33

Paragraph Number

Page Number



14.7.5.1	Clock Phase and Polarity	14-34
14.7.5.2	Baud Rate Selection	14-34
14.7.5.3	Delay Before Transfer	14-35
14.7.5.4	Delay After Transfer	14-35
14.7.5.5	Transfer Length	14-36
14.7.5.6	Peripheral Chip Selects	14-36
14.7.5.7	Master Wraparound Mode	14-37
14.7.6	Slave Mode	14-37
14.7.6.1	Description of Slave Operation	14-39
14.7.7	Slave Wraparound Mode	14-40
14.7.8	Mode Fault	14-41
14.8	Serial Communication Interface	14-41
14.8.1	SCI Registers	14-44
14.8.2	SCI Control Register 0	14-45
14.8.3	SCI Control Register 1	14-45
14.8.4	SCI Status Register (SCxSR)	14-47
14.8.5	SCI Data Register (SCxDR)	14-49
14.8.6	SCI Pins	14-50
14.8.7	SCI Operation	14-50
14.8.7.1	Definition of Terms	14-50
14.8.7.2	Serial Formats	14-51
14.8.7.3	Baud Clock	14-51
14.8.7.4	Parity Checking	14-52
14.8.7.5	Transmitter Operation	14-52
14.8.7.6	Receiver Operation	14-54
14.8.7.7	Receiver Functional Operation	14-56
14.8.7.8	Idle-Line Detection	14-57
14.8.7.9	Receiver Wake-Up	14-58
14.8.7.10	Internal Loop Mode	14-58
14.9	SCI Queue Operation	14-58
14.9.1	Queue Operation of SCI1 for Transmit and Receive	14-58
14.9.2	Queued SCI1 Status and Control Registers	14-59
14.9.2.1	QSCI1 Control Register	14-59
14.9.2.2	QSCI1 Status Register	14-61
14.9.3	QSCI1 Transmitter Block Diagram	14-61
14.9.4	QSCI1 Additional Transmit Operation Features	14-62
14.9.5	QSCI1 Transmit Flow Chart Implementing the Queue	14-64
14.9.6	Example QSCI1 Transmit for 17 Data Bytes	14-66
14.9.7	Example SCI Transmit for 25 Data Bytes	14-67
14.9.8	QSCI1 Receiver Block Diagram	14-68
14.9.9	QSCI1 Additional Receive Operation Features	14-68
14.9.10	QSCI1 Receive Flow Chart Implementing The Queue	14-71
14.9.11	QSCI1 Receive Queue Software Flow Chart	14-72



14.9.12	Example QSCI1 Receive Operation of 17 Data Frames	14-73
---------	---	-------

Section 15

MODULAR INPUT/OUTPUT SUBSYSTEM (MIOS1)

15.1	MIOS1 Features	15-1
15.2	Submodule Numbering, Naming and Addressing	15-3
15.3	MIOS1 Signals	15-3
15.4	Block Diagram	15-4
15.5	MIOS1 Bus System	15-6
15.5.1	Read/Write and Control Bus	15-6
15.5.2	Request Bus	15-6
15.5.3	Counter Bus Set	15-6
15.6	MIOS1 Programmer's Model	15-6
15.7	MIOS1 I/O Ports	15-8
15.8	MIOS Bus Interface Submodule (MBISM)	15-8
15.8.1	MIOS Bus Interface (MBISM) Registers	15-8
15.8.1.1	MIOS1 Test and Pin Control Register	15-8
15.8.1.2	MIOS1 Vector Register	15-9
15.8.1.3	MIOS1 Module and Version Number Register	15-9
15.8.1.4	MIOS1 Module Configuration Register	15-9
15.8.2	MBISM Interrupt Registers	15-10
15.8.2.1	MIOS1 Interrupt Level Register 0 (MIOS1LVL0)	15-10
15.8.2.2	MIOS1 Interrupt Level Register 1 (MIOS1LVL1)	15-11
15.8.3	Interrupt Control Section (ICS)	15-11
15.9	MIOS Counter Prescaler Submodule (MCPSM)	15-12
15.9.1	MIOS Counter Prescaler Submodule (MCPSM) Registers	15-12
15.9.1.1	MCPSM Status/Control Register (MCPSMCSR)	15-13
15.10	MIOS Modulus Counter Submodule (MMCSM)	15-13
15.10.1	MIOS Modulus Counter Submodule (MMCSM) Registers	15-15
15.10.1.1	MMCSM Up-Counter Register (MMCSMCNT)	15-16
15.10.1.2	MMCSM Modulus Latch Register (MMCSMML)	15-16
15.10.1.3	MMCSM Status/Control Register (Duplicated)	15-16
15.10.1.4	MMCSM Status/Control Register (MMCSMSCR)	15-17
15.11	MIOS Double Action Submodule (MDASM)	15-18
15.11.1	MIOS Double Action Submodule (MDASM) Registers	15-19
15.11.1.1	MDASM Data A Register	15-21
15.11.1.2	MDASM Data B Register (MDASMBR)	15-21
15.11.1.3	MDASM Status/Control Register (Duplicated)	15-22
15.11.1.4	MDASM Status/Control Register	15-23
15.12	MIOS Pulse Width Modulation Submodule (MPWMSM)	15-25
15.12.1	MIOS Pulse Width Modulation Submodule (MPWMSM) Registers	15-26
15.12.1.1	MPWMSM Period Register (MPWMSMPERR)	15-27
15.12.1.2	MPWMSM Pulse Width Register (MPWMSMPULR)	15-27

Paragraph Number

Page Number



15.12.1.3	MPWMSM Counter Register (MPWMSMCNTR)	15-28
15.12.1.4	MPWMSM Status/Control Register(MPWMSMCR)	15-28
15.13	MIOS 16-bit Parallel Port I/O Submodule (MPIO SM)	15-30
15.13.1	MIOS 16-bit Parallel Port I/O Submodule (MPIO SM) Registers.	15-30
15.13.1.1	MPIO SM Data Register (MPIO SM DR)	15-30
15.13.1.2	MPIO SM Data Direction Register (MPIO SM DDR)	15-31
15.14	MIOS1 Interrupts	15-31
15.14.1	MIOS Interrupt Request Submodule (MIR SM)	15-32
15.14.2	MIOS Interrupt Request Submodule 0 (MIR SM0) Registers	15-33
15.14.2.1	MIR SM0 Interrupt Status Register (MIOS1 SR0)	15-34
15.14.2.2	MIR SM0 Interrupt Enable Register (MIOS1 ER0)	15-35
15.14.2.3	MIR SM0 Request Pending Register (MIOS1 RPR0)	15-35
15.14.3	MIOS Interrupt Request Submodule 1 (MIR SM1) Registers	15-36
15.14.3.1	MIR SM1 Interrupt Status Register (MIOS1 SR1)	15-36
15.14.3.2	MIR SM1 Interrupt Enable Register (MIOS1 ER1)	15-37
15.14.3.3	MIR SM1 Request Pending Register (MIOS1 RPR1)	15-37
15.15	MIOS1 Function Examples	15-38
15.15.1	MIOS1 Input Double Edge Pulse Width Measurement	15-38
15.15.2	MIOS1 Input Double Edge Period Measurement	15-40
15.15.3	MIOS1 Double Edge Single Output Pulse Generation	15-41
15.15.4	MIOS1 Output Pulse Width Modulation With MDASM	15-42
15.15.5	MIOS1 Input Pulse Accumulation	15-43
15.16	MIOS1 Configuration	15-43

Section 16 CAN 2.0B CONTROLLER MODULE

16.1	Features	16-1
16.2	External Pins	16-2
16.3	TouCAN Architecture	16-3
16.3.1	TX/RX Message Buffer Structure	16-3
16.3.1.1	Common Fields for Extended and Standard Format Frames	16-4
16.3.1.2	Fields for Extended Format Frames	16-6
16.3.1.3	Fields for Standard Format Frames	16-6
16.3.1.4	Serial Message Buffers	16-6
16.3.1.5	Message Buffer Activation/Deactivation Mechanism	16-7
16.3.1.6	Message Buffer Lock/Release/Busy Mechanism	16-7
16.3.2	Receive Mask Registers	16-7
16.3.3	Bit Timing	16-8
16.3.3.1	Configuring the TouCAN Bit Timing	16-9
16.3.4	Error Counters	16-9
16.3.5	Time Stamp	16-10
16.4	TouCAN Operation	16-11
16.4.1	TouCAN Reset	16-11

Paragraph Number

Page Number



16.4.2	TouCAN Initialization	16-11
16.4.3	Transmit Process	16-12
16.4.3.1	Transmit Message Buffer Deactivation	16-13
16.4.3.2	Reception of Transmitted Frames	16-13
16.4.4	Receive Process	16-13
16.4.4.1	Receive Message Buffer Deactivation	16-14
16.4.4.2	Locking and Releasing Message Buffers	16-15
16.4.5	Remote Frames	16-15
16.4.6	Overload Frames	16-16
16.5	Special Operating Modes	16-16
16.5.1	Debug Mode	16-16
16.5.2	Low-Power Stop Mode	16-17
16.5.3	Auto Power Save Mode	16-18
16.6	Interrupts	16-19
16.7	Programmer's Model	16-20
16.7.1	TouCAN Module Configuration Register	16-22
16.7.2	TouCAN Test Configuration Register	16-24
16.7.3	TouCAN Interrupt Configuration Register	16-24
16.7.4	Control Register 0	16-25
16.7.5	Control Register 1	16-26
16.7.6	Prescaler Divide Register	16-27
16.7.7	Control Register 2	16-28
16.7.8	Free Running Timer	16-29
16.7.9	Receive Global Mask Registers	16-29
16.7.10	Receive Buffer 14 Mask Registers	16-30
16.7.11	Receive Buffer 15 Mask Registers	16-30
16.7.12	Error and Status Register	16-30
16.7.13	Interrupt Mask Register	16-32
16.7.14	Interrupt Flag Register	16-33
16.7.15	Error Counters	16-33

Section 17 TIME PROCESSOR UNIT 3

17.1	Overview	17-1
17.2	TPU3 Components	17-2
17.2.1	Time Bases	17-2
17.2.2	Timer Channels	17-2
17.2.3	Scheduler	17-2
17.2.4	Microengine	17-2
17.2.5	Host Interface	17-3
17.2.6	Parameter RAM	17-3
17.3	TPU Operation	17-3
17.3.1	Event Timing	17-3



17.3.2	Channel Orthogonality	17-3
17.3.3	Interchannel Communication	17-4
17.3.4	Programmable Channel Service Priority	17-4
17.3.5	Coherency	17-4
17.3.6	Emulation Support	17-4
17.3.7	TPU3 Interrupts	17-5
17.3.8	Prescaler Control for TCR1	17-5
17.3.9	Prescaler Control for TCR2	17-7
17.4	Programming Model.	17-8
17.4.1	TPU Module Configuration Register.	17-10
17.4.2	TPU3 Test Configuration Register	17-12
17.4.3	Development Support Control Register	17-12
17.4.4	Development Support Status Register	17-14
17.4.5	TPU3 Interrupt Configuration Register	17-14
17.4.6	Channel Interrupt Enable Register	17-15
17.4.7	Channel Function Select Registers	17-15
17.4.8	Host Sequence Registers.	17-16
17.4.9	Host Service Request Registers.	17-17
17.4.10	Channel Priority Registers	17-18
17.4.11	Channel Interrupt Status Register	17-19
17.4.12	Link Register.	17-19
17.4.13	Service Grant Latch Register	17-19
17.4.14	Decoded Channel Number Register.	17-19
17.4.15	TPU3 Module Configuration Register 2	17-20
17.4.16	TPU Module Configuration Register 3	17-21
17.4.17	TPU3 Test Registers	17-22
17.4.18	TPU3 Parameter RAM	17-22
17.5	Time Functions.	17-23

Section 18 DUAL-PORT TPU RAM (DPTRAM)

18.1	Features.	18-1
18.2	DPTRAM Configuration and Block Diagram	18-2
18.3	Programming Model.	18-2
18.3.1	DPTRAM Module Configuration Register (DPTMCR)	18-3
18.3.2	DPTRAM Test Register	18-4
18.3.3	Ram Base Address Register (RAMBAR)	18-5
18.3.4	MISR High (MISRH) and MISR Low (MISRL)	18-5
18.3.5	MISC Counter (MISCNT)	18-6
18.4	Operation	18-6
18.4.1	Normal Operation	18-6
18.4.2	Standby Operation	18-6
18.4.3	Reset Operation	18-7



18.4.4 Stop Operation	18-7
18.4.5 Freeze Operation	18-8
18.4.6 TPU3 Emulation Mode Operation.....	18-8
18.5 Multiple Input Signature Calculator (MISC)	18-8

Section 19

CDR MoneT FLASH EEPROM

19.1 Introduction	19-1
19.1.1 MPC555 / MPC556 CMF Features.....	19-2
19.1.2 Glossary of Terms for the CMF EEPROM	19-2
19.2 Programming Model.....	19-4
19.2.1 CMF EEPROM Control Registers	19-4
19.2.1.1 CMF EEPROM Configuration Register (CMFMCR).....	19-5
19.2.1.2 CMF EEPROM Test Register (CMFTST).....	19-7
19.2.1.3 CMF EEPROM High Voltage Control Register (CMFCTL).....	19-9
19.2.2 CMF EEPROM Array Addressing.....	19-11
19.2.2.1 Read Page Buffers	19-12
19.2.2.2 Program Page Buffers	19-13
19.2.2.3 Array Configuration for CMF Module A	19-14
19.2.2.4 Array Configuration for CMF Module B	19-15
19.3 Shadow Information.....	19-15
19.3.1 Address Range of Shadow Information	19-16
19.3.2 Reset Configuration Word (CMFCFIG)	19-16
19.4 Array Read Operation	19-17
19.5 Programming the CMF Array	19-18
19.5.1 Program Sequence.....	19-18
19.5.2 Program Margin Reads	19-22
19.5.3 Over-Programming.....	19-23
19.6 Erasing CMF Array Blocks.....	19-23
19.6.1 Erase Sequence.....	19-23
19.6.2 Erase Margin Reads.....	19-26
19.6.3 Erasing Shadow Information Words.....	19-26
19.7 Voltage Control for Programming and Erasing	19-27
19.7.1 Pulse Status	19-27
19.7.2 Pulse Width Timing Equation	19-27
19.7.3 System Clock Scaling.....	19-28
19.7.4 Exponential Clock Multiplier	19-29
19.7.5 Linear Clock Multiplier	19-29
19.7.6 A Technique to Determine SCLKR, CLKPE, and CLKPM	19-29
19.7.7 Starting and Ending a Program or Erase Sequence	19-30
19.7.8 Controlling the Program/Erase Voltage	19-31
19.8 Censored and Non-Censored Accesses	19-31
19.8.1 Uncensored Mode	19-31



19.8.2 Censored Mode	19-31
19.8.3 Device Modes and Censorship Status	19-32
19.8.4 Setting and Clearing Censor	19-33
19.8.5 Switching the CMF EEPROM Censorship	19-35
19.9 Pin Descriptions	19-36
19.9.1 E _{PEE} Signal	19-36
19.9.2 FLASH Program/Erase Voltage Conditioning	19-37
19.10 Reset Operation	19-39
19.10.1 Master Reset	19-39
19.10.2 Soft Reset	19-39
19.10.3 Emulation Operation	19-40
19.11 Disabling the CMF Module	19-40

Section 20 STATIC RANDOM ACCESS MEMORY (SRAM)

20.1 Features	20-1
20.2 Block Diagram	20-1
20.3 Programming Model	20-2
20.3.1 SRAM Module Configuration Register (SRAMMCR)	20-2
20.3.2 SRAM Test Register (SRAMTST)	20-3

Section 21 DEVELOPMENT SUPPORT

21.1 Overview	21-1
21.2 Program Flow Tracking	21-1
21.2.1 Program Trace Cycle	21-2
21.2.1.1 Instruction Queue Status Pins — VF [0:2]	21-3
21.2.1.2 History Buffer Flushes Status Pins— VFLS [0..1]	21-4
21.2.1.3 Queue Flush Information Special Case	21-4
21.2.2 Program Trace when in Debug Mode	21-4
21.2.3 Sequential Instructions Marked as Indirect Branch	21-5
21.2.4 The External Hardware	21-5
21.2.4.1 Synchronizing the Trace Window to the CPU Internal Events	21-5
21.2.4.2 Detecting the Trace Window Start Address	21-6
21.2.4.3 Detecting the Assertion/Negation of VSYNC	21-7
21.2.4.4 Detecting the Trace Window End Address	21-7
21.2.4.5 Compress	21-7
21.2.5 Instruction Fetch Show Cycle Control	21-8
21.3 Watchpoints and Breakpoints Support	21-8
21.3.1 Internal Watchpoints and Breakpoints	21-11
21.3.1.1 Restrictions	21-13
21.3.1.2 Byte and Half-Word Working Modes	21-13
21.3.1.3 Examples	21-14
21.3.1.4 Context Dependent Filter	21-15



21.3.1.5 Ignore First Match.	21-15
21.3.1.6 Generating Six Compare Types.	21-16
21.3.2 Instruction Support	21-16
21.3.2.1 Load/Store Support	21-17
21.3.3 Watchpoint Counters	21-21
21.3.3.1 Trap Enable Programming	21-21
21.4 Development System Interface	21-21
21.4.1 Debug Mode Support	21-24
21.4.1.1 Debug Mode Enable vs. Debug Mode Disable.	21-26
21.4.1.2 Entering Debug Mode.	21-26
21.4.1.3 The Check Stop State and Debug Mode	21-29
21.4.1.4 Saving Machine State upon Entering Debug Mode	21-29
21.4.1.5 Running in Debug Mode.	21-30
21.4.1.6 Exiting Debug Mode	21-30
21.5 Development Port	21-31
21.5.1 Development Port Pins.	21-31
21.5.2 Development Serial Clock	21-31
21.5.3 Development Serial Data In	21-31
21.5.4 Development Serial Data Out.	21-32
21.5.5 Freeze Signal	21-32
21.5.5.1 SGPIO6/FRZ/ $\overline{\text{PTR}}$ Pin	21-32
21.5.5.2 IWP[0:1]/VFLS[0:1] Pins.	21-32
21.5.5.3 VFLS[0:1]_MPIO32B[3:4] Pins.	21-32
21.5.6 Development Port Registers.	21-32
21.5.6.1 Development Port Shift Register	21-33
21.5.6.2 Trap Enable Control Register.	21-33
21.5.6.3 Development Port Registers Decode	21-33
21.5.6.4 Development Port Serial Communications — Clock Mode Selection	21-34
21.5.6.5 Development Port Serial Communications — Trap Enable Mode	21-38
21.5.6.6 Serial Data into Development Port — Trap Enable Mode	21-38
21.5.6.7 Serial Data Out of Development Port — Trap Enable Mode	21-39
21.5.6.8 Development Port Serial Communications — Debug Mode.	21-39
21.5.6.9 Serial Data Into Development Port.	21-40
21.5.6.10 Serial Data Out of Development Port.	21-41
21.5.6.11 Fast Download Procedure	21-41
21.6 Software Monitor Debugger Support	21-43
21.6.1 Freeze Indication	21-43
21.7 Development Support Registers	21-43
21.7.1 Register Protection.	21-44
21.7.2 Comparator A–D Value Registers (CMPA–CMPD)	21-45
21.7.3 Comparator E–F Value Registers.	21-46
21.7.4 Breakpoint Address Register (BAR).	21-46
21.7.5 Comparator G–H Value Registers (CMPG–CMPH).	21-46



21.7.6 I-Bus Support Control Register	21-47
21.7.7 L-Bus Support Control Register 1	21-49
21.7.8 L-Bus Support Control Register 2	21-50
21.7.9 Breakpoint Counter A Value and Control Register	21-52
21.7.10 Breakpoint Counter B Value and Control Register	21-53
21.7.11 Exception Cause Register (ECR)	21-53
21.7.12 Debug Enable Register (DER)	21-55
21.7.13 Development Port Data Register (DPDR)	21-57

Section 22

IEEE 1149.1-COMPLIANT INTERFACE (JTAG)

22.1 JTAG Interface Block Diagram	22-1
22.2 JTAG Signal Descriptions	22-2
22.3 Operating Frequency	22-3
22.4 TAP Controller	22-3
22.5 Instruction Register	22-4
22.5.1 EXTEST	22-5
22.5.2 SAMPLE/PRELOAD	22-5
22.5.3 BYPASS	22-5
22.5.4 CLAMP	22-6
22.5.5 HI-Z	22-6
22.6 Restrictions	22-6
22.7 Low-Power Stop Mode	22-6
22.8 Non-IEEE 1149.1-1990 Operation	22-7
22.9 Boundary Scan Register	22-7

Appendix A

MPC555 / MPC556 INTERNAL MEMORY MAP

Appendix B

REGISTER GENERAL INDEX

Appendix C

REGISTER DIAGRAM INDEX

Appendix D

TPU ROM FUNCTIONS

D.1 Overview	D-1
D.2 Programmable Time Accumulator (PTA)	D-4
D.3 Queued Output Match TPU Function (QOM)	D-6
D.4 Table Stepper Motor (TSM)	D-8
D.5 Frequency Measurement (FQM)	D-11
D.6 Universal Asynchronous Receiver/Transmitter (UART)	D-13
D.7 New Input Capture/Transition Counter (NITC)	D-16
D.8 Multiphase Motor Commutation (COMM)	D-18
D.9 Hall Effect Decode (HALLD)	D-20

Paragraph Number

Page Number



D.10	Multichannel Pulse-Width Modulation (MCPWM)	D-22
D.11	Fast Quadrature Decode TPU Function (FQD)	D-29
D.12	Period/Pulse-Width Accumulator (PPWA)	D-32
D.13	Output Compare (OC)	D-34
D.14	Pulse-Width Modulation (PWM)	D-36
D.15	Discrete Input/Output (DIO)	D-38
D.16	Synchronized Pulse-Width Modulation (SPWM)	D-40
D.17	Read / Write Timers and Pin TPU Function (RWTPIN)	D-43
D.18	ID TPU Function (ID)	D-45
D.19	Serial Input/Output Port (SIOP)	D-47
D.19.1	Parameters	D-48
D.19.1.1	CHAN_CONTROL	D-50
D.19.1.2	BIT_D	D-50
D.19.1.3	HALF_PERIOD	D-50
D.19.1.4	BIT_COUNT	D-50
D.19.1.5	XFER_SIZE	D-50
D.19.1.6	SIOP_DATA	D-50
D.19.2	Host CPU Initialization of the SIOP Function	D-51
D.19.3	SIOP Function Performance	D-51
D.19.3.1	XFER_SIZE Greater Than 16	D-52
D.19.3.2	Data Positioning	D-52
D.19.3.3	Data Timing	D-52

Appendix E CLOCK AND BOARD GUIDELINES

E.1	INTRODUCTION	E-1
E.2	MPC555 / MPC556 Family Power Distribution	E-2
E.3	PLL and Crystal Oscillator External Components	E-4
E.3.1	Crystal Oscillator External Components	E-4
E.3.2	KAPWR Filtering	E-5
E.3.3	PLL External Components	E-6
E.3.4	PLL Off-Chip Capacitor C_{XFC}	E-7
E.4	Clock Oscillator and PLL External Components Layout Requirements	E-7
E.4.1	Traces and Placement	E-7
E.4.2	Grounding/Guarding	E-8

Appendix F MEMORY ACCESS TIMING

F.1	Introduction	F-1
-----	--------------	-----

Appendix G ELECTRICAL CHARACTERISTICS

G.1	Absolute Maximum Ratings ($V_{SS} = 0\text{ V}$)	G-1
G.2	Target Failure Rate	G-2
G.3	Package	G-2
G.4	EMI Characteristics	G-2
G.4.1	Reference Documents	G-2
G.4.2	Definitions and Acronyms	G-2
G.4.3	Testing Characteristics	G-3
G.5	Thermal Characteristics	G-3
G.5.1	Thermal References	G-5
G.6	ESD Protection	G-6

**Paragraph
Number**

**Page
Number**



G.7 DC Electrical Characteristics	G-7
G.8 Oscillator and PLL Electrical Characteristics	G-12
G.9 Power Up/Down Sequencing	G-12
G.10 FLASH Electrical Characteristics	G-13
G.10.1 Flash Module Life	G-14
G.10.2 Programming and Erase Algorithm	G-15
G.11 Generic Timing	G-16
G.12 Interrupt Timing	G-39
G.13 Debug Port Timing	G-40
G.14 Reset Timing	G-43
G.15 IEEE 1149.1 Electrical Characteristics	G-47
G.16 QADC64 Electrical Characteristics	G-52
G.17 QSMCM Electrical Characteristics	G-53
G.18 GPIO Electrical Characteristics	G-57
G.19 TPU3 Electrical Characteristics	G-57
G.20 TouCAN Electrical Characteristics	G-58
G.21 MIOS Timing Characteristics	G-59
G.21.1 MPWMSM Timing Characteristics	G-60
G.21.2 MMCSM Timing Characteristics	G-62
G.21.3 MDASM Timing Characteristics	G-65
G.21.4 MPIO SM Timing Characteristics	G-68

Appendix H

**FLASH ELECTRICAL CHARACTERISTICS FOR ALL J76N
MASK SETS AND 0K02A AND 1K02A ONLY**

H.1 Electrical Characteristics	H-1
H.1.1 Flash Module Life	H-3
H.2 Programming and Erase Algorithm	H-3

INDEX

Online publishing by JABIS™, <http://www.jabis.com>