

# 恩智浦S32K3域控制器应用介绍

曾福 Frankie Zeng  
应用工程师  
2022年7月



SECURE CONNECTIONS  
FOR A SMARTER WORLD

PUBLIC

NXP, THE NXP LOGO AND NXP SECURE CONNECTIONS FOR A SMARTER WORLD ARE TRADEMARKS OF NXP B.V.  
ALL OTHER PRODUCT OR SERVICE NAMES ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. © 2022 NXP B.V.





# AGENDA

- Zonal Aggregator Typical Challenges
- S32K3 Overview
  - Power consumption
  - Communication interfaces
  - Freedom of interferences
- S32K Demo Overview
  - TSN Motor control demo
  - T-box demo
  - Multi-network synchronization
  - Door zone demo
- Summary





# AGENDA

- Zonal Aggregator Typical Challenges
- S32K3 Overview
  - Power consumption
  - Communication interfaces
  - Freedom of interferences
- S32K Demo Overview
  - TSN Motor control demo
  - T-box demo
  - Multi-network synchronization
  - Door zone demo
- Summary

# ARCHITECTURAL CHANGES DRIVE GROWTH IN NODES AND PROCESSING PERFORMANCE


## TODAY

Traditional  
Flat Architecture



## 2021+

Domain and  
Zonalization Transitions



**BODY DOMAIN  
AND ZONE EXAMPLE**

## Two parallel architectural evolutions

1

### Domain Focus

Scalable and centralized  
software development

1. Flexible & scalable software environment
2. Efficiently supports the user-defined vehicle
3. Centralized OTA, easily upgradable software

+

2


### Zonal Focus

Simplified wiring and connectivity


1. Dramatically reduced wire routing and cable costs
2. Flexible data monetization
3. Easy integration of new hardware

# ZONAL MODULES: MAIN CLUSTERS AS OF TODAY


## ZONAL AGGREGATOR



## ZONAL CONTROLLER



## ZONAL PROCESSOR



Adv. Low Power Modes & Fast Wake-up

Direct I/O Control (e.g. Body, Motors)

Comms Acceleration (Gateway Offload)

Multi-ECU Virtualization

Adaptive AUTOSAR / Linux

## Key MCU/MPU Attributes

## ZONAL AGGREGATOR TYPICAL CHALLENGES

- Low power and fast wakeup
- Low latency communication
- Communication protocol translation
- Freedom of interferences across different application tasks





# AGENDA

- Zonal Aggregator Typical Challenges
- S32K3 Overview
  - Power consumption
  - Communication interfaces
  - Freedom of interferences
- S32K Demo Overview
  - TSN Motor control demo
  - T-box demo
  - Multi-network synchronization
  - Door zone demo
- Summary


## S32K3: EXPANDING THE S32 PLATFORM

**NXP's S32 Automotive Platform enables software reuse across multiple applications,** reducing development complexity and easing the burden for Tier 1s and carmakers

**S32K3 expands S32**  
into zone control and edge nodes


**Extends S32K family into new applications:**

- Advanced Body Electronics
- Battery Management
- Zone Control





# S32K BROAD PORTFOLIO AND APPLICATIONS



Typical  
Application

Arm®  
CPU Core

ASIL C/D –BMS,  
Electrification

2-3 x M7 240Mhz

ASIL A/B –High perf body,  
Zone & IO, Info/Audio

2 x M7 160Mhz

ASIL A/B – “K1 extension”,  
Security 2022+, OTA

1 x M7 120Mhz

ASIL A/B – CAN FD and  
Ethernet nodes


1 x M4 112Mhz

ASIL A/B – Small CAN FD  
and LIN nodes

1 x M0+ 48Mhz


## S32K3 PLATFORM – UNMATCHED SCALABILITY

- Core & Platform: Same Arm Cortex®-M7 core across S32K3 family for software reuse
- Security: HSE B across S32K3 family
- Safety: ASIL D and ASIL B fully compatible in S32K3 family
- Memory: 512K-8MB in S32K3, scalable down to 128KB in S32K1
- Package: BGA / MaxQFP pin compatible in S32K3 family



K3 Flash	K3 Package				
	48 LQFP	100 MAXQFP	172 MAXQFP	257 BGA	289 BGA
	7 x 7 mm	10 x 10 mm	16 x 16 mm	14 x 14 mm	17 x 17 mm
8M			K358/48/38/28		K358/48/38/28**
6M					
4M			K344/24/14	K344/24/14	
2M		K342/22/12	K342/22/12		
1M	K311	K311	K341		
512K	K310	K310			


\*\*BGA257 is subset of BGA289



## S32K3 OPTIMIZED FOR LOW CURRENT CONSUMPTION

### • RUN mode

- Scalable current consumption based on the application requirements.
- All modules + FLASH are powered.
- All modules can be clock-gated to reduce power.
- Full support for max speed. Up to 160MHz.



### • Standby mode

- Main cores / Platform / Flash / PLL are power gated off. Large parts of SoC inactive.
- **STANDBY-RAM** (32KB Content retention).
- **WAKE-UP** from up to **60** digital inputs.
- **WAKE-UP** from up to **24** analog inputs (**3 x LPCMP**).
- **WAKE-UP** from on-chip timers (**PIT0, SWT0, RTC**).
- **Pad-keeping**.
- Configurable secure and un-secure wake-up routes.

### • Power estimation tool

- Help customers to obtain initial power / current consumption estimations based on their specific use case.




Figure 2-1. Power Estimation Tool



## S32K3 COMMUNICATION INTERFACES

- Ethernet MAC (10/100/1000Mbps): MII/RMII/RGMII interface, AVB and TSN support
  - TSN Enhancement to Scheduled Traffic Standard 802.1Qbv-2015, Frame Preemption Standard 802.1Qbu-2016 Standard 802.1br
  - Support IEEE 1722 Layer 2 Transport Protocol, IEEE 802.1AS Timing and Synchronization, IEEE 802.1Qav
  - Compliant with 3 Industrial Ethernet Protocols
- Ethernet 10BaseT1S
  - Supported by SPI + external MAC&PHY
- CAN FD
  - FlexCAN modules with ISOCAN-FD and DMA support
  - Support 5Mbps using 16 time quanta
- Enhanced FlexIO configurable as different communication peripherals
  - SENT, I2C, I2S, UART, SPI, entry level TFT LCD driver
- Synchronous Audio Interface (SAI)
  - Supports full duplex serial interfaces with frame synchronization such as I2S, AC97, TDM, and codec/DSP interfaces



# S32K3: ETHERNET IP

## S32K342/44

- Supports 10/100/200\*/1000Mbps Ethernet
- Supports MII, MII-Lite, RMII, RGMII interfaces.
  - Pinout mux ease PCB routing
  - TJA1100/1 compliant

## General

TCP/IP acceleration features

Single and Double VLAN support

RX Frame parser (Filtering by mask)

2 queues on Reception and Transmission of Traffic

## AVB features

IEEE 1722 Layer 2 Transport Protocol

IEEE 802.1AS Timing and Synchronization

IEEE 802.1Qav: Forwarding and Queuing for Time-Sensitive Streams (FQTSS)


4-channel IEEE 1588 timer

Automatic time stamping

Media clock recovery support

## TSN Features

- TSN Enhancement to Scheduled Traffic Standard 802.1Qbv-2015
- TSN Frame Preemption Standard 802.1Qbu-2016Standard 802.1br




TSN Protocol Support		
Standard	Description	S32K3 Family
802.1Qbv	Scheduled Traffic	Yes (Qbv 2015)
802.1Qav	Forwarding and Queuing Enhancements	Yes
802.1Qbu, 802.3BR	Frame Preemption	Yes (Qbu, QBR 2016)
802.1AS	Timing and synchronization for Time-Sensitive Applications	Yes

Enhancement vs S32K148

## FLEXCAN OVERVIEW

- Protocol Engine (PE):
  - Requesting RAM access for receiving and transmitting message frames
  - Validating received messages
  - Performing error handling
  - Detecting CAN FD messages
- Message Buffer RAM:
  - The message buffers are stored in an embedded RAM dedicated to the FlexCAN module
- Support of CAN 2.0 & CAN FD
- Support 3 to 8 FlexCAN instances across K3 family





## FLEXCAN FEATURES OVERVIEW - S32K344

Feature	FlexCAN0	FlexCAN1	FlexCAN2	FlexCAN3	FlexCAN4	FlexCAN5
CAN FD and CAN	Yes	Yes	Yes	Yes	Yes	Yes
Number of CAN Classic Message buffers	96	64	64	32	32	32
Number of CANFD 64-byte Message Buffers	21	14	14	7	7	7
Rx FIFO Filtering (CAN Classic)	Yes	Yes	Yes	Yes	Yes	Yes
ECC	Yes	Yes	Yes	Yes	Yes	Yes
PNET	No	No	No	No	No	No
External Tick for timestamps	Yes, supported by PIT_RTI_2 Trigger[0] source					
DMA support for CANFD	Yes	Yes	Yes	Yes	Yes	Yes
Enhanced Rx FIFO (CANFD)	Yes	No	No	No	No	No


## HIGHLIGHTS OF DIFFERENCES BETWEEN S32K1'S FLEXCAN

Feature in K3	In K1
RAM ECC memory for Message buffers	Non-ECC memory
Enhanced RX FIFO with capability for CAN FD frames	Only legacy RX FIFO that supports CAN Classic frames
DMA trigger for reception of CANFD messages	DMA not available for CANFD
32-bit wide timestamping timer	16-bit wide timestamping timer
Pretended networking mode (CAN reception in low power modes) is no longer supported	PNET mode available




# FLEXIO OVERVIEW

- The FlexIO is a highly configurable module providing a wide range of functionality including
  - Emulation of a variety of serial communication protocols
  - Flexible 16-bit timers with support for a variety of trigger, reset, enable and disable conditions.
  - Programmable logic blocks allowing the implementation of digital logic functions on-chip and configurable interaction of internal and external modules
  - Programmable state machine for offloading basic system control functions from CPU
- Configurations on S32K3
  - 32 pins, 8 Timers (16-bit), 8 shifters
- FlexIO is able to emulate:
  - UART, I2C, SPI, I2S
  - Parallel shifting
    - TFT interface
    - Camera Interface
    - Intel8080/Motorola64k Protocol
  - Input-capture, pulse edge interval measurement.
    - SENT protocol support
  - PWM/Waveform generation





## S32K3XX FREEDOM OF INTERFERENCES SUPPORT



Pool of HW resources arranged around cores based on applications requirements!



# AGENDA

- Zonal Aggregator Typical Challenges
- S32K3 Overview
  - Power consumption
  - Communication interfaces
  - Freedom of interferences
- S32K Demo Overview
  - TSN Motor control demo
  - T-box demo
  - Multi-network synchronization
  - Door zone demo
- Summary

# TSN MOTOR CONTROL DEMO

## Problem:



- Real time control via Ethernet from central compute platform– challenges of varying communication latency

## Goal:

- Remote speed controller implementation in the Central Compute Platform, decoupled from the Smart Actuator

## Demo:


- Speed control loop latency kept within limits by time-aware traffic shaping (IEEE 802.1Qbv, IEEE 802.1as)
- Redundant control data paths enabled between Central Compute Platform and Zonal Controllers (IEEE 802.1cb)
- Multi-domain gPTP configuration for maintaining local clock synchronization in case of single link failure






## WHERE IS THE 5G T-BOX IN A VEHICLE E/E ARCHITECTURE

- Benefits of 5G T-BOX with gateway integrated:
  - ✓ **Lower latency:** Able to get the critical vehicle data from CAN/LIN bus directly and timely in urgent case, such as high-way car collision occurrence
  - ✓ **V2X ability**
  - ✓ **Save system power consumption of low-power mode when IGN OFF:** can get important data without wakeup other ECU
  - ✓ **Save BOM cost**
  - ✓ **At least 4 CAN w/ FD required** for the new EV E/E architecture



# T-BOX BLOCK DIAGRAMS



## 5G Support

- Basic 5G T-BOX functionality with FOTA

## I/O aggregator support

- 5x 100BASE-T1
- 1x 1000BASE-Tx
- 1x 1000BASE-T1 (ext.)
- 6x CAN-FD
- 4x LIN 2.x

## AVB Support

- SJA1110 TSN switch with internal 802.1AS synchronization middleware
- Media clock generation supporting CS2x00 and CDCE6214
- Low-power stereo codec
- SAI header for TDF853x class-D amplifier connection or another codec

## S32K MULTI NETWORK SYNCHRONIZATION DEMO

- **Technical Challenges Addressed:**

- Background: the adoption of zonal architecture
- Protocol translation (ISELED, LIN, CAN, Ethernet) across different zones
- Synchronization of lighting/sound effects across different zones

- **Demo Key Features:**

- HW based on S32K1xx EVBs and ISELED strips
- Middle-layer SW built on S32 EcoSystem (S32 DS, S32K1 SDK, ISELED driver)
- Distributed time concept to have same time stamp across all nodes in network

- **Benefits:**

- Scalable solution across communication interfaces with single S32K family
  - Demo supports ISELED, LIN, CAN (FD), Ethernet protocols
- Smooth synchronization effects with fast response time/ low latency




Fig 1. Use case example in zonal architecture




Fig 2. Demo Set Up Overview


# SMART DOOR ZONE SOLUTION WITH ISELED AND ETHERNET AVB

## • Problem:

- Traditional door solutions use dedicated modules with point to point wiring for lighting and audio. This requires extensive wiring, complicated OTA updates, and limits design flexibility. The addition of radar complicates the challenge.
- Adopting a zonal architecture with an integrated Door Zone module reduces wiring, simplifies OTA, increases design flexibility, and enables the addition of radar, but introduces challenges in synchronization between door zones

## • Solution:

- Smart Door Zone module for lighting, audio, and radar
- Lighting and audio synchronization supported by ISELED and Ethernet AVB
- ISELED is a digital LED Solution for dynamic lighting effects with synchronization
- ISELED has been developed by an open alliance to provide a complete eco-system to support market adoption
- NXP's S32K1xx family is the first and only production-ready HW and SW solution for ISELED on the market







# AGENDA

- Zonal Aggregator Typical Challenges
- S32K3 Overview
  - Power consumption
  - Communication interfaces
  - Freedom of interferences
- S32K Demo Overview
  - TSN Motor control demo
  - T-box demo
  - Multi-network synchronization
  - Door zone demo
- Summary



## SUMMARY

- S32K3 family solves the challenges in zonal aggregators with:
  - rich communication interfaces
  - low power performance
  - freedom of interferences support
- Various demos available to further demonstrate use cases



# TECHNOLOGY SHOWROOM

## JOURNEYS BY DESIRED ENGAGEMENT



- Self-guided tour
- Live-streaming at set times
- Guided tours

## 60+ VIRTUAL DEMOS

- Focus on system solutions
- Set up along NXP verticals

## JOURNEYS BY DESIRED FOCUS

- Low Power Innovations
- Advanced Analog
- Connectivity
- Edge & AI/ML
- Safety & Security



SHOWROOM.NXP.COM




## WELCOME TO FOLLOW NXP AT SOCIAL PLATFORMS



欢迎您关注「恩智浦微招聘」公众号  
及时获取恩智浦“芯”职位及员工  
活动相关资讯



关注NXP客栈公众号，查看恩  
智浦最新官方资讯及技术材料



关注恩智浦B站官方账号，观  
看恩智浦最新技术视频



# Q&A





SECURE CONNECTIONS  
FOR A SMARTER WORLD



[SHOWROOM.NXP.COM](https://showroom.nxp.com)