

UM11748

MC33665A_CCMU_Demo user manual

Rev. 2 — 25 August 2022

User manual

Document information

Information	Content
Keywords	MC33665A, CANoe, CAN (FD), MC33775A
Abstract	MC33665A_CCMU_Demo user manual to set up in CANoe.



Revision history

Rev	Date	Description
2	20220825	minor text update, updated to MC33665A_CCMU_Demo_V2, removed section for RD33775ADSTEBV, title update from MC33665A CANoe tool user manual to MC33665A_CCMU_Demo user manual
1	20220620	initial version

1 Important notice

IMPORTANT NOTICE

For engineering development or evaluation purposes only



NXP provides the product under the following conditions:

This evaluation kit is for use of ENGINEERING DEVELOPMENT OR EVALUATION PURPOSES ONLY.

It is provided as a sample IC pre-soldered to a printed-circuit board to make it easier to access inputs, outputs and supply terminals. This evaluation board may be used with any development system or other source of I/O signals by connecting it to the host MCU computer board via off-the-shelf cables. This evaluation board is not a Reference Design and is not intended to represent a final design recommendation for any particular application. Final device in an application heavily depends on proper printed-circuit board layout and heat sinking design as well as attention to supply filtering, transient suppression, and I/O signal quality.

The product provided may not be complete in terms of required design, marketing, and or manufacturing related protective considerations, including product safety measures typically found in the end device incorporating the product. Due to the open construction of the product, it is the responsibility of the user to take all appropriate precautions for electric discharge. In order to minimize risks associated with the customers' applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards. For any safety concerns, contact NXP sales and technical support services.

2 Introduction

The MC33665A is a general-purpose battery management system (BMS) communication gateway IC for CAN (FD) to four transport protocol link (TPL) ports. The MC33665ATF4AE offers a CAN or CAN FD interface for communication with an MCU as defined in ISO 11898. The CAN physical layer is not included. An external CAN transceiver such as TJA1442 or TJA1443 of NXP or relevant transceivers must be used based on the application.

Note: MC33665A referred in this document is a CAN (FD) variant with MC33665ATF4AE.

Communication can be established to MC33665A (MC33665ATF4AE) with CAN or CAN FD protocol. CANoe is a software tool from Vector Informatik GmbH which is known in automotive industry. Goal of MC33665A_CCMU_Demo is to utilize the features of CANoe to communicate with MC33665A in extracting the cell voltages and temperatures from MC33775A BCCs designed by NXP.

This document describes how to set up the CANoe environment for MC33665A and use the workspace of MC33665A_CCMU_Demo to generate the voltage and temperature measurements.

- MC33665A: general-purpose BMS communication CAN (FD) gateway
- MC33775A: 14-channel Li-ion battery cell controller (ASIL D)

NXP offers the following board solutions to see the functionality of devices and support the setup in testing the devices.

- <https://www.nxp.com/FRDM665CANFDEVB>
- <https://www.nxp.com/RD33775ACNCEVB>
- [BATT-14CEMULATOR](#)
- [BATT-14EXTENDER](#)

3 Demo prerequisites


Below is the list of devices or hardware required to run MC33665A_CCMU_Demo.

- A PC or laptop which meets minimum hardware and software requirements to install the CANoe (license version) from Vector
- CANoe tool with a valid license which is either installed in PC or in HW (dongle or relevant) connected to the PC. Note: MC33665A_CCMU_Demo is generated to support CANoe version 11, version 13, and version 15.
- Hardware to interface with PC (USB) to CAN (FD) (DB-9 or relevant connector); typically VN1610 or relevant which had CAN (FD) capability of data speeds up to 5 Mbit/s can be used
- RD33775ACNCEVB: centralized cell monitoring unit (CCMU) based on CAN (FD)
- Standard DC power supply which is minimum 25 W with 12 V output
- 14 cell slider battery pack emulator (BATT-14CEMULATOR)
- 14 cell battery pack extender board (BATT-14EXTENDER)

4 Software setup

To set up the CANoe software in a PC or laptop which is intended to use for demo, follow below steps.

- Install the CANoe tool from Vector. Follow the installation guidelines of CANoe. Note: Check the compatibility of MC33665A_CCMU_Demo for CANoe version and license.
- Download the MC33665A_CCMU_Demo available at <https://www.nxp.com/MC33665A>




Name	Date modified	Type	Size
Database	8/1/2022 11:20 PM	File folder	
Panels	8/1/2022 11:20 PM	File folder	
Pictures	8/1/2022 11:20 PM	File folder	
CCMU_Demoboard_RV1.0	8/1/2022 11:15 PM	CAN File	71 KB
MC33665A_CCMU_Demo_V2	8/1/2022 11:16 PM	CANalyzer/CANo...	1,281 KB
MC33665A_CCMU_Demo_V2.stcfg	8/1/2022 11:16 PM	STCFG File	1 KB
MC33665A_CCMU_Demo_V2_ver110	8/1/2022 11:15 PM	CANalyzer/CANo...	324 KB
MC33665A_CCMU_Demo_V2_ver110.stcfg	8/1/2022 11:15 PM	STCFG File	1 KB
MC33665A_CCMU_Demo_V2_ver130	8/1/2022 11:16 PM	CANalyzer/CANo...	1,281 KB
MC33665A_CCMU_Demo_V2_ver130.stcfg	8/1/2022 11:16 PM	STCFG File	1 KB

aaa-045845

Figure 1. MC33665A_CCMU_Demo files

- **Database** folder has .dbc files to support communication with MC33665A and MC33775A. NXP_BMS_QPHY_V1.dbc file supports for MC33665A_CCMU_Demo.
- Two panels to support the MC33665A_CCMU_Demo are available in **Panels** folder.

- **CCMU_Demoboard_RV1.0.can** is the communication access programming language (CAPL) file to support as node in MC33665A_CCMU_Demo_V2.
- MC33665A_CCMU_Demo_V2 is compatible for **CANoe 15**, MC33665A_CCMU_Demo_V2_ver130 is compatible for **CANoe 13**, and MC33665A_CCMU_Demo_V2_ver110 is compatible for **CANoe 11**. MC33665A_CCMU_Demo_V2 CANoe configuration files are forward compatible for latest CANoe version.
- Open the CANoe installed in PC or laptop. To run the full features of MC33665A_CCMU_Demo, select the available CANoe license. MC33665A_CCMU_Demo can work for CANoe versions 11 or above (select the appropriate MC33665A_CCMU_Demo file).
- Click the **File** tab on top left corner of CANoe tool → click **Open** → browse to the location of MC33665A_CCMU_Demo files shown in [Figure 1](#) → select the compatible MC33665A_CCMU_Demo_V2 configuration file → click **open** button (on bottom right corner) to open the workspace in **CANoe**
- Workspace of MC33665A_CCMU_Demo_V2 in configuration tab consists of **Simulation Setup** window and **Trace** window as shown in [Figure 2](#).



aaa-045846

Figure 2. MC33665A_CCMU_Demo workspace

- Battery management unit (BMU) is the simulation node communicating to MC33665A and MC33775A with appropriate CAN or CAN FD messages on **CAN1** network. Based on Vector CAN hardware (such as VN1610), select the right CAN network in **Channels**, and select appropriate **CAN** network (CAN1 or CAN2 based on Vector CAN hardware).
- BMU node specification is preselected with CAPL file CCMU_Demoboard_RV1.0.can.




Figure 3. CANoe node configuration

- **NXP_BMS_QPHY_V1** database is connected to **Databases** in simulation setup to interpret the CAN or CAN FD messages. It supports both MC33665A (TPL2 and TPL3) and MC33775A (TPL3). NXP_BMS_QPHY_V1 database is compatible for CAN or CAN FD communication to MC33665ATF4AE with ID0_STB_OD, ID1, ID2, and ID3 pins set to zero.

5 Hardware setup

MC33665A_CCMU_Demo is built to work in CANoe from Vector. Demo can work with specific preconditions in hardware which are listed below.

- Vector CAN hardware tools (such as VN1610) must be interfaced to board which has MC33665A CAN (FD) variant (MC33665ATF4AE). **ID0_STB_OD, ID1, ID2, and ID3** pins of MC33665A must be set to zero.
- MC33665A_CCMU_Demo is compatible to support up to four MC33775A battery cell controller (BCC) devices on TPL port 0 of MC33665A.
- RD33775ACNCEVB can be used for the demo. If there is a customer-specific hardware based on MC33665A, check if CAN transceiver supports CAN FD baud rate requirements of MC33665A_CCMU_Demo.
- Before starting the demo, check the termination of CAN transceiver and make sure it is matching to the CAN bus impedance requirements (60 Ω).
- CFG0 and CFG1 pins on MC33665A must be aligned with setup in CANoe configuration.

Table 1. CFG pins of MC33665A

CFG1	CFG0	Data rate
0	0	250 kbit/s
0	1	500 kbit/s
1	0	1 Mbit/s
1	1	reserved

- Any changes to CFG0 and CFG1 pins on MC33665A should be reflected for CAN baud rate settings (shown in [Figure 4](#)) in CANoe workspace (MC33665A_CCMU_Demo_V2) → network hardware configuration. See [Table 1](#) and CFG0 and CFG1 pin settings of MC33665A on RD33775ACNCEVB before updating the **Network Hardware Configuration**.




Figure 4. CAN HW baud rate




Figure 5. CAN FD arbitration baud rate

MC33665A_CCMU_Demo can work with different CAN FD hardware settings (arbitration baud rate: set by CFG pins of MC33665A; data baud rate: 1 Mbit/s, 2 Mbit/s, 5 Mbit/s possible to set in CCMU panel).




Figure 6. CANoe CCMU setup

- [Figure 6](#) shows the block diagram of setup for MC33665A_CCMU_Demo with CCMU board. RD33775ACNCEVB also known as CCMU can be interfaced from laptop with Vector CAN hardware (such as VN1610).
- Cell interface connections can be connected to external cell emulators.
- Check the voltages of CFG0, CFG1, ID0_STB_OD, ID1, ID2, ID3 pins of MC33665A populated on the RD33775ACNCEVB before starting the demo.
- Install 120 Ω resistor for CAN communication in above setup. Ignore the same if there is an additional termination in network which is not part of the setup shown above.
- To set up and run the demo, follow the safety precautions guided by lab manager or supervisor.
- Follow the user manual of boards for setup and smooth operation of demo.

6 Running CANoe demo

MC33665A_CCMU_Demo can be run from a PC or laptop which is installed with CANoe (as per prerequisites specified in [Section 3](#)). Make sure that the relevant hardware is available with interconnection guidelines of boards. Follow below **steps** in installing and running the MC33665A_CCMU_Demo.

1. Set up the PC or laptop which is used to install and run the MC33665A_CCMU_Demo. Complete the procedure specified in [Section 4](#) before starting the MC33665A_CCMU_Demo.
2. Set up the hardware as specified and shown in [Section 5](#). Make sure that the preconditions of hardware setup are done appropriately before finalizing and running the setup. Power on the hardware by checking the interconnections of setup.
 - a. Vector HW USB to PC → DB-9 connector CAN interface to RD33775ACNCEVB
 - b. Power supply (12 V/20 W) to BATT-14CEMULATOR → cell interface connection of BATT-14CEMULATOR to BATT-14EXTENDER → four cell interface cables from BATT-14EXTENDER to RD33775ACNCEVB
3. Start CANoe installed in PC or laptop. Set up the workspace as described in [Section 4](#). Set up the CAN channel as per the Vector CAN hardware (VN1610 as shown in [Figure 7](#)) connected to board populated with MC33665A CAN (FD).
4. Open the hardware → network hardware to set the initial baud rate for CAN communication matching to CFG0 and CFG1 settings of MC33665A in RD33775ACNCEVB




Figure 7. Initial CAN settings

5. Click the 'Start' button on left top corner of CANoe tool to run the initial configuration of MC33665A with CAN and set the CAN FD baud rate. Initial settings for CAN FD data baud rate to MC33665A is set as 2 Mbit/s. CFG0 and CFG1 pins of MC33665A sets arbitration baud rate for CAN FD.
6. Update the initial CAN FD settings in CANoe. Select the **Hardware** → click **Network Hardware** → change the mode to **ISO CAN FD** and update the data rate to **2000 kBd** → press **OK**




Figure 8. Initial CAN FD settings

- Click the **START** button to run the setup in CAN FD with updated data baud rate settings. CAN or CAN FD traffic can be monitored and logged using 'Trace' window as shown in [Figure 11](#)
- Panels can be used to visualize the data from RD33775ACNCEVB to run and control the MC33665A_CCMU_Demo. Select **Home** → click **Panel** drop down menu → select and click **Add Panel** → select the location of files stored in [Figure 1](#) → open **Panels** folder → select the **NXP_CCMU_CANFD** → press **Open**




Figure 9. CCMU panel

- CCMU panel** gives overview of CAN bus statistics, with two demo sequences and update CAN FD settings. VC0 to VC13 primary cell voltages of MC33775A can be

seen as Cell 1 to Cell 14 on the CCMU panel. AN0 and AN1 of MC33775A can be seen as Temp 1 and Temp 2 on the panel.

10. As shown in CCMU panel (Modes / Config) in [Figure 9](#), demo can run in two sequences to communicate and monitor the onboard MC33775A battery cell controllers. **Apps + Sync + Diag + Balancing** is a sequence which executes application measurements of primary cell voltages, sync measurements of both primary cell voltages and secondary cell voltages, overvoltage and undervoltage measurements along with balancing of cells for every **100 ms**. **Apps Meas + Diagnosis** is a sequence which runs for every **25 ms** to run and update application measurements of primary cell voltages with undervoltage, overvoltage measurements of four MC33775A battery cell controllers.
11. **CAN Load (%)** gives a reference for bus loading on CAN bus used for communication (channels CAN1 or CAN 2) calculated by CANoe tool. **Standard Data** (total) gives the log of complete CAN/CAN FD messages on bus.
12. CAN FD communication from CANoe to RD33775ACNCEVB can be done at different data baud rates. Enter the appropriate data speeds (1 Mbit/s, 2 Mbit/s or 5 Mbit/s) in CCMU panel. Press **CAN FD Speed** button to update the settings from CANoe (CCMU panel) to MC33665A on RD33775ACNCEVB. Note: Demo stops running while updating CAN FD speed to MC33665A.
13. Update the same data speed entered on CCMU panel to CANoe configuration. Select **Hardware** → press **Network Hardware** → update **Data rate** same as provided in CCMU panel → click **OK** → press the **START** in CANoe or on panel to resume the demo at updated CAN FD baud rates.
14. **Analysis** tab in MC33665A_CCMU_Demo_V2 gives options to analyze the traffic to evaluate the performance of MC33665A and MC33775A.




Figure 10. CCMU demo analysis

15. **Graphics** and **Data** windows offer different visualization and facilities to log the cell voltages and temperatures from MC33775A. **CAN Statistics** window provides the information of CAN bus performance based on CANoe features and configuration. Key pointers to check are Busload (%) and types of requests made in BMU with relevant responses from MC33665A.

16. BATT-14CEMULATOR can be used effectively to emulate the cell voltage behavior which can be visualized in Graphics window (data extracted from MC33775A and MC33665A).
17. **Trace** window in CANoe offers to see the log of CAN or CAN FD messages on the selected CAN channel (CAN1 or CAN2).




Figure 11. CCMU demo trace window

18. [Figure 11](#) shows the data for cell voltages for a given CADD, DADD, RADD, MADD, and relevant TPL message information. Trace window is used to check the timing of requests and responses from MC33665A.
19. **Device** panel can be used to see the performance of individual MC33775A. Select **Home** → click **Panel** drop down menu → select and click **Add Panel** → select the location of files stored in [Figure 1](#) → open **Panels** folder → select the **NXP_Device_Panel** panel file → press **Open**




Figure 12. Device panel

20. Enter the device address 1 to 4 in order to monitor the respective MC33775A populated on RD33775ACNCEVB. Note: In RD33775ACNCEVB, typically device address is allocated sequentially to MC33775A connected on TPL port 0 of MC33665A. First MC33775A connected on TPL port 0 of MC33665A is assigned with device address 1 whereas the last onboard device has device address 4. In case of ongoing demo session press the **STOP** button and press the **START** button to update the panel with new device address, else press **START** button to run the **Device** panel with new device address.
21. Selected primary cell voltages and secondary cell voltages are updated in the **Device** panel based on refresh rate selected on CCMU panel.
22. **Device Panel** provides an option to perform the balancing function in MC33775A selected in device address. Enter the number (limited to single digit for demo) in 'Balancing Timer'. If the entered value is **1**, the respective balancing resistor is on for 10 s (multiplication factor for balancing timer for a respective balancing control cell).
23. Enter the number (limited to single digit for demo) in balancing timer for respective cells → press **Timer** or **PWM 50 %** to start the balancing function of a particular cell selected for MC33775A. **Timer** function gives a command for **ALWAYS ON** until the timer runs out, whereas **PWM 50 %** turns on balancing resistor with 50 % duty cycle until the timer runs out.
24. Cell undervoltage and overvoltage flags of a selected MC33775A are read and updated in **Device Panel** in Cell Controller Error Status section.
25. **Important:** Upon **Reset** or **Power ON** of RD33775ACNCEVB during the running session of the demo, start the MC33665A_CCMU_Demo procedure from step 4 and continue at least until step 6 to set up the initial configuration and update settings to MC33665A (the initial data settings for CAN FD is 2 Mbit/s)

7 References

- [1] Product summary page for MC33665A <http://www.nxp.com/MC33665A>
- [2] Product summary page for TJA144x <http://www.nxp.com/TJA144x>

8 Legal information

8.1 Definitions

Draft — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

8.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Terms and conditions of commercial sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

Suitability for use in automotive applications — This NXP product has been qualified for use in automotive applications. If this product is used by customer in the development of, or for incorporation into, products or services (a) used in safety critical applications or (b) in which failure could lead to death, personal injury, or severe physical or environmental damage (such products and services hereinafter referred to as "Critical Applications"), then customer makes the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, safety, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP. As such, customer assumes all risk related to use of any products in Critical Applications and NXP and its suppliers shall not be liable for any such use by customer. Accordingly, customer will indemnify and hold NXP harmless from any claims, liabilities, damages and associated costs and expenses (including attorneys' fees) that NXP may incur related to customer's incorporation of any product in a Critical Application.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Evaluation products — This product is provided on an "as is" and "with all faults" basis for evaluation purposes only. NXP Semiconductors, its affiliates and their suppliers expressly disclaim all warranties, whether express, implied or statutory, including but not limited to the implied warranties of non-infringement, merchantability and fitness for a particular purpose. The entire risk as to the quality, or arising out of the use or performance, of this product remains with customer.

In no event shall NXP Semiconductors, its affiliates or their suppliers be liable to customer for any special, indirect, consequential, punitive or incidental damages (including without limitation damages for loss of business, business interruption, loss of use, loss of data or information, and the like) arising out of the use of or inability to use the product, whether or not based on tort (including negligence), strict liability, breach of contract, breach of warranty or any other theory, even if advised of the possibility of such damages.

Notwithstanding any damages that customer might incur for any reason whatsoever (including without limitation, all damages referenced above and all direct or general damages), the entire liability of NXP Semiconductors, its affiliates and their suppliers and customer's exclusive remedy for all of the foregoing shall be limited to actual damages incurred by customer based on reasonable reliance up to the greater of the amount actually paid by customer for the product or five dollars (US\$5.00). The foregoing limitations, exclusions and disclaimers shall apply to the maximum extent permitted by applicable law, even if any remedy fails of its essential purpose.

Safety of high-voltage evaluation products — The non-insulated high voltages that are present when operating this product, constitute a risk of electric shock, personal injury, death and/or ignition of fire. This product is intended for evaluation purposes only. It shall be operated in a designated test area by personnel that is qualified according to local requirements and labor laws to work with non-insulated mains voltages and high-voltage circuits.

The product does not comply with IEC 60950 based national or regional safety standards. NXP Semiconductors does not accept any liability for damages incurred due to inappropriate use of this product or related to non-insulated high voltages. Any use of this product is at customer's own risk and liability. The customer shall fully indemnify and hold harmless NXP Semiconductors from any liability, damages and claims resulting from the use of the product.

Translations — A non-English (translated) version of a document, including the legal information in that document, is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Security — Customer understands that all NXP products may be subject to unidentified vulnerabilities or may support established security standards or specifications with known limitations. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately.

Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP.

NXP has a Product Security Incident Response Team (PSIRT) (reachable at PSIRT@nxp.com) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

8.3 Trademarks

Notice: All referenced brands, product names, service names, and trademarks are the property of their respective owners.

NXP — wordmark and logo are trademarks of NXP B.V.

Tables

Tab. 1. CFG pins of MC33665A7

Figures

Fig. 1.	MC33665A_CCMU_Demo files	4	Fig. 7.	Initial CAN settings	10
Fig. 2.	MC33665A_CCMU_Demo workspace	5	Fig. 8.	Initial CAN FD settings	11
Fig. 3.	CANoe node configuration	6	Fig. 9.	CCMU panel	11
Fig. 4.	CAN HW baud rate	7	Fig. 10.	CCMU demo analysis	12
Fig. 5.	CAN FD arbitration baud rate	8	Fig. 11.	CCMU demo trace window	13
Fig. 6.	CANoe CCMU setup	8	Fig. 12.	Device panel	14

Contents

1 Important notice3

2 Introduction3

3 Demo prerequisites4

4 Software setup4

5 Hardware setup6

6 Running CANoe demo9

7 References15

8 Legal information16

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.