NOTES (UNLESS OTHERWISE SPECIFIED):

1. THIS DRAWING SPECIFIES THE REQUIREMENTS FOR A PRINTED WIRING BOARD IN ACCORDANCE WITH SPECIFICATION IPC-A-600 CLASS 2 (LATEST REVISION).
2. THE PWB MUST BE LEAD FREE ASSEMBLY PROCESS COMPATIBLE AND MUST BE ABLE TO HANDLE A MINIMUM OF 5 CYCLES AT 260 DEGREES CELSIUS FOR 10 SECONDS.
3. BASE MATERIAL - LAMINATE AND PREPREG SHALL MEET IPC-4101B-26, 83 or 98
   Tg - MUST BE GREATER THAN OR EQUAL TO 150 DEGREES CELSIUS.
   Td - MUST BE GREATER THAN OR EQUAL TO 330 DEGREES CELSIUS.
4. COPPER FOIL WEIGHT - SEE STACKUP DETAIL 'A'
5. CHARACTERISTIC IMPEDANCE - SEE DETAIL 'B'
6. MINIMUM CONDUCTIVE WIDTH/SPACING TO BE .004"/.00425"
7. PLATING FINISH a. BOTH SIDES ENIG (ELECTROLESS NICKEL IMMERSION GOLD):
   .05080-.232 MICRON (2-8 MICROINCH) OF GOLD OVER
   2.540-6.350 MICRON (100-250 MICROINCH) OF NICKEL.
   b. THE PCI CARD EDGE CONNECTOR GOLD FINGERS, PLATING REQUIREMENTS:
   30U OVER HARD GOLD OVER 100~200U NICKEL BOTH SIDES OF THE BOARD.
8. ALL THROUGH HOLE VIAS MAY BE PLATED SHUT.
9. SOLDERMASK - GREEN COLOR (TAIYO OR EQUIVALENT), BOTH SIDES.
   MODIFICATION OF SOLDERMASK IS NOT ALLOWED WITHOUT WRITTEN PERMISSION FROM NXP.
10. SILKSCREEN - WHITE EPOXY INK, BOTH SIDES. NO SILK ON PADS.
11. ELECTRICAL TEST - 100% IPCD356.
12. PRINTED WIRING BOARD IS TO BE INDIVIDUALLY BAGGED.
13. DRC'S MUST BE RUN ON THE GERBER BEFORE BUILDING BOARDS, UNLESS PRIOR APPROVAL IS GIVEN IN WRITING BY NXP.
14. TEARDROPS MAYBE ADDED AT THE FAB HOUSE TO ALL SIGNAL LAYERS.
15. TWO SOLDER SAMPLES TO BE PROVIDED.
16. BASIC GRID INCREMENT AT 1:1 IS .0001.
17. SUPPLIER MARKINGS - ON SOLDER SIDE ONLY, WHERE SHOWN.
   - MUST BE UL RECOGNIZED AND MUST HAVE AN ID THAT CONFORMS TO UL94V-0
18. THE PWB WILL BE MARKED AS LEAD FREE BY USE OF AN INK STAMP (P6)
19. THE PWB WILL BE MARKED AS LEAD FREE PROCESS COMPATIBLE BY USE OF AN INK STAMP (260°C)
20. ALL PLATED AND NON-PLATED THROUGH HOLES ARE TO BE DRILLED AT PRIMARY DRILL STEP.
   ALL HOLE LOCATION TOLERANCES ARE TO BE +/-.002 IN REFERENCE TO THE PRIMARY DATUM.
21. FINISHED PCB MUST BE PANELIZED FOR ASSEMBLY ACCORDING TO CONTRACT MANUFACTURERS REQUIREMENTS.
   THE ADDITION OF RAILS AND .125"NON-PLATED TOOLING HOLES ARE AT THE DISCRETION OF
   CONTRACT MANUFACTURER.PANELIZATION MUST BE APPROVED BY CONTRACT MANUFACTURER.
22. THIS BOARD USES VIA-IN-PAD:
   A. VIA-IN-PAD TO BE FILLED WITH NON-CONDUCTIVE VIA FILL.
      LACKWERKE-PETERS PP2795 OR EQUIVALENT AND MADE PLANAR TO THE PADS.
   B. OVERPLATE THE FILLED VIA AND APPLY FINISH METAL TREATMENT.
23. THE MANUFACTURE HAS THE OPTION TO ADD COPPER THIEVING ON OUTER AND INNER LAYERS, KEEP A MINIMUM DISTANCE OF .100" FROM ANY BOARD FEATURES.

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	A	ORIGINAL RELEASE	11-09-15	G.R.R.M.C.
	B	RE-SPIN PER ECOXXX	06-15-16	A.M.



DETAIL C
SCALE: NONE





VIEW FROM PRIMARY SIDE

DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
8 ⑧	8.0	+0.0/-8.0	PLATED	335
22 ⑪	8.1	+0.0/-8.0	PLATED	52
②	28.0	+2.0/-2.0	PLATED	20
④	40.0	+3.0/-3.0	PLATED	43
4	41.0	+3.0/-3.0	PLATED	18
④	47.0	+2.0/-2.0	PLATED	20
④	48.0	+3.0/-3.0	PLATED	30
⚠	63.0	+3.0/-3.0	PLATED	2
⊕	35.0	+2.0/-2.0	NON-PLATED	2
⑧	81.0	+2.0/-2.0	NON-PLATED	8
②	110.0	+2.0/-2.0	NON-PLATED	8
◯	63.0x52.0	+3.0/-3.0	PLATED	1
○	63.0x52.0	+3.0/-3.0	PLATED	2

DETAIL B
IMPEDANCE REQUIREMENTS
IMPEDANCE TOLERANCE IS 10%

	Single Ended		Differential		
Layers	Trace Width (Mils)	Impedance (Ohms)	Trace Width (Mils)	Trace Spacing "Airgap" (Mils)	Impedance (Ohms)
L1_PS	5.00	50	4.25	4.50	90
L3_INT_1	5.00	50	4.25	4.50	90
L4_INT_1	5.00	50			
L6_SS	5.00	50	4.25	4.50	90

FINISHED Cu WEIGHT



LAYER 1	COMPONENT SIDE	1/2 to 1 oz.
LAYER 2	POWER PLANE	1 oz.
LAYER 3	INTERNAL 1	1/2 oz.
LAYER 4	INTERNAL 2	1/2 oz.
LAYER 5	GROUND PLANE	1 oz.
LAYER 6	SOLDER SIDE	1/2 to 1 oz.

DETAIL A
LAYER STACKUP
SCALE: NONE

--- PUBI (PUBLIC INFORMATION)
X IUO (NXP INTERNAL USE ONLY)
--- CP (NXP CONFIDENTIAL PROPRIETARY)

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO NXP AND SHALL NOT BE USED FOR ENGINEERING DESIGN PROCUREMENT OR MANUFACTURE IN WHOLE OR IN PART WITHOUT THE CONSENT OF NXP.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES [MM]
TOLERANCES ARE:
DECIMALS ANGLES
.XX .01 ±0-30'
.XXX .005
✓ RMS ALL MACHINED SURFACES
BREAK ALL SHARP EDGES AND CORNERS.
REMOVE BURRS.
UNDERLINED DIM. NOT TO SCALE.
THIRD ANGLE ORTHOGRAPHIC PROJECTION IS USED.

APPROVALS	DATE
DRAWN neuronPro-RCC02C	06-15-16
CHECKED JORGE MANUEL R.	06-15-16
DESIGN ENGINEER TOMAS MAREK	06-15-16

PART NO. 170-29083

NXP SEMICONDUCTORS
6501 WILLIAM CANNON DRIVE WEST AUSTIN, TEXAS 78735 USA

TITLE: PRINTED WIRING BOARD
TWR-CM3120-EVM

SIZE	CAD FILE NAME	DWG. NO.	REV
D	LAY-29083	FAB-29083	B

SCALE: DO NOT SCALE DRAWING SHEET 1 OF 1